



	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH-2WIRE-A-SET 2 PCS SET ATTE	IP CAMERA BCS-L-EIP44VSR4-AI1 - 4 Mpx 2.7 ... 13.5 mm - MOTOZOOM BCS Line
		
	469.00 PLN 469.00 PLN	1429.00 PLN 1429.00 PLN
Standard	...	IP
Connectors	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG) 	...
LAN ports	1 pcs RJ45 10 / 100 Mbps	...
Resolution	...	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Sensor	...	1/2.9 " Progressive Scan CMOS
Lens	...	2.7 ... 13.5 mm @ F1.5 - Motozoom
View angle	...	104 ° ... 29 °
Range of IR illumination	...	40 m
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Terminals	<p>ETH-2WIRE-A-TX :</p> <ul style="list-style-type: none"> • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W (" +/-": 1, 2 pins; "+/-": 3, 6 pins) or (" +/-": 4, 5 pins; "+/-": 7, 8 pins) • Power • DATA - 2-wire <p>ETH-2WIRE-A-RX :</p> <ul style="list-style-type: none"> • PoE OUT - Hi-PoE (802.3af/at/bt) ("+": 3, 6 / 4, 5 pins; "-": 1, 2 / 7, 8 pins) • Power • DATA - 2-wire 	...
Transmission speed	10 / 100 Mbps	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	Microphone built-in
Main stream frame rate	...	25 fps @ 4 Mpx
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in

Max. number of on-line users	...	20
ONVIF	...	✓
Transmission range	<ul style="list-style-type: none"> • 300 m @ 100 Mbps : 2-wire, • 800 m @ 10 Mbps : 2-wire • 100 m @ UTP : Switch PoE - ETH-2WIRE-A-TX • 100 m @ UTP : ETH-2WIRE-A-RX - IP Camera 	...
Intelligent image analysis	...	<ul style="list-style-type: none"> • intrusion - classification of people and vehicles • crossing the line (tripwire) - classification of people and vehicles
LED indicators	<ul style="list-style-type: none"> • Power • LAN (RJ-45) • PoE (RJ-45) • 2-wire • 2-wire 10 Mbps • LV - low voltage < 44 V 	...
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • AGC - Automatic Gain Control • AES - Auto Electronic Shutter • Image rotation and mirror • ICR - Movable InfraRed filter • Day/night mode • AWB - Auto White Balance • Motion Detection - max. 4 zones • Privacy zones - max. 4 • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • D-ZOOM - Digital Zoom : 16 x
Protections	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH-2WIRE-A-TX 	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default IP address	...	192.168.1.108
Main features	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks 	...
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777

Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Power supply	ETH-2WIRE-A-TX : • 24 ... 56 V DC - PoE • 12 ... 56 V DC - Power ETH-2WIRE-A-RX : • 44 ... 56 V - Power • The output PoE voltage is equal to the input voltage	• PoE (802.3af), • 12 V DC / 500 mA
Power consumption	1.35 W (total)	max. 6 W
Housing	Plastic (polycarbonate)	Dome - Metal
Color	...	White
"Index of Protection"	IP20	IP67
Mechanical protection class	...	—
Operation temp	-25 °C ... 65 °C	...
Operation temp	...	-30 °C ... 60 °C
Weight	0.028 kg (single element)	0.69 kg
Dimensions	73 x 51 x 23 mm (single element)	Ø 122 x 108 mm
Supported languages	...	Polish, English
Manufacturer / Brand	ATTE	BCS Line
Guarantee	3 years	3 years

