



|                               |   |  |
|-------------------------------|---|--|
|                               | <a href="#">ACCESS POINT 4G LTE +ROUTER ARCHER-MR200 2.4 GHz, 5 GHz 433 Mbps + 300 Mbps TP-LINK</a> | <a href="#">IP DECODER NVD0905DH-4I-4K - 12 Mpx, 4K</a>  |
|                               |                    |    |
|                               | 354.87 PLN<br>354.87 PLN  | 17275.00 PLN<br>17275.00 PLN   |
| Frequency range               | 2.4 GHz ,<br>5 GHz  | ...  |
| Antenna type                  | 3 x WiFi - built-in ,<br>2 x 4G LTE   | ...  |
| Standards                     | IEEE 802.11 b/g/n, IEEE<br>802.11 a/n/ac, IEEE<br>802.3/3u  | ...  |
| Supported resolutions         | ...   | 9 Channels @ 4000 x<br>3000 px - 12 Mpx ,<br>9 Channels @ 3840 x<br>2160 px - 4K ,<br>36 Channels @ 1920 x 1080<br>- 1080p ,<br>81 Channels @ 1280 x 720 -<br>720p ,<br>144 Channels @ 704 x 576 -<br>D1 |
| Number of supported screens   | ...   | 9 pcs  |
| Baud rates                    | • 5 GHz : 433 Mbps (max) +<br>2.4 GHz : 300 Mbps (max)<br>• LTE : 150 Mbps                          | ...  |
| Video inputs                  | ...   | • 2 x HDMI 4K<br>• 2 x DVI   |
| Video outputs                 | ...   | 9 x HDMI   |
| Audio outputs                 | ...   | HDMI   |
| Network interface             | ...   | 2 x RJ45 10/100/1000 Base-T  |
| Default IP address            | ...   | 192.168.1.108  |
| Modulation type               | DBPSK, DQPSK, CCK<br>OFDM, 16-QAM, 64-QAM   | ...  |
| Default admin user / password | ...   | admin / -  |
| LAN ports                     | • 1 x 10/100 Mbps -<br>LAN/WAN<br>• 3 x 10/100 Mbps - LAN   | ...  |
| Serial ports                  | ...   | • 2 pcs RS-232 @ RJ45<br>• 1 pcs RS-232 @ D-Sub<br>• 1 pcs RS-485  |

|                               |   |                           |
|-------------------------------|---|---------------------------|
| Alarm inputs / outputs        | ...   | 4 / 4                     |
| Power consumption             | ...   | ≤ 70 W                    |
| Receiver sensitivity          | 5 GHz :<br>• 11a 54M: -74dBm<br>• 11ac HT20: -67dBm<br>• 11ac HT40: -64dBm<br>• 11ac HT80: -60dBm<br>• 11n HT20: -71dBm<br>• 11n HT40: -70dBm<br>2.4 GHz :<br>• 11g 54M: -76dBm<br>• 11n HT20: -73dBm<br>• 11n HT40: -67dBm | ...                       |
| LTE                           | ✓   | ...                       |
| QSS                           | ✓   | ...                       |
| WDS                           | ✓   | ...                       |
| Power supply                  | 12 V DC / 1 A (power adapter included)  | 230 V AC                  |
| Operation temp                | 0 °C ... 40 °C  | -10 °C ... 55 °C          |
| Permissible relative humidity | 95 % (non-condensing)   | ...                       |
| Main features                 | <ul style="list-style-type: none"> <li>• SIM socket</li> <li>• WPS/RESET button</li> </ul>  | ...                       |
| Weight                        | 0.26 kg   | 4.70 kg                   |
| Dimensions                    | 202 x 163 x 34 mm   | 440 x 415 x 76 mm - 1.5 U |
| Manufacturer / Brand          | TP-LINK   | DAHUA                     |
| Guarantee                     | 3 years   | 3 years                   |