




	<a href="#">POWER DISTRIBUTION UNIT ACAR-DIGITAL (5 OUTLETS)</a>	<a href="#">IP CAMERA F4C-PV Wi-Fi, Smart Dual Light Active Deterrence - 3.7 Mpx 2.8 mm DAHUA</a>	<a href="#">IP VANDALPROOF CAMERA IPC3634SB-ADZK-I0-BLACK - 4 Mpx 2.7 ... 13.5 mm - MOTOZOOM UNIVIEW</a>
			
	230.34 PLN 230.34 PLN	189.00 PLN 189.00 PLN	1846.86 PLN 1846.86 PLN
Standard	...	IP	TCP/IP
Rated voltage	230 V AC / 50 Hz	...	...
Protection level	≤ 1.3 kV	...	...
Matrix size	...	...	4 Mpx
Nominal load current	10 A (total)	...	...
Maximal load power	2300 W	...	...
Nominal stroke current	2 kA (L/N) - 8/20 μs	...	...
Maximum stroke current	6.5 kA (L/N) - 8/20 μs	...	...
Leak current	< 0.5 mA	...	...
Automatic delayed fuse	✓	...	...
Response time	< 25 ns	...	...
Number of outlets	5 grounded outlets 16A/250V - (Schuko)	...	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Switch	Two-way switch - with light indication	...	...
Sensor	...	1/3 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Lens	...	2.8 mm	2.7 ... 13.5 mm - Motozoom, AutoFocus
White light LED illuminator range	...	30 m	...
S/N ratio	...	> 56 dB	...
View angle	...	98 °	• 98 ° ... 31 ° (manufacturer data) • 100 ° ... 28 ° (our tests result)
Range of IR illumination	...	30 m	40 m
RS-485 interface	...	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—	—
Audio	...	• Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support • Audio output • Audio detection	• Microphone built-in • Audio transmission via network • Audio detection
Length of the cable	3 m	...	...
Main stream frame rate	...	25 fps @ 4 Mpx	25 fps @ 4 Mpx
Network interface	...	• Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz, • 10/100 Base-T (RJ-45)	10/100 Base-TX (RJ-45)
Network protocols	...	...	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, SSL / TLS, SSH
WEB Server	...	Built-in	Built-in
Max. number of on-line users	...	6	32
ONVIF	...	✓	✓
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>	Access by a cloud (P2P) • Android: Free application <a href="#">EZView</a> • iOS (iPhone): Free application <a href="#">EZView</a>
Default IP address	...	192.168.1.108	DHCP or 192.168.1.13

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: [info@delta.poznan.pl](mailto:info@delta.poznan.pl)  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	...	admin / - The administrator password should be set at the first start	admin / 123456
Web browser access ports	...	80, 37777	80, 554
PC client access ports	...	37777	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	37777	80
Port ONVIF	...	80	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> <li>• Easily readable LCD with backlight displaying detailed information on system state,</li> <li>• Supply voltage measurement : 80 V ... 250 V @ 50Hz,</li> <li>• Supply current measurement : 0.01 A ... 10 A @ 50/60 Hz,</li> <li>• Power measurement : 1 W ... 2500 W,</li> <li>• Energy measurement : 1 Wh ... 9999 Wh</li> <li>• Energy meter reset</li> <li>• Setting the alarm after exceeding the power consumption</li> </ul>	<ul style="list-style-type: none"> <li>• Active deterrence function</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Motion Detection - max. 4 configurable zones - Human detection</li> <li>• Privacy zones - max. 4</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Vertical or horizontal image mirror</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Privacy zones - max. 4</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, people counting , crowd gathering estimation</li> </ul>
Power supply	...	12 V DC / 550 mA	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 580 mA</li> </ul>
Power consumption	...	≤ 6.6 W @ 12 V DC	≤ 7 W
Housing	Plastic - non-flammable	Compact - Plastic	Dome - Metal
Color	...	White + Black	Black
"Index of Protection"	...	IP67	IP67
Vandal-proof	...	—	IK10
Operation temp	...	-40 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.65 kg	0.25 kg	0.69 kg
Dimensions	447 x 57 x 43 mm	131 x 78 x 97 mm	Ø 129 x 110 mm
Supported languages	...	Polish, English	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	...	DAHUA	UNIVIEW
Guarantee	2 years	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00