



	IP CAMERA IPC2124LE-ADF40KM-G - 4 Mpx 4 mm UNIVIEW	AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H24M-36 - 1080p 4 mm
		
	642.51 PLN 642.51 PLN	168.00 PLN 168.00 PLN
Standard	TCP/IP	AHD / HD-CVI / HD-TVI / PAL
Sensor	1/3 " Progressive Scan CMOS	1/2.8 " Sony CMOS - STARVIS Back-illuminated
Matrix size	4 Mpx	2.1 Mpx
Range of IR illumination	50 m	...
S/N ratio	> 52 dB	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	• 1920 x 1080 - 1080p, AHD / HD-CVI / HD-TVI, • 1280 x 720 - 720p / AHD / HD-CVI / HD-TVI, • 960 x 576 - 960H, PAL
Lens	4 mm	4 mm
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
View angle	• 84 ° (manufacturer data) • 80 ° (our tests result)	• 72 ° (manufacturer data) • 80 ° (our tests result)
Min. illumination	...	0.001 Lux
Main stream frame rate	25 fps @ 4 Mpx	...
Video output	...	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL
Network interface	10/100 Base-T (RJ-45)	...
Audio	• Microphone built-in • Audio transmission via network • Audio detection	—
OSD menu	...	✓
Application	...	The camera is designed for indoor use, due to the possibility of steam condensation.

Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL / TLS, QoS, IEEE 802.1x, SNMP	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette) 	<ul style="list-style-type: none"> • WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • White Balance - ATW/Manual • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto)

Power supply	• PoE (802.3af), • 12 V DC / 540 mA	12 V DC / 120 mA
Power consumption	≤ 6.5 W	...
Housing	Compact, Metal + Plastic	Mini, Metal
Color	White	Black
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	-10 °C ... 50 °C
Weight	0.43 kg	0.03 kg
Dimensions	190 x 73 x 71 mm	30 x 30 x 29 mm (without bracket)
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, French, Spanish, Japanese, Portuguese, Russian, Italian
Manufacturer / Brand	UNIVIEW	APTI
Guarantee	3 years	2 years