




	ACCESS CONTROL PANEL CPR32-NET-BRD ROGER	NVR NVR5432-EI 32 CHANNELS +eSATA WizSense DAHUA	FLUSH BOX 2-GANG SE-2X60-G SIMET
			
	1350.05 PLN 1350.05 PLN	5012.00 PLN 5012.00 PLN	38.47 PLN 38.47 PLN
Standard	...	TCP/IP	...
Supported resolutions	...	max. 32 Mpx	...
Number of sections	2
"Index of Protection"	IP20
Inputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 32
Video outputs	...	2 pcs HDMI 4K 2 pcs VGA	...
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Outputs	<ul style="list-style-type: none"> • 6 pcs - Transistor outputs • 2 pcs - Relay outputs NO/NC
Audio inputs	...	1 pcs CINCH	...
Communication	<ul style="list-style-type: none"> • 2 x RS-485
Audio outputs	...	2 pcs CINCH	...
Events memory	<ul style="list-style-type: none"> • Events saving to the micro SD card (not included) • Recording up to 240 000 events from the control panel
Image compression method	...	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG	...
Bitrate	...	max. 384 Mbps	...
Material	halogen free and inflammable
Color	Blue
Supported hard drives	...	4 x 16 TB SATA + 1 x eSATA	...
Recording modes	...	Manual, Sensor, Motion detection, Schedule	...
Mounting holes distance	60 mm
Output load	<ul style="list-style-type: none"> • Transistor outputs : 1 A / 15 V DC • Relay outputs : 1.5 A / 30 V DC
External storage devices backup	...	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	...	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 32 channels in the same time @ 1080p (without AI) • Records playback from max. 24 channels in the same time @ 1080p (AI) 	...
Network interface	...	2 x RJ-45 10/100/1000 Base-TX	...

Main features	<ul style="list-style-type: none"> • Ability to block/unblock partition at a specified time, or as per access schedule, • Central management of the access control system, • Integration with the alarm system SATEL INTEGRA, • History of 250 000 events • Electrical protection of all inputs and outputs as well as communication buses • Full support via network 	...	<ul style="list-style-type: none"> • Flush-mounted, serial, deep, for special electrical and electronic equipment • The ability to combine boxes • flammability index : 960 °C • 4 fixing points • 2 Mounting screws - included • Guides for attaching the TS35 rail
Network functions	...	Full support via network, Remote records copying, Web-Server built-in	...
Battery backup support	✓
Permissible relative humidity	10 % ... 95 % (non-condensing)
Network protocols	...	HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, SNMP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, PPPoE, FTP, DDNS, Alarm Server, IP Search, Multicast, P2P, Auto Register	...
ONVIF	...	21.12	...
Default IP address	...	192.168.1.108	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application	...
Web browser access ports	...	80, 37777	...
PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream 	...
USB	...	1 pcs USB 2.0 2 pcs USB 3.0	...
Serial ports	...	RS-485, RS-232	...
Alarm inputs / outputs	...	16 / 6	...
PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others 	...
Motion Detection	...	✓	...
Intelligent image analysis	...	✓	...



Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, face detection • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Face recognition • Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Support for up to 20 face databases, including 20 000 face images • In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number • Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity • Privacy zones • Cooperation with POS (Point of Sale) terminals • Working in a cluster <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) 	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Power supply	<ul style="list-style-type: none"> • 24 V DC • 12 V DC • 18 V AC 	100 ... 240 V AC @ 50 / 60 Hz	...
Power consumption	...	max. 13 W (without HDD)	...
Operation temp	5 °C ... 40 °C	-10 °C ... 55 °C	...
Weight	0.15 kg	4.42 kg	0.065 kg
Dimensions	175 x 81 x 50 mm	440 x 415 x 76 mm	153 x 82 x 82 mm
Supported languages	...	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian	...
Manufacturer / Brand	ROGER	DAHUA	SIMET
Guarantee	3 years	3 years	2 years

