



	<a href="#">IP CAMERA TC-C35TS SPEC:I8/A/E/Y/M/H/2.7-13.5MM/V4.1 - 5 Mpx 2.7 ... 13.5 mm TIANDY</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16H8T- IT3F(2.8mm) - 5 Mpx Hikvision</a>
		
	1768.00 PLN 1768.00 PLN	489.00 PLN 489.00 PLN
Standard	IP	AHD / HD-CVI / HD-TVI / CVBS
Matrix size	...	5.0 Mpx
Sensor	1/2.7 " Progressive Scan CMOS	Progressive Scan CMOS
RS-485 interface	✓	...
Memory card slot	Micro SD card support up to 512GB	...
Image compression method	S+265 / H.265 / H.264	...
Resolution	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	<ul style="list-style-type: none"> <li>• AHD / HD-TVI : 2560 x 1944 - 5 Mpx ,</li> <li>• AHD / HD-CVI / HD-TVI : 2560 x 1440 - 4 Mpx ,</li> <li>• HD-TVI : 1920 x 1080 - 1080p ,</li> <li>• CVBS : 960 x 576 - 960H</li> </ul>
Alarm inputs / outputs	2 / 1	...
Lens	2.7 ... 13.5 mm Motozoom	2.8 mm
View angle	98 ° ... 32 °	<ul style="list-style-type: none"> <li>• 98 ° (manufacturer data)</li> <li>• 95 ° (our tests result)</li> </ul>
Range of IR illumination	80 m	60 m
IR illuminator power adjustment	...	Automatic
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>,</li> <li>• Audio input</li> <li>• Audio output</li> <li>• Audio transmission via network</li> <li>• Bi-directional audio streaming support</li> <li>• Compliance with the AAC standard</li> </ul>	...
Main stream frame rate	<ul style="list-style-type: none"> <li>• 25 fps @ 5 Mpx</li> <li>• 50 fps @ 2 Mpx</li> </ul>	...
Interface	10/100 Base-TX (RJ-45)	...

Video output	...	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / CVBS, BNC socket
WEB Server	Built-in	...
Max. number of on-line users	2	...
OSD menu	...	OSD menu available via recorder
ONVIF	✓	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Default IP address	192.168.1.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...
PC client access ports	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> <li>• classification of people and vehicles</li> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• abandoned/missing object</li> <li>• illegal parking</li> <li>• people counting</li> <li>• detection of people gathering</li> <li>• heat map</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• protective helmet detection</li> <li>• detection of persons on duty</li> <li>• video tampering</li> </ul>	...
SAP Code	...	300510468

Main features	<ul style="list-style-type: none"> <li>• Motozoom lens</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Possibility to change the resolution, quality and bit rate</li> </ul>	<ul style="list-style-type: none"> <li>• WDR <math>\geq</math> 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ICR - Movable InfraRed filter</li> <li>• Mirror - Mirror image</li> <li>• BLC - Back Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 875 mA</li> </ul>	12 V DC / 480 mA
Power consumption	$\leq$ 10.5 W	$\leq$ 5.8 W
Housing	Compact - Metal	Compact, Metal + Plastic
Color	White	White + Black
"Index of Protection"	IP67	IP67
Mechanical protection class	—	...
Operation temp	-35 °C ... 65 °C	-40 °C ... 60 °C
Weight	1.15 kg	0.57 kg
Dimensions	265 x 105 x 105 mm	217 x 87 x 80 mm
Supported languages	Polish, English, Albanian, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Arabic, Vietnamese, German, Ukrainian, Portuguese	English
Manufacturer / Brand	TIANDY	Hikvision
Guarantee	3 years	3 years