





	SMART SWITCH ROW-04M Wi-Fi SUPLA ZAMEL	SMART SWITCH ROW-01 Wi-Fi 230 V AC ZAMEL	MULTI-PURPOSE AGENT K2-07/50ML SPRAY 50 ml K2
			
	406.25 PLN 406.25 PLN	217.80 PLN 217.80 PLN	5.40 PLN 5.40 PLN
Support	SUPLA	SUPLA	...
Package	Spray 50 ml
Number of inputs	4	2 pcs	...
Number of outputs	4
Number of pins	4 x NO/NC	1 x NO	...
Rated voltage	195 V ... 255 V AC	230 V AC	...
Total maximal current	5 A @ 250 V AC	5 A	...
Maximal total load	1250 VA	1250 VA	...
Application	Lighting control, switching devices on/off	Lighting control, switching devices on/off	<ul style="list-style-type: none"> • Elimination of squeaks, • Lubrication, • Removal of water, • Penetration, • Corrosion protection, • Surface preservation, • Removal of dirt
Maximal outputs load	<ul style="list-style-type: none"> • 750 W (single output) - light bulbs and halogen lamps • 250 W (single output) - CFL fluorescent lamps • 60 W (single output) - LED bulbs 	<ul style="list-style-type: none"> • 750 W (single output) - light bulbs and halogen lamps • 250 W (single output) - CFL fluorescent lamps • 60 W (single output) - LED bulbs 	...
Connector type	screw terminals	screw terminals	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Mobile phones support	<ul style="list-style-type: none"> • The SUPLA free application on Android • The SUPLA free application on iOS 	<ul style="list-style-type: none"> • The SUPLA free application on Android • The SUPLA free application on iOS 	...
Main features	<ul style="list-style-type: none"> • Control from a Web browser, • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API 	<ul style="list-style-type: none"> • Control from a Web browser, • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API 	<ul style="list-style-type: none"> • Spray formulation with a straw for easy application in hard-to-reach places • It can be used in any position, even upside down

Housing	Plastic, DIN, TS-35 rail mounting	Plastic	...
"Index of Protection"	IP20	IP20	...
Color	Green	Green	...
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C	...
Weight	0.117 kg	0.040 kg	0.05 kg
Dimensions	90 x 66 x 35 mm	47 x 47 x 20 mm	Ø 35 x 104 mm
Manufacturer / Brand	ZAMEL	ZAMEL	K2
Guarantee	2 years	2 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00