



	<a href="#">ACCESS POINT NS-5ACL(5-PAK) UBIQUITI 5 PCS SET</a>	<a href="#">CABLE PROTECTOR ATLO-KP-8X400</a>
		
	1316.40 PLN 1316.40 PLN	13.58 PLN 13.58 PLN
Material	...	Stainless steel
Color	...	Silver
In package	<b>5 pcs The price for package</b>	...
Frequency range	5150 MHz ... 5875 MHz 2412 MHz ... 2472 MHz	...
Antenna type	MIMO TDMA 13 dBi Integrated	...
Polarization	vertical/horizontal	...
Standards	<ul style="list-style-type: none"> <li>• IEEE 802.11a</li> <li>• IEEE 802.11n</li> <li>• IEEE 802.11ac</li> </ul>	...
VSWR	max. 1.8 : 1	...
LAN ports	1 x 10/100/1000 Mbps	...
Receiver sensitivity	<ul style="list-style-type: none"> <li>• -96 dBm ± 2 dB @ 1 x BPSK (1/2)</li> <li>• -95 dBm ± 2 dB @ 2 x QPSK (1/2)</li> <li>• -92 dBm ± 2 dB @ 2 x QPSK (3/4)</li> <li>• -90 dBm ± 2 dB @ 4 x 16-QAM (1/2)</li> <li>• -86 dBm ± 2 dB @ 4 x 16-QAM (3/4)</li> <li>• -83 dBm ± 2 dB @ 6 x 64-QAM (2/3)</li> <li>• -77 dBm ± 2 dB @ 6 x 64-QAM (3/4)</li> <li>• -74 dBm ± 2 dB @ 6 x 64-QAM (5/6)</li> <li>• -69 dBm ± 2 dB @ 8 x 256-QAM (3/4)</li> <li>• -65 dBm ± 2 dB @ 8 x 256-QAM (5/6)</li> </ul>	...
Operating system	AirOS	...
Operation modes	Access Point - Point to Point, Access Point - Point to Multi Point, Station - Point to Point, Station - Point to Multi Point	...

Protections	Overvoltage protection $\pm$ 24 kV Contact/Air (ESD/EMP)	...
Transmitter power	<ul style="list-style-type: none"> <li>• 25 dBm <math>\pm</math> 2 dB @ 1 x 8PSK (1/2)</li> <li>• 25 dBm <math>\pm</math> 2 dB @ 2 x Mbps QPSK (1/2)</li> <li>• 25 dBm <math>\pm</math> 2 dB @ 2 x QPSK (3/4)</li> <li>• 25 dBm <math>\pm</math> 2 dB @ 4 x 16-QAM (1/2)</li> <li>• 25 dBm <math>\pm</math> 2 dB @ 4 x 16-QAM (3/4)</li> <li>• 25 dBm <math>\pm</math> 2 dB @ 6 x 64-QAM (2/3)</li> <li>• 24 dBm <math>\pm</math> 2 dB @ 6 x 64-QAM (3/4)</li> <li>• 23 dBm <math>\pm</math> 2 dB @ 6 x 64-QAM (5/6)</li> <li>• 21 dBm <math>\pm</math> 2 dB @ 8 x 256-QAM (3/4)</li> <li>• 21 dBm <math>\pm</math> 2 dB @ 8 x 256-QAM (5/6)</li> </ul>	...
Horizontal beam width (H)	45 °	...
Vertical beam width (V)	45 °	...
Memory	64 MB DDR2	...
Processor	Atheros MIPS 74KC, 560MHz	...
Power supply PoE	✓	...
Power supply	24 V / 0.5 A - Gigabit PoE (power adapter not included)	...
Power consumption	7 W	...
Operation temp	-40 °C ... 70 °C	...
Permissible relative humidity	5 % ... 95 %	...
Main features	<ul style="list-style-type: none"> <li>• Throughput up to 450 Mbps</li> <li>• Range up to 10+ km</li> <li>• Channel bandwidths 10/20/30/40/50/60/80 MHz</li> <li>• Extra radio module for device management</li> <li>• The device is designed to work both inside and outside the building</li> <li>• Very easy and quick installation without any tools</li> <li>• It has a tight and UV-resistant housing</li> </ul>	Metal ends
Weight	0.177 kg	0.056 kg

Dimensions	179 x 78 x 59 mm	<ul style="list-style-type: none"> <li>• Ø 8 mm - Inner diameter,</li> <li>• Ø 11 mm - External diameter,</li> <li>• 400 mm - Length ( CABLE PROTECTOR )</li> <li>• 430 mm - Total length</li> </ul>
Manufacturer / Brand	UBIQUITI	...
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00