



	VIDEO OVERVOLTAGE LIMITER OPV-1LA	DVB-S/S2 DIGITAL RECEIVER OPTI-AX300-PLUS
		
	58.94 PLN 58.94 PLN	117.00 PLN 117.00 PLN
Input frequency	...	950 ... 2150 MHz
Input impedance	...	75 Ω
Standard	...	DVB-S, DVB-S2
Standard	<ul style="list-style-type: none"> • AHD - 5 Mpx • HD-CVI - 8 Mpx 4K UHD • HD-TVI - 5 Mpx • CVBS - PAL / NTSC 	...
Protected line	Coaxial	...
Threshold voltage	> 2.4 V	...
Maximum stroke current	5 kA (8/20μs)	...
Supported resolutions	...	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Response time	15 ns	...
Insertion loss	0.3 dB	...
Capacity	7 pF	...
Audio sampling	...	22.1 kHz, 32 kHz, 44.1 kHz, 48 kHz
Serial impedance per line	1 Ω (Wire)	...
Bandwidth	0 ... 140 MHz	...
Demodulation	...	QPSK, 8PSK, 16APSK, 32APSK
Grounding	Indirect, via inserted cable	...
Input socket type	BNC socket	...
Output socket type	BNC plug	...
Video format	...	4:3, 16:9
Length of grounding cable	0.5 m	...
Audio decoder	...	Dolby Digital (AC-3)
Permissible relative humidity	< 95 %	...
Video decoder	...	MPEG-2, MPEG-4 AAC, MPEG-4 HE-AAC, H.264
Power supply	...	12 V DC / 1 A (power adapter included)
Power consumption	...	max. 8 W (operation) < 1 W (in standby mode)

Connectors	...	<ul style="list-style-type: none"> • HDMI, • EURO (SCART), • "F" - LNB socket, • USB 2.0, • SPDIF
Main features	...	<ul style="list-style-type: none"> • Multimedia player • The USB port dedicated to external disks • DiSEqC 1.0, 1.2, 1.3, USALS, UNICABLE systems support • Teletext and screen text support • Electronic Program Guide - EPG • SD and HD quality channels
Operation temp	- 20 °C ... 55 °C	0 °C ... 40 °C
Weight	0.08 kg	0.25 kg
Dimensions	84 x 25 x 25 mm	180 x 130 x 40 mm
Supported languages	...	Polish, English, Danish, German, Russian, Slovenian, Swedish, Turkish
Manufacturer / Brand	DELTA	Opticum
Guarantee	3 years	2 years