



	SWITCH POE TL-SG3210XHP-M2 8-PORT SFP TP-LINK	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR XVR7108HE-4KL-I 8 CHANNELS DAHUA
		
	2227.42 PLN 2227.42 PLN	1642.00 PLN 1642.00 PLN
Standard	...	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs	...	8 pcs BNC
Video outputs	...	<ul style="list-style-type: none"> • 1 pcs HDMI 4K • 1 pcs VGA There is a possibility to configure a SPOT function on one of the output
Audio inputs	...	<ul style="list-style-type: none"> • 8 pcs CINCH, • 8 - Audio support via coaxial cable, HD-CVI only
Audio outputs	...	1 pcs CINCH
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 100/1000/2500 Base-TX, • 2 x port SFP+ - Uplink 1000 Base-X / 10 Gigabit Ethernet, • 1 x RJ45 - Console, • 1 x micro USB - Console 	...
Management	✓	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Number of compression levels	...	6
Transmission speed	<ul style="list-style-type: none"> • 100 / 1000 / 2500 Mbps - 8 LAN & PoE ports, • 10 Gb/s - 2 SFP ports 	...
Maximal output power	30 W / port PoE	...
Maximal total power	240 W	...
Jumbo Frame	9 kB	...
MAC addresses table	16k	...

Main features	<ul style="list-style-type: none"> • Omada Central Management System • Software Omada Controller • Support for Access Point Wi-Fi 6 • Switch is managed via a web browser, command line interface and SNMP, RMON protocols • CoS/DSCP priority based on IEEE 802.1p standard • Queue scheduling: SP, WRR, SP+WRR • Port/flow-based rate limiting • Static link aggregation • Spanning Tree STP/RSTP/MSTP • BPDU Filtering/Guard • TC / Root Protect • Loop back detection • Data Flow Control (802.3x) • Port mirroring function • IPTV compliance • IGMP Snooping V1/V2/V3 • MLD Snooping V1/V2 • IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • GVRP (GARP VLAN Registration Protocol) support • Access Control List - ACL package filtering based on source and destination MAC addresses • Hardware supports IP + MAC binding based on port • DHCP snooping support • Support DoS defence • Storm Control function • IEEE 802.1x and Radius Authentication • Port isolation • SSL, SSH • IPv6 compliance • Multicast • Static routing • DHCP server • DHCP client • System logs • Group control • Reboot schedule • MIB support • Console : RJ-45 output, micro USB 	
---------------	---	--



Image records resolutions	...	<ul style="list-style-type: none"> • HD-CVI : 8 Mpx - 3840 x 2160 , 6 Mpx - 2880 x 1920 4 Mpx - 2560 x 1440 1080p - 1920 x 1080 720p - 1280 x 720 • AHD : 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 3 Mpx - 2048 x 1536 1080p - 1920 x 1080 720p - 1280 x 720 • HD-TVI : 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 3 Mpx - 2048 x 1536 1080p - 1920 x 1080 720p - 1280 x 720 • CVBS : 960H - 960 x 576 • IP : max. 8.3 Mpx - 3840 x 2160 px
LED diodes	<ul style="list-style-type: none"> • Power, System, PoE Max, Fan • Link/Act • 100/1000 Mbps Speed, 2.5 Gb/s Speed - 1 ... 8 ports • 1 Gb/s Speed, 10 Gb/s Speed - 9, 10 ports • PoE, Over Budget, FAULT - 1 ... 8 ports 	...
Housing	Metal	...
Operation temp	0 °C ... 50 °C	...
Certificates	CE, FCC, RoHS	...
Recording speed adjustment	...	<ul style="list-style-type: none"> 8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 7 fps 6 Mpx @ 1 ... 10 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 3 Mpx @ 1 ... 15 fps 4M-N @ 1 ... 25 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Power consumption	max. 17.24 W @ 110 V max. 291.49 W @ 110 V (PoE)	...
Operation modes	...	8 x AHD / HD-CVI / HD-TVI / CVBS / IP + 8 x IP
Recording modes	...	Manual, Sensor, Motion detection, Schedule

Supported hard drives	...	1 x 10 TB SATA
External storage devices backup	...	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records	...	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function 1/4/9 channel synchronous playback
Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Alarm inputs / outputs	...	8 / 3
PTZ control	...	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones



Main features	...	<ul style="list-style-type: none"> • Cooperation with Dahua devices working in the concept of the Internet of Things (IoT), • POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window, • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Coax Audio/Alarm support, • Intelligent image analysis : crossing the line (tripwire), crossing the line (tripwire), abandoned/missing object, classification of people and vehicles
USB	...	1 pcs USB 2.0 1 pcs USB 3.0
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	100 ... 240 V AC	12 V DC / 2 A (power adapter included)
Color	...	Black
Weight	2.2 kg	1.28 kg
Dimensions	440 x 180 x 44 mm, RACK 19", 1U	325 x 255 x 55 mm
Supported languages	...	Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian
Country of origin	...	China
Manufacturer / Brand	TP-LINK	DAHUA
Guarantee	5 years	3 years