



	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC- HFW1500C-0280B-S2 - 5 Mpx 2.8 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76H0T- ITPF(2.8MM)(C) - 5 Mpx Hikvision
		
	243.00 PLN 243.00 PLN	249.00 PLN 249.00 PLN
Standard	AHD, HD-CVI, HD-TVI, CVBS	AHD / HD-CVI / HD-TVI / CVBS
Sensor	1/2.7 " CMOS	Progressive Scan CMOS
Matrix size	5 Mpx	5 Mpx
Resolution	2880 x 1620 - 5 Mpx - HD- CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p - HD- CVI only 960 x 576 - 960H	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI - 20 fps • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps • 1920 x 1080 - 1080p @ HD-TVI - 25 fps • 960 x 576 - 960H @ PAL
Range of IR illumination	30 m	20 m
Lens	2.8 mm	2.8 mm
IR illuminator power adjustment	Automatic	Automatic
View angle	<ul style="list-style-type: none"> • 111 ° (manufacturer data) • 106 ° (our tests result) 	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 83 ° (our tests result)
IR illuminator support	...	ICR - Movable InfraRed filter
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	—

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	✓	OSD menu available via recorder
Power supply	12 V DC / 310 mA	12 V DC / 340 mA
Power consumption	≤ 3.7 W	≤ 4.3 W
Housing	Compact, Plastic	Dome, Plastic
Color	White	White
"Index of Protection"	IP67	IP67
Vandal-proof	...	—
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.18 kg	0.15 kg
Dimensions	Ø 70 x 161 mm	Ø 85 x 79 mm
Manufacturer / Brand	DAHUA	Hikvision
SAP Code	...	300613619
Guarantee	3 years	3 years