



	<a href="#">ACCESS POINT TL-EAP225-OUTDOOR 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK</a>	<a href="#">CUSTOMER PREMISES EQUIPMENT PFWB5-90N DAHUA</a>
		
	430.39 PLN 430.39 PLN	1630.00 PLN 1630.00 PLN
Frequency range	2.4 GHz, 5 GHz	5150 MHz ... 5850 MHz
Vertical beam width (V)	...	20 °
Horizontal beam width (H)	...	90 °
Antenna type	<ul style="list-style-type: none"> <li>• 2.4 GHz : 2 x 3 dBi Outdoor, Omnidirectional antenna 2x2 MIMO,</li> <li>• 5 GHz : 2 x 4 dBi Outdoor, Omnidirectional antenna 2x2 MIMO</li> </ul>	18 dBi, 2x2 MIMO - Bandwidth 5 GHz
Standards	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac	802.11 a/n
Operation modes	...	WDS client, TDMA client, WDS Base Station, TDMA Base Station, ARP NAT Base Station, Bridge, Router
Wireless transmission range	...	<ul style="list-style-type: none"> <li>• Recommended ≤ 5 km</li> <li>• max. 7 km</li> </ul>
Baud rates	2.4 GHz : max. 300 Mbps (dynamic) + 5 GHz : max. 867 Mbps (dynamic)	max. 300 Mbps
Protections	WEP, WPA/WPA2-Personal, WPA/WPA2-Enterprise	Overvoltage protection
LAN ports	1 x 10/100/1000 Mbps	1 x 10/100 Mbps
Management interface	Web browser, Omada application	...
Transmitter power	< 20 dBm @ 2.4 GHz < 26 dBm @ 5 GHz	29 dBm
Housing	Outdoor, plastic (Weatherproof)	...
Overvoltage protection	<ul style="list-style-type: none"> <li>• 15 kV ESD</li> <li>• 4 kV lightning</li> </ul>	...
Power supply PoE	✓	✓
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af)</li> <li>• 24 V Passive PoE - PoE Adapter (included)</li> </ul>	12 V ... 24 V DC - Passive PoE (power adapter included)
Power consumption	10.5 W	4.5 W
Operation temp	-30 °C ... 70 °C	-30 °C ... 70 °C

Permissible relative humidity	10 % ... 90 %	...
-------------------------------	---------------	-----



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> <li>• Omada Central Management System</li> <li>• Software Omada Controller</li> <li>• 220 on-line users</li> <li>• Multi-SSID ( max. 16 )</li> <li>• Enable/Disable Wireless Radio</li> <li>• QoS - mechanisms, which provide the high quality of transmission</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Transmit power control</li> <li>• TP-Link Mesh technology: MU-MIMO, Automatic route selection, AP control, Bandwidth control, Beamforming</li> <li>• Airtime Fairness - technology that improves network performance when multiple clients with different data rates appear in it</li> <li>• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source</li> <li>• Load balance</li> <li>• Rate limit</li> <li>• Wireless Network Schedule</li> <li>• Wireless transmission statistics</li> <li>• Authentication using the welcome page</li> <li>• Access control</li> <li>• MAC addresses filtering</li> <li>• Wireless isolation between clients</li> <li>• SSID to VLAN mapping</li> <li>• Rogue Access Point detection</li> <li>• 802.1x Radius</li> <li>• e-mail personal messaging</li> <li>• Remote management</li> <li>• RESET button</li> <li>• LED indication</li> <li>• Power supply PoE</li> <li>• Easy to install on any wall or pole (mounting kit included)</li> </ul>	...
---------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----



"Index of Protection"	IP65	...
Weight	0.168 kg	0.51 kg
Dimensions	215 x 46 x 27 mm (without antennas & mounting kit) 404 x 91 x 55 mm (with antennas & mounting kit)	383 x 100 x 98 mm
Manufacturer / Brand	TP-LINK	DAHUA
Guarantee	5 years	3 years