



	NVR DS-7632NXI-K2 32 CHANNELS ACUSENSE Hikvision	UPS AT-UPS1000-LCD 1000 VA EAST
		
	2115.00 PLN 2115.00 PLN	1373.97 PLN 1373.97 PLN
Standard	TCP/IP	...
Power adapter type	...	Online
Nominal power	...	900 W
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	...
Apparent Power	...	1000 VA
Input voltage	...	230 V AC \pm 25 %
Video outputs	1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output	...
Input frequency	...	50 / 60 Hz (auto detection)
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Output voltage	...	230 V AC \pm 5 % (Pure Sine Wave)
Audio inputs	1 pcs CINCH	...
Output frequency	...	50 / 60 Hz \pm 1 %
Audio outputs	1 pcs CINCH	...
Voltage adjustment	...	\pm 1 %
Frequency adjustment	...	—
Transfer time	...	0 ms
Image compression method	H.265+ / H.265 / H.264 / H.264+	...
Charging time (recover to 90% capacity)	...	8 hours
Bitrate	max. 256 Mbps	...
Battery	...	3 pcs - 12V/7Ah
Supported hard drives	2 x 10 TB SATA	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Smart Playback function Records playback from max. 16 channels in the same time	...
Estimated battery operation time	...	<ul style="list-style-type: none"> • 45 minutes @ 100 W, • 12 minutes @ 300 W, • 7 minutes @ 500 W

Network interface	1 x RJ-45 10/100/1000 Base-TX	...
Number of outputs	...	2 pcs CEE 7/3 (Schuko)
Management software	...	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)
Network functions	<ul style="list-style-type: none"> • Live image view, Playback the records, Backup the records • max. 128 on-line users - iVMS-4200 application 	...
Protections	...	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • Overcharge protection • EPO (Emergency power off) switch • Ethernet filter
Operation state indication	...	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling
Network protocols	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS	...
ONVIF	✓	...
Main features	...	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • "Cold Start" function • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Excellent microprocessor control guarantees high reliability • self test feature • Battery charge and maintenance control • USB/RS-232 communication port
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Application	...	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type	...	Tower

Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect	...
Web browser access ports	80, 8000	...
PC client access ports	8000	...
Mobile client access ports	8000	...
Operation temp. / Relative humidity	...	0 °C ... 40 °C / 0 ... 90 %
RTSP URL	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream	...
USB	2 pcs USB 2.0	...
Serial ports	—	...
Alarm inputs / outputs	4 / 1	...
PTZ control	✓	...
Motion Detection	✓	...
Intelligent image analysis	✓	...
Main features	• Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles • face detection • Comparison of faces with images from the database • Support for up to 16 face databases, including 20 000 face images • Smart search for a person based on a face photo • NVR from the AcuSense series	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	12 V DC / 3.33 A (power adapter included)	...
Power consumption	max. 15 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	1.72 kg	12 kg
Dimensions	380 x 322 x 52 mm	430 x 145 x 215 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	EAST
SAP Code	303616125	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00