



	IP CAMERA IPC3618SB-ADF28KM-10 - 8.3 Mpx 4K UHD 2.8 mm UNIVIEW	IP CAMERA IPC-HDW1431S-0280B-S4 - 4 Mpx 2.8 mm DAHUA	CONNECTOR STRIP KE-LTE6-4.0 SIMET
			
	1401.84 PLN 1401.84 PLN	647.00 PLN 647.00 PLN	10.02 PLN 10.02 PLN
Standard	TCP/IP	TCP/IP	...
Number of terminal pairs	6
Sensor	1/2.7 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS	...
Connector type	terminals
Matrix size	8.3 Mpx	4 Mpx	...
Nominal voltage	500 V
Scanning system	Progressive
Rated current	32 A
Wire gauge	4 mm ²
Dielectric	Polomel MEC-3
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 1728 - 5.3 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.6 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
S/N ratio	> 56 dB
Lens	2.8 mm	2.8 mm	...
RS-485 interface	—
View angle	• 112 ° (manufacturer data) • 100 ° (our tests result)	93 °	...
Range of IR illumination	30 m	30 m	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	—	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	—	...
Audio	• Microphone built-in • Audio transmission via network • Audio detection	—	...
Bitrate	...	32 ... 10240 kbps - H.264 12 ... 8448 kbps - H.265	...
Main stream frame rate	20 fps @ 8.3 Mpx 25 fps @ 5.3 Mpx	20 fps @ 4 Mpx 25 fps @ 3.7 Mpx	...
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, SSL / TLS, QoS	HTTP, HTTPS, TCP, ARP, RTSP, RTP, RTCP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, QoS, UPnP, NTP, RTMP, IEEE 802.1x, Multicast, ICMP, IGMP, TLS	...
WEB Server	Built-in	Built-in	...
Max. number of on-line users	32	20	...
ONVIF	✓	18.12	...
Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
Default IP address	DHCP or 192.168.1.13	192.168.1.108	...
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 554	80, 37777	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	37777	...
Mobile client access ports	80	37777	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Port ONVIF	80	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, face detection, people counting, crowd gathering estimation 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 460 mA 	...
Power consumption	≤ 5 W	< 5.5 W	...
Housing	Dome, Metal	Dome - Metal + Plastic	...
Color	White	White	White
"Index of Protection"	IP67	IP67	...
Vandal-proof	—
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C	...
Weight	0.46 kg	0.27 kg	...
Dimensions	Ø 111 x 94 mm	Ø 108 x 85 mm	60 x 22 x 18 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, Czech, French, Spanish Dutch, German, Portuguese, Russian, Italian	...
Manufacturer / Brand	UNIVIEW	DAHUA	SIMET
Guarantee	3 years	3 years	2 years