




|                      | <a href="#">USB SWITCH US-221A<br/>ATEN</a>  | <a href="#">CABLE TRACKER MS-6812</a>   | <a href="#">CABLE CP-50 SATEL</a>   |
|----------------------|--|---|---|
|                      |   |    |  |
|                      | 149.12 PLN<br>149.12 PLN   | 87.19 PLN<br>87.19 PLN  | 30.00 PLN<br>30.00 PLN  |
| Output signal        | ...  | 1.5 kHz - Transmitter   | ...   |
| Input signal         | ...  | 100 Hz ... 300 kHz - Receiver   | ...   |
| Connectors           | <ul style="list-style-type: none"> <li>• 2 x socket USB 2.0 B - Computer interface</li> <li>• 1 x socket USB 2.0 A - Connecting to the device</li> </ul>   | ...   | ...   |
| Support              | ...  | ...   | Alarm control panels SATEL : MICRA, PERFECTA, VERSA, INTEGRA, and others            |
| Length of the cable  | 180 cm   | ...   | 0.5 m   |
| USB standard         | 2.0  | ...   | ...   |
| Main features        | ...  | <ul style="list-style-type: none"> <li>• Identification the wire in the group of wires</li> <li>• Wire continuity test</li> <li>• Searching the place of wire damage</li> <li>• Telephone line status identification</li> </ul> | ...   |
| Power supply         | ...  | 2 x 9V, type 6F22 battery (included)  | ...   |
| Main features        | <ul style="list-style-type: none"> <li>• LED indication</li> <li>• Support for platforms: Windows, Linux, Mac, Sun</li> <li>• Overload protection</li> <li>• USB A / USB B cable included - 1.8 m</li> </ul> | ...   | ...   |
| Weight               | 0.05 kg  | 0.09 kg - Transmitter<br>0.07 kg - Receiver   | 0.012 kg  |
| Manufacturer / Brand | ATEN   | ...   | SATEL   |
| Dimensions           | 72 x 66 x 25 mm  | 249 x 33 x 25 mm - Transmitter<br>238 x 43 x 26 mm - Receiver   | ...   |
| Guarantee            | 2 years  | 2 years   | 2 years   |