



	ACCESS CONTROLLER MODULE MC16-PAC-ST-3 ROGER	VIDEO SEPARATOR SV-1000P STANDARD: PAL,
		
	1750.00 PLN 1750.00 PLN	141.29 PLN 141.29 PLN
Number of served transitions	3 (two-way)	...
Standard	...	CVBS - PAL / NTSC
Number of supported readers	12	...
Number of inputs	...	1 pcs BNC
Number of outputs	...	1 pcs BNC
Number of users	unlimited (purchase of the appropriate license required)	...
Input impedance	...	75 Ω
Output impedance	...	75 Ω
Galvanic (optical) isolation between signal inputs and outputs	...	1000 V peak
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Opto-isolation between power and signal inputs / outputs	...	1000 V peak
Buffer memory	8 000 000 events buffer	...
Number of access zones	6	...
Gain adjustment	...	-5 dB ... +5 dB
Number of alarm zones	6	...
Bandwidth	...	9 MHz / 1 Vpp
Battery backup support	12 V / 7 Ah	...
Transmission error	...	0.75 % (f=3.58MHz, Vin=1Vpp)
Assembly	...	To the wall
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	...

Main features	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	...
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	12 V DC / 80 mA
Operation temp	5 °C ... 40 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Weight	0.14 kg	0.095 kg
Dimensions	175 x 72 x 30 mm	61 x 120 x 30 mm
Manufacturer / Brand	ROGER	DELTA
Guarantee	3 years	3 years