

	DESOLDERING WIRE P-LUT/1.5MM Blow	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTI-AI80FQRTD 4.5 mm - 1080p	TV OR MONITOR MOUNT AX-HAMMER	TV OR MONITOR MOUNT AX-TYTAN-ALUX
				
	6.39 PLN 6.39 PLN	180.00 PLN 180.00 PLN	114.35 PLN 114.35 PLN	435.00 PLN 435.00 PLN
Strip width	1.5 mm	...	...	...
Strip length	150 cm	...	...	...
Scanning system	...	Progressive	...	...
Optical zoom	...	—	...	...
Mounting standard	...	...	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400, 600 x 400	VESA : 200, 300, 400 x 200, 400, 600 x 400
Screen size range	...	...	23 " ... 70 "	37 " ... 70 "
Sensor	...	1/2.9 " GC2093 1/2.9 " GC2053	...	...
Bearing capacity	...	...	50 kg	45 kg
Matrix size	...	2.1 Mpx 2 Mpx	...	...
Lens	...	4.5 mm 4.5 mm	...	...
Distance from mounting surface	...	...	83 ... 455 mm	54 ... 448 mm
Tilt adjustment	...	...	0 ° ... 15 °	-15 ° ... 15 °
Cards support	...	13.56 MHz S50	...	...
Horizontal rotation	...	...	-45 ° ... 45 °	-60 ° ... 60 °
Keyboard built-in	...	—	...	...
Rotation in the plane of the screen	...	...	—	± 3 °
Doorbell button	...	—	...	...
Resolution	...	1920 x 1080 - 1080p 1280 x 720 - 720p 640 x 480 px	...	...
View angle	...	66 ° 66 ° 90 °	...	...
Interface	...	USB, RS-232 TTL	...	...
Maximum background illumination	...	100 000 Lux	...	...

QR codes reading	...	• 1D : EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codabar, Interleaved 2 of 5 (ITF), ITF-6, ITF-14, ISBN, ISSN, MSI-Plessey, GS1 Databar, Code 11, Industrial 25, Standard 25, Plessey, Matrix 2 of 5 • 2D : QR Code, Data Matrix, PDF417, Aztec	...	...
Reading distance	...	• EAN13 (13 mm) : 30 ... 140 mm • Code 39 (5 mm) : 30 ... 50 mm • QR Code (20 mm) : 35 ... 120 mm • Data Matrix (10 mm) : 30 ... 70 mm • PDF417 (6.67 mm) : 30 ... 80 mm	...	...
Minimal contrast	...	25 %	...	...
Standard	...	TCP/IP	...	...
Range of IR illumination	...	5 m	...	...
White light LED illuminator range	...	5 m	...	...
Temperature measurement	...	✓	...	...
Temperature measurement range	...	35.7 °C ... 42 °C	...	...
Accuracy of temperature measurement	...	± 0.3 °C	...	...
Temperature measurement distance	...	0.7 m ... 1.2 m	...	...
Face recognition distance	...	0.5 m ... 2.0 m (max 30 000 faces in the database)	...	...
Internal memory	...	Support storage of 50 000 records	...	...
Video output	...	—	...	...
RS-485 interface	...	✓	...	...
Wiegand interface	...	✓	...	...
Memory card slot	...	—	...	...
Alarm inputs / outputs	...	0 / 1	...	...
Audio	...	Speaker built-in	...	...
Network interface	...	10/100 Base-T (RJ-45)	...	...
Network protocols	...	IPv4, TCP/IP, HTTP, MQTT, RTSP, SMTP, NTP	...	...
WEB Server	...	Built-in	...	...
ONVIF	...	—	...	...
Default IP address	...	DHCP / 192.168.1.88	...	...
Default admin user / password	...	admin / 12345	...	...
Web browser access ports	...	80	...	...
PC client access ports	...	80	...	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	• Built-in LCD display showing the image from the video camera and the result of temperature measurement - 800 x 1280 px, 8 " • Wiegand 34/26 • Day/Night mode (color/b&w/auto) • RESET button • Alarm output of NO/NC relay type • Relay output operating modes: access control or notification of an exception • Built-in QR code reader	...	...
Power supply	...	12 V / 2 A DC	...	...
Power consumption	...	≤ 18 W	...	...
Housing	...	Compact - Metal	...	...
Color	...	Silver	Black	Silver / Black
"Index of Protection"	...	—	...	...
Operation temp	...	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)	...	...
Weight	...	1.8 kg	4.8 kg	4.76 kg
Dimensions	Ø 50 x 11 mm	366 x 132 x 144 mm	670 x 430 x (83 ... 455) mm	720 x 435 x (54 ... 448) mm
Montage hole diameter	...	35 mm	...	...
Length of the cable	...	65 cm	...	...
Supported languages	...	English, French, Spanish, Ukrainian, Italian	...	...
Manufacturer / Brand	Blow	APTI	...	...
Guarantee	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00