




	POWER DISTRIBUTION UNIT LE-049492 (5 OUTLETS) 3 m LEGRAND	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500T-A-0280B-S2 - 4.7 Mpx 2.8 mm DAHUA	NORMALLY OPEN RELAY MODULE PK4-12-ZD DELTA	TRIPLE SMART LIGHT SWITCH ATLO-WB3-TUYA Wi-Fi, Tuya Smart	CLEANER FOR RECOVERY OF POTENTIOMETERS KONTAKT-PR/400 SPRAY 400 ml AG TERMOPASTY
					
	86.47 PLN 86.47 PLN	338.00 PLN 338.00 PLN	89.26 PLN 89.26 PLN	53.32 PLN 53.32 PLN	26.93 PLN 26.93 PLN
Number of relay outputs	4
Package	Spray 400 ml
Total maximal current	16 A
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Maximal total load	3680 W
Sensor	...	1/2.7 " CMOS
Current consumption	35 mA per each relay at voltage 12 V DC
Matrix size	...	5 Mpx
Rated voltage	230 V AC / 50 Hz	100 ... 240 V AC, 50 / 60 Hz	...
Number of outlets	5 grounded outlets 16A/250V CEE 7/5
Fuse	—
Maximum power	300 W (for each output)	...
Switch	—
Rated current	max. 10 A	...
Relay maximal load	10 A (max), 30 V DC / 50 V AC (max)
Wire gauge	3 x 1.5 mm ²
Length of the cable	3 m
Number of buttons	3	...
Output	4 x NO/NC
Application	relay for electromagnetic lock/electric strike	Works with lighting - switching on/off	Cleaning and regeneration of potentiometers
Number of outputs	3	...
Connector type	screw terminals	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Mobile phones support	<ul style="list-style-type: none"> The Tuya Smart free application on Android The Tuya Smart free application on iOS 	...
Resolution	...	2880 x 1620 - 4.7 Mpx - HD-CVI only : Aspect Ratio 16 : 9, 2560 x 1440 - 3.7 Mpx, 1920 x 1080 - 1080p 960 x 576 - 960H
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 111 ° (manufacturer data) • 104 ° - HD-CVI, 91 ° - HD-TVI, 90 ° - AHD (our tests result)
Range of IR illumination	...	30 m
Main features	<ul style="list-style-type: none"> • DIN, TS-35 rail mounting, • LED indication, • Protections : Overvoltage, Reverse polarity connection 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication 	Spray preparation with a brush for easy application in hard-to-reach places

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

IR illuminator power adjustment	...	Automatic
Operation temp	-10 °C ... 40 °C	-20 °C ... 50 °C	...
Permissible relative humidity	≤ 80 %	...
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	Microphone built-in, HD-CVI only
S/N ratio	...	> 65 dB
OSD menu	...	✓
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance
Power supply	...	12 V DC / 270 mA	10 ... 16 V DC
Power consumption	...	≤ 3.2 W
Housing	Plastic	Compact, Metal	...	Plastic	...
Color	White / Gray	White	...	White	...
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	0.57 kg	0.37 kg	0.08 kg	0.11 kg	0.36 kg
Dimensions	250 x 54 x 37 mm	Ø 73 x 176 mm	73 x 44 x 40 mm	87 x 86 x 41 mm	Ø 66 x 187 mm
Manufacturer / Brand	LEGRAND	DAHUA	DELTA	...	AG TERMOPASTY
Guarantee	2 years	3 years	3 years	2 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00