



	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA DS-2CE56D8T-ITMF(2.8MM) - 1080p Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1200TMO-A-0280B-S6 - 1080p 2.8 mm DAHUA
		
	323.00 PLN 323.00 PLN	290.00 PLN 290.00 PLN
Standard	AHD / HD-CVI / HD-TVI / CVBS	HD-CVI, HD-TVI, AHD, CVBS
Sensor	Progressive Scan CMOS	Progressive Scan CMOS
Matrix size	2.1 Mpx	2.1 Mpx
Resolution	<ul style="list-style-type: none"> • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI • 960 x 576 - 960H @ PAL 	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL
Range of IR illumination	30 m	60 m
IR illuminator power adjustment	Automatic	Automatic
Lens	2.8 mm	2.8 mm
View angle	<ul style="list-style-type: none"> • 104 ° (manufacturer data) • 101 ° (our tests result) 	<ul style="list-style-type: none"> • 102 ° (manufacturer data) • 101 ° (our tests result)
IR illuminator support	ICR - Movable InfraRed filter	...
S/N ratio	> 62 dB	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω

Main features	<ul style="list-style-type: none"> • WDR \geq 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • AGC - Automatic Gain Control • Auto White Balance • Privacy zones • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	OSD menu available via recorder	OSD menu available via DAHUA recorder
Power supply	12 V DC / 280 mA	12 V DC / 410 mA
Power consumption	\leq 3.4 W	\leq 4.9 W
Housing	Dome, Metal	Dome, Metal + Plastic
"Index of Protection"	IP67	IP67
Color	White	White
Vandal-proof	—	—
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.24 kg	0.44 kg
Dimensions	91 x 83 x 68 mm	Ø 122 x 99 mm
Manufacturer / Brand	Hikvision	DAHUA
SAP Code	300612680	...
Guarantee	3 years	3 years