



	ACCESS POINT MAP-2ND mAP, 2.4 GHz 300 Mbps MIKROTIK	AHD, HD-CVI, HD-TVI CAMERA APTI-H50V2-28W-L 2Mpx / 5Mpx 2.8 mm
		
	210.68 PLN 210.68 PLN	124.80 PLN 124.80 PLN
Frequency range	2.4 GHz	...
Processor	Qualcomm Atheros AR9531 650 MHz	...
Standard	...	AHD, HD-CVI, HD-TVI
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	5 Mpx
Antenna type	2 x 2 MIMO Omnidirectional antenna , Dual-chain - embedded 1.2 dBi	...
Standards	IEEE 802.11 b/g/n	...
Baud rates	300 Mbps	...
LAN ports	2 x 10 / 100 Mbps LAN	...
LED indicators	Power, Operation mode, WiFi, User, PoE OUT, 2 x Ethernet	...
Resolution	...	<ul style="list-style-type: none"> • 2592 x 1944 - 5 Mpx - AHD / HD-TVI, • 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-TVI, • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 91 ° (manufacturer data) • 92 ° (our tests result)
White light LED illuminator range	...	25 m
Receiver sensitivity	2.4 GHz : <ul style="list-style-type: none"> • 1M : -96 dBm • 11M : -89 dBm • 6M : -93 dBm • 54M : -74 dBm • MCS0 : -93 dBm • MCS7 : -71 dBm 	...
Video output	...	AHD / HD-CVI / HD-TVI, 1 Vpp / 75 Ω

Transmitter power	max. 22 dBm	...
Audio	...	—
OSD menu	...	✓
DHCP server	✓	...
Firmware update	✓	...
Operating system	MikroTik RouterOS	...
Management interface	Web browser, MikroTik application	...
Default IP address	192.168.88.1	...
Operation modes	<ul style="list-style-type: none"> • Access Point, • Station 	...
Main features	...	<ul style="list-style-type: none"> • Possibility to turn off the LED illuminator • Automatic LED light intensity adjustment • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Auto White Balance • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image
"Index of Protection"	...	IP67
Housing	...	Dome, Aluminum + Plastic
Power supply	<ul style="list-style-type: none"> • 8 ... 57 V DC - 24 V DC / 0.8 A (power adapter included) • 10 ... 57 V DC - Passive PoE, PoE (802.3af/at) • 5 V DC - Micro USB-B socket 	12 V DC / 270 mA
Vandal-proof	...	—
Power consumption	max. 5 W	≤ 3.2 W
Color	...	White
Operation temp	...	-20 °C ... 60 °C

Main features	<ul style="list-style-type: none"> • Dual-chain • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Built-in 2-port switch • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Port USB 2.0 - Possibility to connect 3G/4G modem, Power connector • PoE IN : PoE 802.3af/at / PASSIVE - port ETH1 • PoE OUT : Passive PoE - port ETH2 • Voltage control • Mode button • RESET button • USB A / micro USB B cable included 	...
Operation temp	-20 °C ... 70 °C	...
Weight	0.068 kg	0.36 kg
Dimensions	68 x 68 x 19 mm	Ø 109 x 93 mm
Manufacturer / Brand	MikroTik	APTI
Guarantee	2 years	2 years