



	<a href="#">EXTENDER VGA-EX-60</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-ECO-PLUS (6 OUTLETS)</a>
		
	55.28 PLN 55.28 PLN	242.26 PLN 242.26 PLN
Device type	Passive	...
Maximal load power	...	2300 W
Power supply	—	...
Nominal voltage	...	230 V AC / 50 Hz
Video transmission range	max. 60 m	...
Symmetrical socket impedance	100 Ω	...
Fuse	...	10 A / 250 V
Switch	...	two-way
Leak current	...	< 0.5 mA
Response time	...	< 25 ns
Connectors type	<ul style="list-style-type: none"> <li>• 1 pcs VGA socket</li> <li>• 1 pcs RJ-45 shielded socket</li> </ul>	...
Nominal voltage of surge suppressor	...	250 V
Protection level	...	1.3 kV (L/N)
Nominal stroke current	...	2 kA (L/N) - (8/20μs)
Maximum stroke current	...	6.5 kA (L/N) - (8/20μs)
Electric shock protection system	...	Ground connectors (pins) connected with ground wire of AC mains
Housing	...	Plastic - non-flammable
Number of output outlets	...	<ul style="list-style-type: none"> <li>• 1 MASTER outlet, two-contact with ground contact</li> <li>• 3 SLAVE outlets with auto switch off the power supply after switch off the receiver powered from MASTER outlet</li> <li>• 2 outlets separate from MASTER outlet</li> </ul>
Resolution	<ul style="list-style-type: none"> <li>• 1600 x 1200 px UXGA,</li> <li>• 1280 x 1024 px SXGA,</li> <li>• 1280 x 768 px WXGA,</li> <li>• 1024 x 768 px XGA,</li> <li>• 800 x 600 px SVGA,</li> <li>• 640 x 480 px VGA</li> </ul>	...
Length of the cable	...	1.45 m

Grounding	—	...
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	≤ 85 %	...
Weight	0.07 kg	0.56 kg
Dimensions	57 x 42 x 27 mm	447 x 55 x 53 mm
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00