



	BUFFERED SWITCHING POWER SUPPLY ADAPTER APS-30 SATEL	SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE
		
	420.00 PLN 420.00 PLN	469.00 PLN 469.00 PLN
Adapter type	Switching	...
Input voltage	230 V AC	...
Output voltage	12 V	...
Connectors	...	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs cable terminal • 1 pcs BNC
Max. output current (total)	3 A	...
LAN ports	...	1 pcs RJ45 100 Mbps
Battery charging current	0.5 A / 1 A (switchable)	...
Power	36 W	...
Number of outputs	3 pcs	...
Adapter operation control	<ul style="list-style-type: none"> • AC input voltage presence indication AC • Battery charging indication 	...
Place for battery	12V/17Ah	...
Max. battery dimensions	190 x 165 x 80 mm	...
LAN+PoE port configuration description	...	<ul style="list-style-type: none"> • xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+/-": 3, 6 pins) or ("+/-": 4, 5 pins; "+/-": 7, 8 pins) • xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W
Transmission range	...	<ul style="list-style-type: none"> < 1000 m @ Coaxial cable < 100 m @ xCOAX4-SW - Switch PoE < 100 m @ xCOAX4-CAM - IP Camera
LED indicators	...	<ul style="list-style-type: none"> • PoE • LAN • Link • 10Mb

Protections	<ul style="list-style-type: none"> • Overvoltage • Overload 	<ul style="list-style-type: none"> • Overvoltage - LAN, BNC • Short-circuit - xCOAX4-SW
Main features	<ul style="list-style-type: none"> • Microprocessor based battery charge control system • Tamper signaling • LED indication • 2 x OC output 	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Watchdog function - Coaxial cable
Power supply	...	xCOAX4-SW : <ul style="list-style-type: none"> • 10 ... 58 V DC - cable terminal • PoE 802.3af/at / PASSIVE • The output PoE voltage is equal to the input voltage
Power consumption	...	1.35 W (total)
Housing	...	Plastic (PC)
"Index of Protection"	...	IP20
Operation temp	5 °C ... 40 °C	-25 °C ... 65 °C
Weight	3.3 kg	0.033 kg (single element)
Dimensions	382 x 324 x 108 mm Buffered power unit	<ul style="list-style-type: none"> • 73 x 52 x 20 mm - xCOAX4-SW • 73 x 52 x 20 mm - xCOAX4-CAM
Manufacturer / Brand	SATEL	ATTE
Guarantee	2 years	3 years