




	IP CAMERA TC-C382V SPEC:W/E/Y/S/H/2.8MM PANORAMIC Full-Color - 8 Mpx 2 X 2.8 mm TIANDY	SOLAR IP CAMERA, OUTDOOR DS-2XS2T41G1- ID/4G/C05S07(4MM) 4G/LTE - 3.7 Mpx 4 mm Hikvision	HACKSAW ST-0-20-807 STANLEY
			
	1657.00 PLN 1657.00 PLN	2729.00 PLN 2729.00 PLN	17.09 PLN 17.09 PLN
Blade length	255 mm
Standard	IP	TCP/IP	...
Matrix size	...	4 Mpx	...
Sensor	2 x 1/2.7 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS	...
Main features	<ul style="list-style-type: none"> • Polypropylene handle firmly holding the blade, • Ideal for use in small areas with limited access, • Flexible blade with adjustable length allows precise cutting
White light LED illuminator range	15 m
Resolution	4640 x 1728 - 8 Mpx	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2 x 2.8 mm	4 mm	...
Min. illumination	0.0001 Lux / F1.0 (color)
View angle	<ul style="list-style-type: none"> • 180 ° (manufacturer data) • 180 ° (our tests result) 	<ul style="list-style-type: none"> • 79 ° (manufacturer data) • 76 ° (our tests result) 	...
RS-485 interface	✓
Range of IR illumination	—	30 m	...
Alarm inputs / outputs	1 / 1
Possibilities of adjustment	...	Solar Panel : -30 ° ... 30 ° (horizontal) ; -45 ... 45 (vertical)	...
Interface	10/100 Base-TX (RJ-45)
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio input • Audio output • Bi-directional audio streaming support • Speaker built-in • Audio transmission via network • Compliance with the AAC standard 	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Audio transmission via network, • Bi-directional audio streaming support, • Noise reduction, • Alarm signaling, • Compliance with the AAC standard 	...
Image compression method	S+265 / H.265 / H.264	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Main stream frame rate	25 fps @ 8 Mpx	12.5 fps @ 3.7 Mpx	...
Network interface	...	<ul style="list-style-type: none"> • RJ-45 - 10/100 Mb/s, Ethernet • 4G LTE - The microSIM cards support, Uplink / Downlink : 50 / 150 Mbps 	...
ONVIF	✓	✓	...
WEB Server	Built-in	Built-in	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Intelligent image analysis	<ul style="list-style-type: none"> • crossing the line (tripwire) • intrusion • classification of people and vehicles
Max. number of on-line users	7	6	...
Default admin user / password	admin / - The administrator password should be set at the first start	admin / -	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus 	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	DHCP or 192.168.1.2	192.168.1.64	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	80	...
PC client access ports	3000, 3001	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	3000, 3001	8000	...
Port ONVIF	80	80	...
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization 	...
Memory card slot	Micro SD card support up to 512GB	Micro SD memory cards up to 256GB support (possible local recording)	...
Mechanical protection class	—
Operation temp	-35 °C ... 65 °C



Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ROI - improve the quality of selected parts of image • Day/night mode • Possibility to change the resolution, quality and bit rate 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Day/night mode • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Auto White Balance • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • Motion Detection • Alarm signaling - Audio, E-mail • Alarm notifications • Events saving to the micro SD card • Built-in PIR detector : <ul style="list-style-type: none"> - Detection angle : 80 ° (horizontal), 42 ° (vertical) - Detection range : 12 m • Internal memory : 8 GB (5 GB for recording) • 4G LTE/WCDMA/GSM support - The microSIM cards support • RESET button, • Solar Panel : 6.5 W - built-in battery 51.5 Wh 	...
Estimated battery operation time	...	<ul style="list-style-type: none"> • ~ 2 days • 11 days (Standby mode) 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 920 mA 	<ul style="list-style-type: none"> • Li-Ion battery 8.1 ... 12.6 V, • Solar Panel : 6.5 W, • 12 V DC - 5.5/2.1 socket (power adapter not included), For the purpose of service 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 12 W @ PoE • ≤ 11 W @ 12 V DC 	<ul style="list-style-type: none"> • max. 7 W • ≤ 1.85 W (typical) - 4G LTE support • 80 mW (Standby mode) 	...
Housing	Compact - Metal	Compact, ADC	...
"Index of Protection"	IP67	IP67	...
Color	White	White	...
Operation temp	...	0 °C ... 50 °C	...
Weight	0.8 kg	1.45 kg (total)	0.07 kg
Dimensions	294 x 116 x 72 mm	294 x 189 x 214 mm (total)	270 x 65 x 20 mm
Supported languages	Polish, English, Albanian, Arabic, French, Hebrew, Spanish, Dutch, Korean, German, Portuguese, Thai, Ukrainian, Vietnamese, Italian	Polish, English, Croatian, Czech, Romanian, Serbian, Slovenian, Turkish	...
Manufacturer / Brand	TIANDY	Hikvision	STANLEY
SAP Code	...	311319441	...
Guarantee	3 years	3 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00