



	RADIO CONTROLLER RK-4K SATEL	RADIO CONTROLLER RK-2K SATEL
		
	187.00 PLN 187.00 PLN	164.00 PLN 164.00 PLN
Operating range in open area	to 350 m	to 350 m
Number of controlled inputs	4	2
Relay operating modes	Bistable, monostable, pulse	Bistable, monostable, pulse
Adjustment range of changeover time in monostable mode	1 ... 3600 s	1 ... 3600 s
Frequency range	433.05 MHz ... 434.79 MHz	433.05 MHz ... 434.79 MHz
The KEELOQ code-hopping technology	✓	✓
Power voltage	• 12 V ... 24 V DC \pm 10 % • 24 V AC \pm 10 %	• 12 V ... 24 V DC \pm 10 % • 24 V AC \pm 10 %
Current consumption (min. / max.)	about 18 mA / about 58 mA	about 18 mA / about 40 mA
Relay contacts load	1 A @ 24 V DC / AC	1 A @ 24 V DC / AC
Current-carrying capacity of LV (OC) output	50 mA	50 mA
Current-carrying capacity of SS (OC) output	500 mA	500 mA
Main features	<ul style="list-style-type: none"> • 4 independent, programmable channels • Support for up to 1024 keyfobs • signaling a low voltage battery in the keyfob • arm/disarm, active/clearance alarm confirmation • Port RS-232 	<ul style="list-style-type: none"> • 2 independent, programmable channels • Support for up to 1024 keyfobs • signaling a low voltage battery in the keyfob • arm/disarm, active/clearance alarm confirmation • Port RS-232
Receiver operation temperatures range	-10 ... 50 °C	-10 ... 50 °C
Operating temperature range for transmitter (remote keyfob)	-20 ... 55 °C	-20 ... 55 °C
Dimensions	72 x 118 x 24 mm	72 x 118 x 24 mm
Weight	0.09 kg	0.09 kg
Manufacturer / Brand	SATEL	SATEL
Guarantee	2 years	2 years