



	<a href="#">ACCESS CONTROLLER MC16-PAC-EX-1-KIT ROGER</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW2802T-A-0280B - 8.3 Mpx, 4K UHD 2.8 mm DAHUA</a>
		
	1825.00 PLN 1825.00 PLN	779.00 PLN 779.00 PLN
Number of served transitions	1 (two-way)	...
Support	RACS 5 v2 (Roger)	...
Number of supported readers	4 pcs	...
Battery backup support	max. 7 Ah	...
Standard	...	AHD, HD-CVI, HD-TVI, PAL
Input lines	8 pcs	...
Sensor	...	1/1.8 " Progressive Scan CMOS
Output lines	8 pcs	...
Matrix size	...	8.3 Mpx
Communication	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• RACS 5 v2 (Roger),</li> <li>• Wiegand</li> </ul>	...
Resolution	...	<ul style="list-style-type: none"> <li>• HD-CVI : 3840 x 2160 - 8.3 Mpx, 4K UHD @ 15 fps , 3072 x 2048 - 6.3 @ 20 fps , 2560 x 1440 - 3.7 Mpx @ 25 fps ,</li> <li>• AHD / HD-TVI : 2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx @ 25 fps ,</li> <li>• CVBS : 960 x 576 - 960H, PAL</li> </ul>
IR illuminator support	...	ICR - Movable InfraRed filter
Range of IR illumination	...	50 m

Main features	<ul style="list-style-type: none"> <li>• Metal housing</li> <li>• Power output : 1 x 0.2 A, 1 x 1.0 A</li> <li>• Power adapter : 24 V DC / 2.2 A,</li> <li>• Battery charging current : 0.3 A</li> <li>• Protection against deep discharge of the battery</li> <li>• Tamper detection - opening the enclosure</li> <li>• Place for battery - 12 V / 7 Ah</li> <li>• Integrated support in VISO EX software</li> <li>• Functions in the VISO EX system: - MSSQL database</li> <li>- work in distributed systems ...</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system - unlimited</li> <li>- division of the system into partitions operated by independent operators</li> <li>- tool for integration with RACS5 (API) systems</li> <li>- integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)</li> </ul>	
IR illuminator power adjustment	...	Automatic
S/N ratio	...	> 65 dB
Operation temp	5 °C ... 40 °C	...
Lens	...	2.8 mm
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
View angle	...	<ul style="list-style-type: none"> <li>• 111 ° (manufacturer data)</li> <li>• 106 ° (our tests result)</li> </ul>
Video output	...	AHD / HD-CVI / HD-TVI / PAL, 1 V <sub>pp</sub> / 75 Ω
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in - HD-CVI only,</li> <li>• External microphone input - HD-CVI only</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu	...	OSD menu available via DAHUA recorder
Power supply	230 V AC	12 V DC / 670 mA
Power consumption	...	≤ 8 W
Housing	...	Dome, Aluminum
Color	...	White
Vandal-proof	...	—
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Weight	3.88 kg	0.51 kg
Dimensions	405 x 365 x 120 mm	Ø 106 x 99 mm
Supported languages	...	Polish, English, French, Spanish, German, Portuguese, Russian, Italian
Manufacturer / Brand	ROGER	DAHUA
Guarantee	3 years	3 years