



	MULTI-FUNCTIONAL CCTV TESTER CS-H7-70H	INTERACTIVE WHITEBOARD MOBILE STAND PKC-MS0B DAHUA
		
	2264.00 PLN 2264.00 PLN	2265.00 PLN 2265.00 PLN
Mounting standard	...	Mounting dimensions : max. 840 mm (vertical) max. 606 mm (horizontal)
Screen size range	...	55 " ... 75 "
Bearing capacity	...	180 kg
Distance from mounting surface	...	—
Color	...	Black
Tilt adjustment	...	—
Horizontal rotation	...	—
Rotation in the plane of the screen	...	—
Video standard	<ul style="list-style-type: none"> • AHD - 8 Mpx, • HD-CVI - 8 Mpx, • HD-TVI - 8 Mpx, • TCP/IP - 4K, • CVBS - PAL / NTSC 	...
Main features	...	<ul style="list-style-type: none"> • Mobile whole structure • Adjustable height of the monitor mount • Easy and universal mounting system
Display	7 " - capacitive touch screen, 1280 x 800 px	...
Manufacturer / Brand	...	DAHUA
Video input	<ul style="list-style-type: none"> • 1 pcs AHD / HD-CVI / HD-TVI / CVBS - BNC socket • 1 pcs HDMI 	...
Video output	<ul style="list-style-type: none"> • 1 pcs CVBS - BNC socket • 1 pcs HDMI 	...
Port LAN	2 pcs - PoE cameras and switches support	...
Audio input	1 pcs Mini Jack	...
Audio output	1 pcs Mini Jack	...
Video signal level meter	—	...

Video signal generator	<ul style="list-style-type: none"> • Test signal generator • Generating eight color bars in PAL / NTSC standards • It is possible to generate a blue or black screen 	...
Serial ports	RS-485	...
Protocols	Support for over 30 RS485 protocols : Pelco-D, Pelco-P, YAAN, YAAN-O, YAAN-1, SAMSUNG, PANASONIC, Lilin-FAST, Lilin-MLP2, MOLYNX, MINKING A01, Fastrax, CBC, LC-NEW, WV-CS850, SONY-EVI, LG-MULTIX, DAT-SD, VICON, Vcltp, DH-YTC 06, Santachi, Bosch OSRD, TeleEye DM2, HD 600, Hikvision, KALATEL ASC, AD 168(M-B), SAMSUNG SPD, Siemens, Cohu, MINKING B01, ALEC	...
Baud rates	150, 300, 600, 1200, 2400, 4800, 9600, 19200, 38400, 115200 b/s	...
LAN (twisted-pair) or telephone cables testing	UTP cables or phone lines connecting test with RJ-45 connectors	...
RS-485, RS-232 lines test	Data analysis from control device (the commands are displayed in hexadecimal)	...
Wi-Fi Module	2.4 GHz	...
Identification the wire in the group of wires	—	...
Audio test	✓	...
Digital multimeter	—	...
Optical power measurement	—	...
VLS (VFL) - Visual Fault Locator of fiber cable	—	...
TDR reflectometer	Detecting and locating a cable break (UTP only)	...
Operation as power source	<ul style="list-style-type: none"> • 12 V DC / 3 A • 24 V DC / 2 A • 5 V DC / 2 A from USB port • 48 V (PoE, LAN), 24 W 	...
Battery power supply	<ul style="list-style-type: none"> • Battery 7500 mAh • 12 V DC / 2 A (power adapter included) 	...

Estimated battery operation time	max. 10 hours	...
Operation	Graphical menu - touch control and by using the buttons	...




DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • AHD cameras test • HD-CVI cameras test • HD-TVI cameras test • PAL/NTSC cameras test • IP cameras test - Supported image compression methods : H.265, H.264, MJPEG • Searching and view of IP cameras compatible with Onvif • Virtual IPC • Bitrate Calculator • DH test tool • Hik test tool • UNV Test Tool • HuaWei Tool • Motor units and PTZ (Speed Dome) cameras control • IP cameras view from embedded applications - iVMS-4500 HD, EZView, gDMSS HD Lite, XMEye, MEye, Fseye • Embedded Internet browser - Google Chrome • Test signal generator • LAN connections monitoring • IP addresses scanner • PING - test the link using ICMP packets • Detection of the connected port in switch • LAN (twisted-pair) cables testing • PoE cameras and switches support • PoE power meter • DC 5V / 12V / 48V power source • Data monitor - serial port data analysis RS-485 • Audio test • Hotspot - Wi-Fi • Video recording to micro SD card with playback possibility - 8 GB included • Playback the records • Calculator • Flashlight built-in 	...
Operation temp	-10 °C ... 50 °C	...



Permissible relative humidity	30 % ... 90 %	...
Weight	0.94 kg	36 kg
Dimensions	242 x 157 x 46 mm	800 x 600 x 1530 mm
Supported languages	Polish, English, Czech, French, Spanish, German, Portuguese, Russian, Serbian, Turkish, Italian	...
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00