



	SWITCHING ADAPTER 24V/2.5A/GPV-MINI	NVR NVR616DRH-128-XI 128 CHANNELS WizMind DAHUA
		
	49.50 PLN 49.50 PLN	48878.00 PLN 48878.00 PLN
Adapter type	Switching	...
Standard	...	IP
Supported resolutions	...	max. 32 Mpx
Power voltage	180 ... 264 V AC	...
Frequency range	47 ... 63 Hz	...
Output voltage	24 V DC	...
Output voltage tolerance	± 3 %	...
Video outputs	...	<ul style="list-style-type: none"> • 2 pcs HDMI 4K • 1 pcs HDMI 8K • 1 pcs HDMI • 2 pcs VGA
Maximal load	2.5 A	...
Output power	60 W	...
Efficiency	86 %	...
Number of outputs	1 pcs	...
Audio support	...	<ul style="list-style-type: none"> • 128 Channels - Audio from cameras, • Bi-directional audio streaming support • Audio detection
Audio inputs	...	1 pcs CINCH
Protections	<ul style="list-style-type: none"> • Overload • Short-circuit • Overvoltage 	...
Audio outputs	...	2 pcs CINCH
Main features	<ul style="list-style-type: none"> • Protection class : II • Box casing designed to wall mounting 	...
Image compression method	...	Smart H.265+ / H.265 / Smart H.264+ / H.264
Housing type	Plastic, Waterproof	...
Bitrate	...	max. 1280 Mbps
"Index of Protection"	IP67	...
Supported hard drives	...	16 x 20 TB SATA + 1 x eSATA , Raid 0/1/5/6/10
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 16 channels in the same time

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network interface	...	4 x RJ-45 10/100/1000/2500 Base-TX
Network functions	...	Full support via network, Remote records copying, Web-Server built-in
ONVIF	...	22.06
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
RTSP URL	...	• rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
USB	...	• 2 pcs USB 2.0 • 2 pcs USB 3.0
Serial ports	...	• 2 pcs RS-485 • 1 pcs RS-232
Alarm inputs / outputs	...	32 / 16
PTZ control	...	• IP Speed Dome Cameras • RS-485 - PELCO-D/P and others
Intelligent image analysis	...	✓
Motion Detection	...	✓



Main features	...	<ul style="list-style-type: none"> • Panel with LCD display, • Intelligent image analysis : IVS analysis - 10 rules, scene changing, face detection, • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Face recognition - supports 6 types of facial attributes extraction • Face recognition and analysis in real time (up to 16 photos per second) • Support for up to 40 face databases, including 300 000 face images • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) • AcuPick support - technology that uses artificial intelligence on both front-end and back-end to search through massive amounts of video data to quickly locate targets with high precision • EPTZ - advanced target detection and tracking algorithms that trigger alarms - can simultaneously zoom and track many people and/or vehicles <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	—
Power supply	...	<ul style="list-style-type: none"> • 100 ... 240 V AC @ 50 ± 2 Hz • Redundant power supply
Power consumption	...	max. 25 W (without HDD)
Operation temp	-20 °C ... 70 °C	-10 °C ... 55 °C
Weight	0.24 kg	13.91 kg
Dimensions	148 x 32 x 28 mm	485 x 543 x 133 mm
Supported languages	...	Polish, English
Manufacturer / Brand	...	DAHUA
Guarantee	3 years	3 years