



	ROUTER RG-EW3200GXPRO Wi-Fi 6, 2.4 GHz, 5 GHz 800 Mbps + 2402 Mbps REYEE	FURNITURE POWER DISTRIBUTION UNIT OR- GM-9032/GR (3 OUTLETS) ORNO
		
	634.13 PLN 634.13 PLN	128.00 PLN 128.00 PLN
Frequency range	2.4 GHz, 5 GHz	...
Rated voltage	...	230 V AC / 50 Hz
Total maximal current	...	16 A
Maximal total load	...	3680 W
Number of outlets	...	3 grounded outlets 16A/250V CEE 7/5, E type
Fuse	...	—
Switch	...	—
Antenna type	8 x Omnidirectional antenna - Integrated : • 6 dBi @ 5 GHz 4x4 MU-MIMO • 5 dBi @ 2.4 GHz 4x4 MU-MIMO	...
Wire gauge	...	Recommended : max. 3 x 1.5 mm ²
Length of the cable	...	—
Standards	IEEE 802.11 b/g/n @ 2.4 GHz , IEEE 802.11 a/n/ac/ax @ 5 GHz	...
Baud rates	800 Mbps + 2402 Mbps	...
Housing	...	Plastic + Aluminum, Steel - powder painted
"Index of Protection"	...	IP20
Color	...	Graphite + Black
LAN ports	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink	...
LED indicators	Status, Mesh	...
DDNS	✓	...
DHCP server	✓	...
Firmware update	✓	...
Protections	WPA/WPA2 Support DoS defence	...

Management interface	Web browser, Configuration using the Reyee Router application	...
Mobile phones support	Android: Free application Reyee Router iOS (iPhone): Free application Reyee Router	...
Transmitter power	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz	...
Power supply	12 V DC / 2.5 A (power adapter included)	...
Power consumption	≤ 36 W	...
Main features	<ul style="list-style-type: none"> • Support for Reyee Mesh technology, • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Static / dynamic routing • Built-in 4-port switch • Access Point • QoS • Remote management • DMZ • UPnP • Support for dynamic ARP mapping and static table • Port forwarding • Port Mapping • parental control • Guest Network - a separate and secure network for guests • DHCP client list • SSID hiding • IPv6 compliance • PPTP VPN Server / Client 	<ul style="list-style-type: none"> • Fixing in the opening of the table top • Pull-out panel with sockets at the push of a button
Operation temp	0 °C ... 45 °C	...
Permissible relative humidity	5 % ... 95 % (non-condensing)	...
Weight	0.77 kg	1.22 kg
Dimensions	230 x 230 x 162 mm	<ul style="list-style-type: none"> • 265 x 132 x 77 mm • 224 x 108 x 65 mm - Mounting dimensions (box)
Manufacturer / Brand	RUIJIE / REYEE	ORNO
Guarantee	2 years	2 years