



	IP CAMERA TC-C32WN SPEC:I5/Y/WIFI/4MM/V4.1 Wi-Fi - 1080p 4 mm TIANDY	IP CAMERA TC-C35US SPEC:I8/A/E/Y/M/S/H/2.7-13.5MM/V4.0 - 5 Mpx 2.7 ... 13.5 mm TIANDY
		
	508.00 PLN 508.00 PLN	1149.00 PLN 1149.00 PLN
Standard	IP	IP
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	1/2.8 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS
Lens	4 mm	2.7 ... 13.5 mm - Motozoom
View angle	83 °	98 ° ... 32 °
Range of IR illumination	50 m	80 m
RS-485 interface	...	—
Memory card slot	Micro SD card support up to 512GB	Micro SD card support up to 512GB
Image compression method	S+265 / H.265 / H.264	S+265 / H.265 / H.264
Alarm inputs / outputs	—	1 / 1
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network 	<ul style="list-style-type: none"> • Microphone built-in, • Audio input • Audio output • Audio transmission via network • Bi-directional audio streaming support • Compliance with the AAC standard
Main stream frame rate	25 fps @ 1080p	<ul style="list-style-type: none"> • 25 fps @ 5 Mpx • 50 fps @ 2 Mpx
Network interface	<ul style="list-style-type: none"> • Wi-Fi - 2.4 GHz IEEE 802.11 b/g/n, • 10/100 Base-T (RJ-45) 	10/100 Base-TX (RJ-45)
WEB Server	Built-in	Built-in
Max. number of on-line users	2	2
ONVIF	✓	✓
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus 	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus

Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address	DHCP or 192.168.1.2	192.168.1.2
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	3000, 3001	3000, 3001
PC client access ports	3000, 3001	3000, 3001
Port ONVIF	80	80
Intelligent image analysis	...	<ul style="list-style-type: none"> • classification of people and vehicles • crossing the line (tripwire) • video tampering • face detection
Main features	<ul style="list-style-type: none"> • Wi-Fi Module, Range : 50 m • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Privacy zones - max. 4 • Motion Detection • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • Motozoom lens • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate • Audio detection
Power supply	12 V DC	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 875 mA
Power consumption	≤ 6 W	≤ 10,5 W
Housing	Compact, Metal + Plastic	Compact - Metal
Color	White	White

"Index of Protection"	IP67	IP67
Vandal-proof	...	—
Operation temp	-40 °C ... 65 °C	-35 °C ... 65 °C
Weight	0.31 kg	0.94 kg
Dimensions	161 x 81 x 72 mm	239 x 90 x 90 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, Italian, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese	Polish, English, Arabic, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Vietnamese, German, Ukrainian, Portuguese, Albanian
Manufacturer / Brand	TIANDY	TIANDY
Guarantee	3 years	3 years