




	<a href="#">RESIDUAL CURRENT CIRCUIT BREAKER LE-402024 ONE-PHASE, AC TYPE 30 mA 25 A LEGRAND</a>	<a href="#">RESIDUAL CURRENT CIRCUIT BREAKER HNC-40/4/003 THREE-PHASE, AC TYPE 30 mA 40 A EATON</a>	<a href="#">CYLINDRICAL MAGNETIC CONTACT K-2-BR SATEL</a>
			
	285.61 NOK 285.61 NOK	406.95 NOK 406.95 NOK	46.33 NOK 46.33 NOK
Detection	...	...	Opening the door or window
Maximum reed switched voltage	...	...	20 V
Maximal switched current	...	...	20 mA
Device type	Residual current circuit breaker, One-phase, AC type	Residual current circuit breaker, Three-phase, AC type	...
Make distance	...	...	28 mm
Rated sensitivity	30 mA	30 mA	...
Break distance	...	...	40 mm
Rated current	25 A	40 A	...
Color	...	...	Brown
Number of poles	2	4	...
Breaking capacity	10000 A	6000 A	...
Rated voltage	230 V AC / 50 Hz	400 V AC / 50 Hz	...
Connectors type	screw terminals	screw terminals	...
Wire gauge	...	1 x 1.5 mm <sup>2</sup> - 35 mm <sup>2</sup> or 2 x 16 mm <sup>2</sup>	...
Main features	...	<ul style="list-style-type: none"> <li>• Contact position indicator</li> <li>• Can be connected with using the supply busbars fork-type or prong-type</li> <li>• Possibility of sealing</li> </ul>	...
Housing	Plastic, DIN, TS-35 rail mounting	Plastic, DIN, TS-35 rail mounting	...
Width in 17.5 mm modules	2	4	...
Weight	0.182 kg	0.317 kg	0.01 kg
Dimensions	36 x 83 x 75 mm	70 x 83 x 75 mm	28 x 8.8 x 9.8 mm
Manufacturer / Brand	LEGRAND	EATON	SATEL
Guarantee	2 years	2 years	2 years