



	<a href="#">IP CAMERA TC-C34XP</a> <a href="#">SPEC:W/E/Y/2.8MM/V4.0</a> Color Maker - 4 Mpx 2.8 mm TIANDY	<a href="#">AHD, HD-CVI, HD-TVI,</a> <a href="#">CVBS, TCP/IP DVR DHI-</a> <a href="#">XVR5104HS-4KL-X 4</a> <a href="#">CHANNELS DAHUA</a>
		
	795.00 PLN 795.00 PLN	773.00 PLN 773.00 PLN
Standard	IP	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs	...	4 pcs BNC
Video outputs	...	• 1 pcs HDMI 4K • 1 pcs VGA
Audio inputs	...	• 1 pcs CINCH, • 4 - Audio support via coaxial cable, HD-CVI only
Audio outputs	...	1 pcs CINCH
Resolution	2592 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	• 100 ° (manufacturer data) • 91 ° (our tests result)	...
White light LED illuminator range	15 m	...
Memory card slot	Micro SD card support up to 512GB	...
Image compression method	S+265 / H.265 / H.264	H.265 / H.265+ / H.264 / H.264+
Audio	• Microphone built-in • Audio transmission via network	...
Main stream frame rate	25 fps @ 4 Mpx	...
Interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	2	...
ONVIF	✓	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart</a> <a href="#">Client Express</a>	...
Default IP address	DHCP or 192.168.1.2	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...
PC client access ports	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• intrusion</li> </ul>	...
Power consumption	≤ 7 W	...
Housing	Dome - Metal + Plastic	...
"Index of Protection"	IP66	...
Mechanical protection class	—	...
Operation temp	-40 °C ... 65 °C	...

Image records resolutions	...	<ul style="list-style-type: none"> <li>• HD-CVI : 8 Mpx 4K UHD - 3840 x 2160 , 4K-N - 1920 x 2160 , 6 Mpx - 2880 x 1920 , 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 ,</li> <li>• AHD : 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 , 4M-N - 1280 x 1440 , 3 Mpx - 2048 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 ,</li> <li>• HD-TVI : 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 , 4M-N - 1280 x 1440 , 3 Mpx - 2048 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 ,</li> <li>• CVBS : 960H - 960 x 576 ,</li> <li>• IP : max. 8 Mpx - 3840 x 2160</li> </ul>
Recording speed adjustment	...	<ul style="list-style-type: none"> <li>• IP : 8 Mpx @ 1 ... 25 fps</li> <li>• Channel 1 : 8 Mpx @ 1 ... 7 fps 6 Mpx @ 1 ... 10 fps 5 Mpx @ 1 ... 12 fps</li> <li>• Channels 1 - 4 : 4K-N @ 1 ... 15 fps 4 Mpx @ 1 ... 15 fps 4M-N @ 1 ... 25 fps 3 Mpx @ 1 ... 15 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel</li> </ul>
Operation modes	...	4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 2 x IP
Recording modes	...	Manual, Motion Detection, Schedule

Supported hard drives	...	1 x 10 TB SATA
External storage devices backup	...	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records	...	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>
Alarm inputs / outputs	—	—
PTZ control	...	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Motion Detection</li> <li>• Privacy zones</li> </ul>	Intelligent image analysis : crossing the line (tripwire), intrusion, abandoned/missing object, face detection
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V / 590 mA</li> </ul>	12 V DC / 2 A (power adapter included)

Color	White	Black
Weight	0.33 kg	0.88 kg
Dimensions	Ø 117 x 96 mm	260 x 236 x 48 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	Polish, English, Czech, Danish, French, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian
Country of origin	...	China
Manufacturer / Brand	TIANDY	DAHUA
Guarantee	3 years	3 years