

	POWER SUPPLY ADAPTER ZR48-158/R10 48 V DC 3.3 A	POWER SUPPLY ADAPTER ZR48-158 48 V DC 3.3 A	POWER SUPPLY ADAPTER ZR48-158X2 2 x 48 V DC 3.3 A	8-PORT PATCH PANEL WITH POWER ADAPTER ZR48-158/POE-8 48 V DC 3.3 A	PATCH PANEL POE-16/R19	PATCH PANEL POE-8/R	PATCH PANEL POE-8/R10	PATCH PANEL POE-8/R19
								
	57.56 EUR 57.56 EUR	67.42 EUR 67.42 EUR	110.04 EUR 110.04 EUR	90.68 EUR 90.68 EUR	66.92 EUR 66.92 EUR	27.65 EUR 27.65 EUR	37.14 EUR 37.14 EUR	43.45 EUR 43.45 EUR
Adapter type	Switching	Switching	Switching - 2 pcs	Switching	...	...	...	...
Maximal output current	...	...	...	...	550 mA / Output	550 mA / Output	550 mA / Output	550 mA / Output
Power voltage	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	Selecting by the switch for each adapter separately • 90 V ... 132 V AC, • 180 V ... 264 V AC	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	...	...	...	...
Voltage frequency range	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	...	...	...	...
Output power	160 W	160 W	2 x 160 W	160 W	...	...	...	...
Output voltage	48 V DC	48 V DC	2 x 48 V DC	48 V DC	max. 60 V	max. 60 V	max. 60 V	max. 60 V
Output voltage adjustment	45.6 V ... 52.8 V DC	45.6 V ... 52.8 V DC	45.6 V ... 52.8 V DC	45.6 V ... 52.8 V	...	...	...	...
Maximal load	3.3 A	3.3 A	2 x 3.3 A	3.3 A 550 mA / Output	...	...	...	...
Efficiency	89 %	89 %	89 %	89 %	...	...	...	...
Power supply distance	...	...	...	100 m	...	...	...	...
Housing	...	...	...	...	1 U Rack 19"	...	1 U Rack 10"	1 U Rack 19"
MTBF (Mean Time Between Faults)	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	> 700000 h - Telcordia SR-332	...	...	...	...
Number of inputs	...	...	...	8 pcs (RJ-45)	16 pcs (RJ-45)	8 pcs (RJ-45)	8 pcs (RJ-45)	8 pcs (RJ-45)
Number of outputs	...	...	...	8 pcs (RJ-45)	16 pcs (RJ-45)	8 pcs (RJ-45)	8 pcs (RJ-45)	8 pcs (RJ-45)
Protections	• Overvoltage • Short-circuit • Overload	• Overvoltage • Short-circuit • Overload	• Overvoltage • Short-circuit • Overload	• 8 PTC polymer fuses - 550 mA • Overvoltage • Short-circuit • Overload	• Short-circuit • Overload	• Short-circuit • Overload	• Short-circuit • Overload	• Short-circuit • Overload
Manufacturer / Brand	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA
Main features	...	...	...	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA Polymer fuse	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA • Mounting with self- adhesive bases The self- adhesive distance elements allow to easy PCB assembly.	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA	Pin numbers for RJ-45 connector • DATA 1, 2 and 3, 6 • Power supply 4, 5 (+) and 7, 8 (-) • Supported data rates 10 / 100 Mbps • Maximal load for single port 550 mA
LED indicators	...	...	...	• red LED - power on 48 V • green LED - failed fuse	Power supply	Power supply	Power supply	Power supply
Housing type	1 U Rack 10"	1 U Rack 19"	1 U Rack 19"	1 U Rack 19"	...	...	...	...
Operation temp. / Relative humidity	-10 °C ... 70 °C / 10 % ... 80 %	-10 °C ... 70 °C / 10 % ... 80 %	-10 °C ... 70 °C / 10 % ... 80 %	-10 °C ... 70 °C / 10 % ... 80 %	-10 °C ... 55 °C / < 95 %	-10 °C ... 55 °C / < 95 %	-10 °C ... 55 °C / < 95 %	-10 °C ... 55 °C / < 95 %
Weight	0.57 kg	0.68 kg	1.13 kg	0.74 kg	0.34 kg	0.078 kg	0.175 kg	0.29 kg
Dimensions	256 x 44 x 99 mm	482 x 44 x 100 mm	482 x 44 x 100 mm	483 x 44 x 102 mm	483 x 44 x 36 mm	220 x 44 x 25 mm	256 x 44 x 35 mm	483 x 44 x 36 mm
Guarantee	5 years	5 years	5 years	5 years	3 years	3 years	3 years	3 years