

	COUPLER N-GN-G	SOCKET N-G/ZAC.H-1000	CRIMP SOCKET N-G/ZAC.H-155	CRIMP SOCKET N-G/ZAC.RG-58	COUPLER N-W/N-W	PLUG N-W/SKR.H-1000	CRIMP PLUG N-W/ZAC.CNT-400	CRIMP PLUG N-W/ZAC.H-1000	CRIMP PLUG N-W/ZAC.H-155	CRIMP PLUG N-W/ZAC.RG-58
										
	3.33 EUR 3.33 EUR	3.13 EUR 3.13 EUR	3.06 EUR 3.06 EUR	2.57 EUR 2.57 EUR	4.22 EUR 4.22 EUR	4.67 EUR 4.67 EUR	2.74 EUR 2.74 EUR	3.49 EUR 3.49 EUR	3.14 EUR 3.14 EUR	3.14 EUR 3.14 EUR
Attachment of connector elements	...	Crimping	Crimping	Crimping	...	Twisting on	Crimping	Crimping	Crimping	Crimping
Shield fastening	...	Crimping	Crimping	Crimping	...	Twisting on	Crimping	Crimping	Crimping	Crimping
Connector type	Coupler "N" Socket / "N" Socket	"N" Socket	"N" Socket	"N" - socket	Coupler "N" Plug / "N" Plug	"N" Plug	"N" Plug	"N" Plug	"N" Plug	"N" - plug
Wire mounting	...	Soldering	Soldering	Crimping	...	Soldering	Soldering	Soldering	Soldering	Crimping
Application	...	Coaxial cable	Coaxial cable	Coaxial cable	...	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable
Cable diameter	...	max. 10.3 mm	max. 6.1 mm	max. 5.0 mm	...	max. 10.3 mm	max. 10.29 mm	max. 10.3 mm	max. 6.1 mm	max. 5.0 mm
Impedance	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω	50 Ω
Material	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Example of application	...	• TRI-LAN-400 • H-1000	• TRI-LAN/100 • H-155	RG58	...	• TRI-LAN-400 • H-1000	• CNT-400	• TRI-LAN-400 • H-1000	• TRI-LAN/100 • H-155	RG58
Main features	• Very easy and quick assembly • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C	• Wide frequency range • Corrosion resistance	• Very easy and quick assembly • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C	• Wide frequency range • Corrosion resistance
Weight	0.026 kg	0.019 kg	0.040 kg	0.02 kg	0.042 kg	0.040 kg	0.036 kg	0.025 kg	0.021 kg	0.02 kg
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00