

	ADAPTER AD-UTP 2x RJ45 / 1x RJ45	ADAPTER AD-UTP-2W/2G 2 x RJ45	ADAPTER AD-UTP-2W/WG 2 x RJ45	ADAPTER AD-UTP/R 2x RJ45 / 1x RJ45	USB 3.0 ETHERNET NETWORK ADAPTER TL-UE300 TP-LINK	USB 3.0 ETHERNET NETWORK ADAPTER TL-UE300C TP-LINK	SFP DUMMY PLUG P2P02 SFP/B	BRACKET BR-09ME MIKROTIK	UNIFI NETWORK DEVICES CONTROLLER UNIF-LIC-CK UBIQUITI
									
	4.25 EUR 5.23 EUR	5.57 EUR 6.85 EUR	4.97 EUR 6.11 EUR	4.77 EUR 5.87 EUR	14.30 EUR 17.59 EUR	14.64 EUR 18.01 EUR	0.30 EUR 0.37 EUR	7.34 EUR 9.03 EUR	92.33 EUR 113.57 EUR
Processor	Quad-Core SoC
Application	SFP dummy plug
Supported standards	Gigabit Ethernet	Gigabit Ethernet
Material	Rubber	Plastic - amvINITE	...
Chipset	RTL8153	RTL8153
Bearing capacity	8 kg	...
Supported transmission speeds	10 / 100 / 1000 Mbps	10 / 100 / 1000 Mbps
Distance from mounting surface	100 mm	...
In package	2 pcs - The price for package
Interface	USB 3.0	USB 3.0
Length of the mounting element	120 mm	...
Connectors type	• 2 x RJ-45 shielded socket • 1 x RJ-45 plug - Shielded	• Adapter 1 : 2 x RJ-45 plug + 1 x RJ-45 socket • Adapter 2 : 3 x RJ-45 socket	• Adapter 1 : 2 x RJ-45 plug + 1 x RJ-45 socket • Adapter 2 : 1 x RJ-45 plug + 2 x RJ-45 socket	• 2 x RJ-45 plug • 1 x RJ-45 socket
The diameter of the fixing element	Ø 40 mm	...
Memory	• RAM : 2 GB DDR, • embedded : 16 GB
Length of the cable	12 cm	3 cm	3 cm	5 cm
Network interface	10/100/1000 Base-T
Default IP address	DHCP
Ports	• 1 x RJ45, • 1 x USB 3.0 - A type	• 1 x RJ45, • 1 x USB 3.0 - C type
Pole diameters range	Ø 35 ... Ø 70 mm	...
Operating system	Windows XP/Vista/7/8/10, Linux, Mac OS, Chrome	Windows XP/Vista/7/8/10, Linux, Mac OS, Chrome
Main features	• Compact folding design • Operation status LED indicator • Plug & Play	• Compact folding design • Operation status LED indicator • Plug & Play
Certificates	FCC, CE	FCC, CE	CE, FCC, IC
Main features	High resistance to wind and weather	• Easy and uniform management system for many devices • Access by a cloud (P2P) • Clear graphical interface • Management of switches and access points for LAN, WAN and VLAN networks • Access to detailed statistics of network usage • User groups management • Wireless network coverage map
Power supply	• PoE (802.3af), • 5 V DC / 1 A - USB-C (power adapter not included)
Power consumption	≤ 5 W
Color	Black	Gray	White
Weight	0.04 kg	0.05 kg (total)	0.044 kg (total)	0.022 kg	0.024 kg	0.022 kg	0.0005 kg	0.316 kg	0.11 kg
Dimensions	50 x 37 x 21 mm	• Adapter 1 : 115 x 19 x 19 mm • Adapter 2 : 120 x 40	• Adapter 1 : 115 x 19 x 19 mm • Adapter 2 : 120 x 30	123 x 19 x 20 mm	• 71 x 26 x 16 mm • Length of the cable : 35 mm	• 71 x 26 x 16 mm • Length of the cable : 40 mm	15 x 14 x 9 mm	102 x 135 x 150 mm	122 x 43 x 22 mm
Operation temp	0 °C ... 40 °C
Permissible relative humidity	20 ... 90 % (non-condensing)
Manufacturer / Brand	TP-LINK	TP-LINK	UBIQUITI
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00