

	INDOOR PANEL IP VTH5241DW-S2 Wi-Fi / IP DAHUA	WIRELESS VIDEO DOORPHONE DS-KV8113- WME1(C)/SU Wi-Fi / IP Hikvision	WIRELESS VIDEO DOORPHONE DS-KV8213- WME1(C)/SU Wi-Fi / IP Hikvision	WIRELESS VIDEO DOORPHONE DS-KV8413- WME1(C) Wi-Fi / IP Hikvision	WIRELESS VIDEO DOORPHONE DS-KV9503- WBE1 Wi-Fi / IP Hikvision
					
	477.17 EUR 477.17 EUR	238.35 EUR 238.35 EUR	269.90 EUR 269.90 EUR	290.70 EUR 290.70 EUR	653.36 EUR 653.36 EUR
Sensor	...	2 Mpx	2 Mpx	2 Mpx	2 x 2 Mpx
Compatibility	Interphone installation - DAHUA IP	...	...	...	...
Camera view angle	...	124 °	124 °	124 °	88 °
IR illuminator	...	✓	✓	✓	✓
Shield	10 " capacitive touch screen	...	...	...	...
LED illuminator	...	—	—	—	—
Resolution	1024 x 600	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
PIR detector	...	—	—	—	—
Internal memory	—	...	...	...	...
Memory card slot	Micro SD memory cards up to 32GB support (possible local recording)	...	...	...	...
Display	...	...	...	...	4.3 " IPS, 800 x 480 px - capacitive touch screen
Doorbell button	...	1 pcs	2 pcs	4 pcs	1 pcs
proximity reader built-in	...	13.56 MHz S50	13.56 MHz S50	13.56 MHz S50	13.56 MHz S50
Wireless transmission range	...	The range limited only by the availability of the Wi-Fi network	The range limited only by the availability of the Wi-Fi network	The range limited only by the availability of the Wi-Fi network	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard	...	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network interface	...	• Ethernet • Wi-Fi	• Ethernet • Wi-Fi	• Ethernet • Wi-Fi	• Ethernet • Wi-Fi
RS-485 interface	...	✓	✓	✓	✓
Video output	...	—	—	—	—
Video format	...	H.264	H.264	H.264	H.264, H.265
Supported audio formats	...	G.711	G.711	G.711	G.711
Controlling	One-touch action buttons + capacitive touch screen	...	...	...	...
Alarm inputs	• 6 wired channels • 8 wireless channels : 433 MHz	4 pcs	4 pcs	4 pcs	4 pcs
Alarm outputs	1	...	...	...	2 pcs - Relay (30V DC / 2A)
Main features	• Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save images if there is no response to the doorbell, • Records a short video message if there is no response to the doorbell button, • IP Dahua cameras support	• WDR - Wide Dynamic Range • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi / LAN, • Tamper detection - removing from mounting surface • Video Doorphone is mounted in a surface housing • The device has the ability to work with the Hik-Connect application for mobile devices, without the use of an internal panel • IK rating : IK08	• WDR - Wide Dynamic Range • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi / LAN, • 2000 indexed users • Memory of 10 000 RFID cards • Output button support max. 2 • Lock control : 2 • Door status detection : 2 • Tamper detection - removing from mounting surface • Video Doorphone is mounted in a surface housing • IK rating : IK08	• WDR - Wide Dynamic Range • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi / LAN, • 2000 indexed users • Memory of 10 000 RFID cards • Output button support max. 2 • Lock control : 2 • Door status detection : 2 • Tamper detection - removing from mounting surface • Video Doorphone is mounted in a surface housing • IK rating : IK08	• Lock control, • Face recognition - Memory of 10000 face templates, • 20 000 indexed users, • WDR - 120 dB - Wide Dynamic Range • Bidirectional communication, • Full support via network : WiFi / LAN, • Tamper detection - removing from mounting surface • Video Doorphone is mounted in a surface housing • The device has the ability to work with the Hik-Connect application for mobile devices, without the use of an internal panel

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	• 12 V DC / 670 mA, • PoE (802.3af)	• PoE (802.3af) • 12 V DC / 830 mA (max)	• PoE (802.3af) • 12 V DC / 830 mA (max)	• PoE (802.3af) • 12 V DC / 830 mA (max)	• PoE (802.3af) • 12 V DC / 1.5 A (power adapter included)
Power consumption	≤ 8 W (operation)	< 10 W (operation)	< 10 W (operation)	< 10 W (operation)	< 6 W (operation)
Housing	...	Aluminum + Plastic, Protects against weather conditions	Aluminum + Plastic, Protects against weather conditions	Aluminum + Plastic, Protects against weather conditions	Aluminum + Plastic, Protects against weather conditions
Mount	...	Surface-mounted	Surface-mounted	Surface-mounted	Surface-mounted
Color	White	Black + Gray	Black + Gray	Black + Gray	Black + Gray
"Index of Protection"	...	IP65	IP65	IP65	IP65
IK rating	...	...	...	...	IK08
Operation temp	-10 °C ... 55 °C	-40 °C ... 53 °C	-40 °C ... 53 °C	-40 °C ... 53 °C	-40 °C ... 60 °C
Weight	1 kg	0.38 kg	0.38 kg	0.38 kg	0.40 kg
Dimensions	265 x 180 x 22 mm	174 x 91 x 33 mm	174 x 91 x 30 mm	174 x 91 x 30 mm	182 x 85 x 32 mm
Supported languages	English	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	Polish, English, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand	DAHUA	Hikvision	Hikvision	Hikvision	Hikvision
SAP Code	...	305303880	305303882	305303884	305303711
Guarantee	3 years	3 years	3 years	3 years	3 years