




	<a href="#">REPEATER VHD-15 AHD, HD-CVI, HD-TVI SIGNAL AMPLIFIER DELTA</a>	<a href="#">CONVERTER HV/HDMI+HV-V2</a>	<a href="#">VIDEO SEPARATOR AHD, HD-CVI, HD-TVI, PAL PFM791 DAHUA</a>
			
	39.47 EUR 39.47 EUR	83.05 EUR 83.05 EUR	18.59 EUR 18.59 EUR
Input	...	1 x BNC - AHD / HD-CVI / HD-TVI / CVBS @ 8 Mpx (max)	...
Input impedance	...	...	75 Ω
Output impedance	...	...	75 Ω
Opto-isolation between input and output	...	...	800 V - peak
Standard	<ul style="list-style-type: none"> <li>• AHD - 5 Mpx, 12 fps,</li> <li>• HD-CVI - 1080p, 25 fps,</li> <li>• HD-TVI - 5 Mpx, 12 fps,</li> <li>• CVBS - PAL / NTSC</li> </ul>	...	AHD, HD-CVI, HD-TVI, PAL
Insertion loss	...	...	0.5 dB
Device type	Active	...	Passive
Output	...	<ul style="list-style-type: none"> <li>• 1 x BNC - AHD / HD-CVI / HD-TVI / CVBS @ 8.3 Mpx (max),</li> <li>• 1 x HDMI @ 1080p 60 fps</li> </ul>	...
Bandwidth	...	...	0 ... 65 MHz
Output signal possible standards	...	PAL / NTSC	...
Supported resolutions	...	<ul style="list-style-type: none"> <li>• HDMI - 1080p</li> <li>• BNC - 8.3 Mpx (max)</li> </ul>	...
OSD menu	...	—	...
The ability of signal regeneration	150 m - Twisted-pair cable , 300 m - RG59 , 500 m - Triset113	...	...
ESD protection	...	...	600 V (contact discharge) 8000 V (air-gap discharge)
Housing type	...	...	ABS
Main features	...	<ul style="list-style-type: none"> <li>• In the case of no input signal, the device displays a test chart (color bars) on the connected screen</li> <li>• Automatic recognition of the resolution - LED indication</li> <li>• USB cable 0.9 m (included)</li> <li>• BNC cable 0.9 m (included)</li> </ul>	<ul style="list-style-type: none"> <li>• Overvoltage protection : 4 kV 10/700 μs</li> <li>• Compliance with IEC61000-4-2, IEC61000-4-5 standards</li> <li>• MTBF (Mean Time Between Faults) &gt; 20000 h</li> <li>• Length of the cables 2 x 13 cm</li> </ul>

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	...	...	-20 °C ... 55 °C
Permissible relative humidity	...	...	0 % ... 95 %
Gain	4.43 MHz @ 6.82 dB 11 MHz @ 11.57 dB 21 MHz @ 17.07 dB 38 MHz @ 24.17 dB 42 MHz @ 25.23 dB 67.5 MHz @ 21.83 dB	...	...
Power supply	<ul style="list-style-type: none"> <li>• 8 V ... 24 V DC (power adapter not included)</li> <li>• The possibility of remote powering through the unused pairs of twisted-pair cable</li> </ul>	5 V DC / 2 A (power adapter included)	—
Current consumption	< 50 mA	...	...
Coaxial socket impedance	75 Ω	...	...
Symmetrical socket impedance	100 Ω	...	...
Number of inputs	1	...	1 - BNC socket
Number of outputs	1	...	1 - BNC plug
Coaxial socket type	BNC socket	...	...
Symmetrical socket type	terminals	...	...
Weight	0.080 kg	0.18 kg	0.034 kg
Dimensions	103 x 62 x 29 mm	108 x 95 x 25 mm	42 x 23 x 16 mm
Manufacturer / Brand	DELTA	...	DAHUA
Guarantee	3 years	2 years	3 years