

	VIDEO SPLITTER RV-1/2- UHD	VIDEO SPLITTER RV-1/4P	VIDEO SPLITTER RV-2/4P	VIDEO SPLITTER RV-4/8PR	VIDEO SPLITTER RV-8/16PR	VIDEO SPLITTER RV-16/32- UHD/R19	VIDEO SPLITTER RV-8/16- UHD/R	VIDEO SPLITTER RV-8/16- UHD/R19
								
	17.13 EUR 17.13 EUR	18.97 EUR 18.97 EUR	18.74 EUR 18.74 EUR	25.78 EUR 25.78 EUR	48.07 EUR 48.07 EUR	158.27 EUR 158.27 EUR	52.07 EUR 52.07 EUR	89.61 EUR 89.61 EUR
Outputs configuration	...	...	...	✓	✓	...	...	...
Standard	• AHD - 8 Mpx 4K UHD, • HD-CVI - 8 Mpx 4K UHD, • HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC	CVBS - PAL / NTSC	CVBS - PAL, NTSC	CVBS - PAL, NTSC	CVBS - PAL, NTSC	• AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC	• AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC	• AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Number of inputs	1 pcs BNC	1 pcs BNC	2 pcs BNC	4 pcs BNC	8 pcs BNC	16 pcs BNC	8 pcs BNC	8 pcs BNC
Number of outputs	2 pcs BNC	4 pcs BNC	4 pcs BNC	8 pcs BNC	16 pcs BNC	32 pcs BNC	16 pcs BNC	16 pcs BNC
Input / Output protection	...	...	...	...	...	...	ESD, IEC 61000-4-2, ±30kV contact, ±30kV airLightning, IEC 61000-4-5, 12A (t _p =8/20µs)	...
Bandwidth	0 ... 120 MHz (-3dB)	0 ... 40 MHz (-3dB)	0 ... 40 MHz (-3dB)	0 ... 40 MHz (-3dB)	0 ... 40 MHz (-3dB)	0 ... 120 MHz (-3dB)	0 ... 120 MHz (-3dB)	0 ... 120 MHz (-3dB)
Inputs impedance	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω
Outputs impedance	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω
Input protection	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t _p =8/20µs)	...	...	...	...	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t _p =8/20µs)	...	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t _p =8/20µs)
Outputs protection	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t _p =8/20µs)	...	...	...	...	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t _p =8/20µs)	...	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t _p =8/20µs)
Power supply	12 V DC (power adapter not included)	12 V DC (power adapter not included)	12 V DC (power adapter not included)	12 V DC (power adapter not included)	12 V DC (power adapter not included)	7 ... 26 V DC (power adapter not included)	7 ... 26 V DC (power adapter not included)	7 ... 26 V DC (power adapter not included)
Housing type	...	...	...	...	...	1 U Rack 19"	...	1 U Rack 19"
Current consumption	40 mA	60 mA	50 mA	80 mA	100 mA	120 mA @ 12 V DC	60 mA @ 12 V DC	120 mA @ 12 V DC
Gain	0 dB	0 dB	0 dB	0 dB	0 dB	0 dB	0 dB	0 dB
Weight	0.07 kg	0.098 kg	...	0.220 kg	0.350 kg	0.44 kg	0.13 kg	0.34 kg
Dimensions	117 x 30 x 62 mm	117 x 30 x 80 mm	117 x 30 x 80 mm	213 x 36 x 93 mm	222 x 36 x 110 mm	490 x 44 x 38 mm	218 x 40 x 22 mm (without stand)	490 x 44 x 38 mm
Manufacturer / Brand	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA
Guarantee	5 years	3 years	3 years	3 years	3 years	5 years	5 years	5 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00