

	THERMOSTAT FZK-011	THERMOSTAT KTO-011	THERMOSTAT FOR FAN COOLERS KTS-011	THERMOSTAT ZR-011	FAN SPEED CONTROLLER ER-1	THERMOSTAT MOUNTING EAR A19-TT
						
	18.40 EUR 18.40 EUR	5.75 EUR 5.75 EUR	6.44 EUR 6.44 EUR	11.88 EUR 11.88 EUR	5.76 EUR 5.76 EUR	1.51 EUR 1.51 EUR
Application	...	...	...	...	...	Rack 19"
Power supply	...	...	...	...	12 V DC	...
Sensor type	Bimetallic	Bimetallic	Bimetallic	Bimetallic	...	...
Material	...	...	...	...	...	Steel - powder painted
Maximal current consumption	...	...	10 A	...	...	...
Color	...	...	...	...	...	Black
FAN output max. current consumption	...	...	...	...	• Thermistor placed on the board : 150 mA • Thermistor placed on the cable : 750 mA	...
Contact type	• 1 x NC - opened after exceeding the set temperature, • 1 x NO - closed after exceeding the set temperature	NC - opened after exceeding the set temperature	...	• 1 pcs NC - opened after exceeding the set temperature, • 1 pcs NO - closed after exceeding the set temperature Each contact has its own temperature setting	...	...
Maximal power voltage	250 V AC	250 V AC	250 V AC	250 V AC	...	...
FAN output voltages	...	...	...	...	25 °C - 6 V 40 °C - 11 V	...
Mounting	...	...	DIN rail 35 mm	...	...	...
Relay maximal load	• 10 A - NC, • 5 A - NO	10 A	...	10 A	...	...
Manufacturer / Brand	...	...	...	...	DELTA	...
Temperature set range	-20 °C ... 60 °C	0 °C ... 60 °C	0 °C ... 60 °C	0 °C ... 60 °C	...	...
Hysteresis	7 °C ± 4 °C	7 °C ± 4 °C	7 °C ± 4 °C	7 °C ± 4 °C	...	...
Operation temp	-20 °C ... 80 °C	-20 °C ... 80 °C	-20 °C ... 80 °C	-20 °C ... 80 °C	...	...
"Index of Protection"	IP20	IP20	IP20	IP20	...	...
Assembly	DIN TS-35 rail	DIN TS-35 rail	...	DIN TS-35 rail	...	...
Weight	0.062 kg	0.040 kg	0.042 kg	0.090 kg	0.08 kg	0.036 kg
Dimensions	65 x 50 x 38 mm	60 x 43 x 33 mm	60 x 43 x 33 mm	65 x 50 x 46 mm	31 x 25 x 18 mm	97 x 68 x 1 mm
Guarantee	2 years	2 years	2 years	2 years	3 years	2 years