

	SEMICONDUCTOR HEATER HG-140-100W	SEMICONDUCTOR HEATER HG-140-150W	SEMICONDUCTOR HEATER HG-140-15W	SEMICONDUCTOR HEATER HG-140-45W	SEMICONDUCTOR HEATER HG-140-60W	FAN HEATER HVL-031-100W	FAN HEATER HVL-031-150W
							
	23.64 EUR 23.64 EUR	32.03 EUR 32.03 EUR	14.87 EUR 14.87 EUR	17.16 EUR 17.16 EUR	20.97 EUR 20.97 EUR	53.00 EUR 53.00 EUR	58.33 EUR 58.33 EUR
Heating element	PTC thermistor - semiconductor, self regulating	PTC thermistor - semiconductor, self regulating	PTC thermistor - semiconductor, self regulating	PTC thermistor - semiconductor, self regulating	PTC thermistor - semiconductor, self regulating	High power resistor	High power resistor
Heating capacity	...	...	...	...	...	100 W	150 W
Radiator	Aluminum - Extruded profiles, Anodized surface	Aluminum - Extruded profiles, Anodized surface	Aluminum - Extruded profiles, Anodized surface	Aluminum - Extruded profiles, Anodized surface	Aluminum - Extruded profiles, Anodized surface	Aluminum - Die-cast housing, Glass bead blasted surface	Aluminum - Die-cast housing, Glass bead blasted surface
Number of fan coolers	...	...	...	...	...	1 pcs	1 pcs
Minimal airflow	...	...	...	...	...	35 m³/h	35 m³/h
Connectors	Cable terminals - 3 pcs	Cable terminals - 3 pcs	Cable terminals - 3 pcs	Cable terminals - 3 pcs	Cable terminals - 3 pcs	Cable terminals - 3 pcs	Cable terminals - 3 pcs
Power supply	110 V ... 265 V AC/DC	110 V ... 250 V AC/DC	110 V ... 265 V AC/DC	110 V ... 265 V AC/DC	110 V ... 265 V AC/DC	110 V ... 265 V AC/DC	110 V ... 265 V AC/DC
Current consumption	0.43 A (continuous operation), max. 4.5 A at the time of switching	max. 9.0 A - at the time of switching	max. 1.5 A - at the time of switching	max. 3.5 A - at the time of switching	max. 2.5 A - at the time of switching	...	...
Power	100 W	150 W	15 W	45 W	60 W	118 W	160 W
Assembly	DIN TS-35 rail, vertical	DIN TS-35 rail, vertical	DIN TS-35 rail, vertical	DIN TS-35 rail, vertical	DIN TS-35 rail, vertical	DIN TS-35 rail	DIN TS-35 rail
Thermostat switching on temperature	...	...	120 °C ... 140 °C	...	...	...	...
Enabled heater temp	120 °C ... 140 °C	120 °C ... 140 °C	...	120 °C ... 140 °C	120 °C ... 140 °C	...	...
Operation temp	-45 °C ... 70 °C	-45 °C ... 70 °C	-45 °C ... 70 °C	-45 °C ... 70 °C	-45 °C ... 70 °C	-45 °C ... 70 °C	-45 °C ... 70 °C
Weight	0.32 kg	0.47 kg	0.174 kg	0.176 kg	0.32 kg	0.48 kg	0.48 kg
Dimensions	184 x 70 x 58 mm	258 x 70 x 58 mm	109 x 70 x 58 mm	109 x 70 x 58 mm	184 x 70 x 58 mm	112 x 80 x 52 mm	112 x 80 x 52 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00