

	REPEATER VHD-15 AHD, HD-CVI, HD-TVI SIGNAL AMPLIFIER DELTA	VIDEO BALUN TR-1/SV OPTO-ISOLATOR
		
	38.35 EUR 38.35 EUR	32.94 EUR 32.94 EUR
Standard	...	• CVBS - PAL, NTSC
Video transmission range	...	max. 400 m UTP cat. 5e
Coaxial socket voltage range 75Ω (CVBS)	...	1 Vpp
Number of channels	...	1
Video bandwidth	...	0 ... 9 MHz (-3 dB)
Standard	• AHD - 5 Mpx, 12 fps, • HD-CVI - 1080p, 25 fps, • HD-TVI - 5 Mpx, 12 fps, • CVBS - PAL / NTSC	...
Device type	Active	Active
CMRR (dB @ 5MHz)	...	50 dB
Opto-isolation between input and output	...	1000 V (peak)
Opto-isolation between power and signal inputs / outputs	...	1000 V (peak)
The ability of signal regeneration	150 m - Twisted-pair cable , 300 m - RG59 , 500 m - Triset113	...
Power supply	• 8 V ... 24 V DC (power adapter not included) • The possibility of remote powering through the unused pairs of twisted-pair cable	12 V DC / 90 mA
Operation temp	...	-50 °C ... 55 °C
Current consumption	< 50 mA	...
Coaxial socket impedance	75 Ω	75 Ω
Permissible relative humidity	...	< 95 %
Symmetrical socket impedance	100 Ω	100 Ω
Number of inputs	1	...
Number of outputs	1	...
Coaxial socket type	BNC socket	BNC Straight socket
Symmetrical socket type	terminals	Cable terminals
Weight	0.080 kg	0.095 kg
Dimensions	103 x 62 x 29 mm	117 x 30 x 62 mm

Manufacturer / Brand	DELTA	DELTA
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00