

	HEADLIGHT LT-7 Virono	FLASHLIGHT LT-ATEX2AA-ENERGIZER	FLASHLIGHT LT-ATEX20-ENERGIZER	HEADLIGHT LT-HEADLIGHT-HARDCASE/325-ENERGIZER	FLASHLIGHT LT-SPOTLIGHT-HARDCASE-350/RECHARGEABLE-ENERGIZER	FLASHLIGHT LT-TACTICAL-TAC/700-ENERGIZER	HEADLIGHT LT-UNIVERSAL-PLUS/600-ENERGIZER	HEADLIGHT LT-VISION-HD/300-ENERGIZER	HEADLIGHT LT-VISION-HD/350-ENERGIZER	HEADLIGHT LT-VISION-HD/FOCUS-ENERGIZER	HEADLIGHT LT-VISION-ULTRA400-ENERGIZER	FLASHLIGHT LT-HARD-CASE-ENERGIZER	FLASHLIGHT LT-MULTI-USE-ENERGIZER	FLASHLIGHT LT-PIVOT-PLUS-ENERGIZER	FLASHLIGHT LT-PROJECT-PLUS-ENERGIZER
															
	1.62 EUR 1.62 EUR	25.26 EUR 25.26 EUR	29.51 EUR 29.51 EUR	28.25 EUR 28.25 EUR	67.93 EUR 67.93 EUR	30.23 EUR 30.23 EUR	7.78 EUR 7.78 EUR	13.84 EUR 13.84 EUR	16.43 EUR 16.43 EUR	16.43 EUR 17.61 EUR	19.29 EUR 19.29 EUR	22.77 EUR 22.77 EUR	8.89 EUR 8.89 EUR	24.32 EUR 24.32 EUR	25.37 EUR 25.37 EUR
Light source	1 pcs LED COB indicator	1 pcs LED	1 pcs LED	3 pcs LED	2 pcs LED	3 pcs LED	2 pcs LED - White + 1 pcs LED - Red	3 pcs LED	3 pcs LED - White + 2 pcs LED - Red	3 pcs LED - White + 2 pcs LED - Red	2 pcs LED - White + 1 pcs LED - Red + 1 pcs LED - Green	1 pcs LED	1 pcs LED	1 pcs LED	2 pcs LED
Power supply					Battery (included)										
Luminous flux	max. 45 lm (high) , min. 22 lm (low)	150 lm	150 lm	max. 325 lm (high) , min. 110 lm (low)	• 1000 lm (high), • 250 lm (low)	700 lm (high) , 100 lm (medium) , 20 lm (low)	100 lm (max)	max. 300 lm (high) , min. 45 lm (low)	max. 350 lm (high) , min. 45 lm (low)	315 lm (max)	max. 450 lm (high) , min. 30 lm (low)	300 lm	75 lm	• 300 lm (high) • 30 lm (low)	max. 400 lm (high) , min. 40 lm (Smart Dimming)
Range	max. 12 m (high)	~ 175 m	~ 175 m	~ 100 m (high) ~ 50 m (low)	550 m (high) 350 m (low)	max. 100 m (high)	~ 40 m	~ 55 m (high) ~ 25 m (low)	~ 80 m (high) ~ 30 m (low)	~ 85 m	~ 85 m (high) ~ 20 m (low)	~ 105 m	~ 30 m	~ 30 m	~ 125 m (high)
Battery power supply	Alkaline batteries : 3 pcs LR03 AAA (not included)	Alkaline batteries : 2 pcs LR6 (AA) (not included)	Alkaline batteries : 2 pcs LR20 (D) (not included)	Alkaline batteries : 3 pcs LR6 (AA) (included)		Lithium batteries : 2 pcs CR123A 3 V (included)	Alkaline batteries : 2 pcs LR03 AAA (included)	Alkaline batteries : 3 pcs LR03 AAA (included)	Alkaline batteries : 3 pcs LR03 AAA (included)	Alkaline batteries : 3 pcs LR03 AAA (included)	Alkaline batteries : 3 pcs LR03 AAA (included)	Alkaline batteries : 2 pcs AA (included)	alkaline battery : 1 pcs AA (included)	Alkaline batteries : 2 pcs AA (included)	Alkaline batteries : 4 pcs AA (included)
Main features	• Backup time : 7 h (high) ... 15 h (low), • 4 light modes : 100 % (high), 50 % (low), Blinking LED, SOS • Immunity to environmental changes • Waterproof • "Index of Protection" : IPX3 • Light and durable construction • Adjustable, elastic headstrap	• Backup time : 12 h • Certified intrinsically safe flashlight - division I, class I, II, III, • ATEX Certificate • IECEx Certificate, • Shatterproof lens, • Impact resistant up to 1 m, • Immersion resistant to a depth of 1 m, • Dust-proof • Waterproof • "Index of Protection" : IP67 • Handle for easy use when wearing gloves • Large ON/OFF button • Operation temp : -20 °C ... 40 °C	• Backup time : 65 h • Certified intrinsically safe flashlight - division I, class I, II, III, • ATEX Certificate • IECEx Certificate, • Shatterproof lens, • Impact resistant up to 1 m, • Immersion resistant to a depth of 1 m, • Dust-proof • Waterproof • "Index of Protection" : IP67 • Handle for easy use when wearing gloves • Large ON/OFF button • Operation temp : -20 °C ... 40 °C	• Super bright LEDs, • Tilt adjustment, • Backup time : 6.5 h (high) ... 22 h (low), • light modes : Spot + Wide / Spot / Wide, High / Low - Any combination of the above, • Impact resistant up to 7 m, • Immunity to environmental changes • Waterproof • "Index of Protection" : IPX4 • Light and durable construction • Universal helmet attachments • Non-slip headstrap fits most industrial helmets • Greater stability with integrated top strap	• Backup time : 7 h (high) ... 28 h (low), • Battery charging : USB-C • Power output : USB-A • Super bright LEDs • 2 light modes : High, Low, • Impact resistant up to 3 m • Immunity to environmental changes • Waterproof • "Index of Protection" : IPX4 • Small dimensions	• Backup time : 2 h (high) ... 30 h (low), • 4 light modes : High, Medium, Low, Stroboscopic mode, • Impact resistant up to 1 m • Rear button for easy operation • Pivoting metal clip for belt, bag or shirt • Immunity to environmental changes • Tilt adjustment • Backup time : ≤ 9 h (in economical mode) • Operation modes : Standard, Economical, Lighting in red • Shatterproof lens • Immunity to environmental changes • Light and durable construction	• Tilt adjustment, • Backup time : 4 h (high) ... 35 h (low), • 4 light modes : Spot + Wide - Low / High, Spot, Wide, • Fluent luminosity control (Smart Dimming) : 100 % (high) ... 10 % (low), • Impact resistant up to 1 m • Shatterproof lens, • Immunity to environmental changes • Waterproof • "Index of Protection" : IPX4 • Light and durable construction • Adjustable, elastic headstrap	• Tilt adjustment, • Backup time : 4 h (high) ... 35 h (low), • 7 light modes : High - Spot / Spot + Wide / Wide, Low - Spot / Spot + Wide / Wide, Night - Lighting in red, • Fluent luminosity control (Smart Dimming) : 100 % (high) ... 10 % (low), • Impact resistant up to 1 m • Shatterproof lens, • Immunity to environmental changes • Waterproof • "Index of Protection" : IPX4 • Light and durable construction • Adjustable, elastic headstrap	• Tilt adjustment • Backup time : ≤ 50 h (in economical mode) • Operation modes : Standard, Economical, Lighting in red • Shatterproof lens, • Immunity to environmental changes • Light and durable construction • Tilt adjustment, • Backup time : 2.75 h (high) ... 50 h (low), • 7 light modes : High - Spot / Wide, Low - Spot / Wide, Night - Lighting in red / Lighting in red • Stroboscopic mode / Lighting in green, • Fluent luminosity control (Smart Dimming) : 100 % (high) ... 10 % (low), • "The VisionGuard" technology gradually increases the light intensity to prevent a high beam straight in the users' eyes, • Low battery indicator • Impact resistant up to 1 m • Shatterproof lens, • Immunity to environmental changes • Waterproof • "Index of Protection" : IPX4 • Light and durable construction • Adjustable, elastic headstrap	• Light and durable construction, • High resistance to mechanical damages and weather conditions, • Impact resistant up to 7 m, • Shatterproof lens, • "Index of Protection" : IPX4 • Backup time : 6 h, • 10x brighter than standard LED light, • Light and durable construction, • The angular placed head with LED, • High resistance to mechanical damages and weather conditions, • Durable construction resistant to impact, • Impact resistant up to 7 m, • Shatterproof lens, • "Index of Protection" : IPX4 • Integrated magnets to attach to metal surfaces, • Pivoting metal clip for belt, bag or shirt	• Backup time : 5 h (high), 30 h (low), • Light and durable construction, • Vertically rotating head (175°) with LED, • High resistance to mechanical damages and weather conditions, • Durable construction resistant to impact, • Impact resistant up to 7 m, • Shatterproof lens, • "Index of Protection" : IPX4, • 2 light modes , • Fluent luminosity control (Smart Dimming)	• Backup time : 11 h (high) ... 50 h (Smart Dimming) • Light and durable construction, • High resistance to mechanical damages and weather conditions, • Impact resistant up to 7 m, • Shatterproof lens, • "Index of Protection" : IPX4, • 2 light modes , • Fluent luminosity control (Smart Dimming)			
Material	Plastic	Plastic	Plastic	Plastic	Plastic	Aluminum	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic / Rubber	Rubber / Plastic	Rubber / Plastic	Rubber / Plastic
Color	Black	Orange + Black	Orange + Black	Black	Black + Gray	Black	Black	Black / Red	Black / Green	Black / Gray	Black / Yellow	Graphite	Black	Black / Gray	Black / Gray
Weight	0.02 kg	0.128 kg	0.148 kg	0.226 kg (total)	0.62 kg (total)	0.07 kg	0.076 kg (total)	0.076 kg (total)	0.076 kg (total)	0.04 kg	0.076 kg (total)	0.11 kg	0.06 kg	0.2 kg	0.28 kg
Dimensions	75 x 40 x 33 mm	187 x 61 x 56 mm	212 x 61 x 56 mm	90 x 43 x 48 mm	235 x 89 x 153 mm	33 x 35 x 121 mm	94 x 37 x 25 mm	58 x 45 x 38 mm	58 x 45 x 38 mm	58 x 45 x 38 mm	58 x 45 x 38 mm	170 x 35 x 30 mm	90 x 41 x 27 mm	179 x 46 x 44 mm	216 x 57 x 45 mm
Manufacturer / Brand	Virono	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00