

	STRAIGHT PLUG LE-50100 230 V 16 A LEGRAND	ANGULAR PLUG LE-50101 230 V 16 A LEGRAND	ANGULAR PLUG LE-50103 230 V 16 A LEGRAND	ANGULAR PLUG LE-50105 230 V 16 A LEGRAND	ANGULAR PLUG LE-50107 230 V 16 A LEGRAND	STRAIGHT PLUG LE-50110 230 V 16 A LEGRAND	STRAIGHT PLUG LE-50114 230 V 16 A LEGRAND	ANGULAR PLUG LE-50172 230 V 16 A LEGRAND	ANGULAR PLUG LE-50173 230 V 16 A LEGRAND	ANGULAR PLUG LE-50175 230 V 16 A LEGRAND	STRAIGHT PLUG LE-50181 230 V 16 A LEGRAND	ANGULAR PLUG LE-50183 230 V 16 A LEGRAND	ANGULAR PLUG LE-50184 230 V 16 A LEGRAND	STRAIGHT PLUG LE-50309 230 V 2.5 A LEGRAND	STRAIGHT PLUG LE-50310 230 V 2.5 A LEGRAND	ANGULAR PLUG LE-50409 230 V 16 A LEGRAND	STRAIGHT PLUG LE-50444 230 V 16 A LEGRAND	ANGULAR PLUG LE-50461 230 V 16 A LEGRAND	STRAIGHT PLUG LE-555234 230 V 32 A LEGRAND	CEE-PLUG PCE-0246 400 V 32 A 4P 6H IP44 / IP54	CEE-PLUG PCE-0256 400 V 32 A 5P 6H IP44 / IP54	STRAIGHT PLUG POWER- PLUG/IP54/EPN 250 V 16 A	MAINS ADAPTER WITH GROUNDING WS-PLGS- UNI1	MAINS ADAPTER WITH GROUNDING WS-PLGS- UNI2	MAINS ADAPTER WITH GROUNDING WS-PLGS- UNI3
																									
Voltage	246 EUR 246 EUR	258 EUR 258 EUR	369 EUR 369 EUR	393 EUR 393 EUR	393 EUR 393 EUR	839 EUR 839 EUR	554 EUR 554 EUR	393 EUR 393 EUR	419 EUR 419 EUR	608 EUR 608 EUR	262 EUR 262 EUR	359 EUR 359 EUR	359 EUR 359 EUR	239 EUR 239 EUR	239 EUR 239 EUR	1263 EUR 1263 EUR	1724 EUR 1724 EUR	1075 EUR 1075 EUR	873 EUR 873 EUR	504 EUR 504 EUR	575 EUR 575 EUR	453 EUR 453 EUR	1.73 EUR 1.73 EUR	1.98 EUR 1.98 EUR	1.60 EUR 1.60 EUR
Max. current	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	250 V AC	250 V AC	250 V AC
Protection shutter	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	16 A	16 A	10 A
Rated voltage	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	400 V / 50 ... 60 Hz	400 V / 50 ... 60 Hz	250 V, 50 / 60 Hz	...	...	...
Maximal total load	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	3500 W	3500 W	...	...	...	...	...	✓	...	...
Number of poles	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	4P	5P	...	...	...	...
Maximal current load	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	2.5 A	2.5 A	16 A	16 A	16 A	32 A	32 A	32 A	16 A	...	...	...
Grounding	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	6h	6h	6h	✓	...	...
Electrical cable	max. 3 x 1.5 mm²	max. 3 x 1.5 mm²	max. 3 x 2.5 mm²	max. 3 x 2.5 mm²	max. 3 x 2.5 mm²	max. 3 x 2.5 mm²	max. 3 x 2.5 mm²	max. 3 x 1.5 mm²	max. 3 x 1.5 mm²	max. 3 x 1.5 mm²	max. 2 x 1.5 mm²	max. 2 x 1.5 mm²	max. 2 x 1.5 mm²	max. 2 x 0.75 mm²	max. 2 x 0.75 mm²	max. 3 x 1.5 mm²	max. 3 x 2.5 mm²	max. 3 x 1.5 mm²	max. 3 x 6 mm²	max. 4 x 6 mm²	max. 5 x 6 mm²	...	...	...	...
Cable terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	automatic spring terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	automatic spring terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	...	...	...
Plug type	CEE 7/6	CEE 7/6	CEE 7/6	CEE 7/6	CEE 7/6	CEE 7/6	CEE 7/6	CEE 7/7	CEE 7/7	CEE 7/7	CEE 7/17	CEE 7/17	CEE 7/17	CEE 7/16, C type	CEE 7/16, C type	CEE 7/7	CEE 7/6	CEE 7/7	CEE, 2P+Z	CEE	CEE	CEE 7/6 (Uni-Schuko)	...	...	...
IK rating	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	CEE 7/5	...	...	...	...	...	...
Socket type	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	CEE 7/5	...	...	...	...	...	...
Contact material	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	CuZn	CuZn	...	...	...	...	...
Maximum wire insulation diameter	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	20 mm	22 mm	...	...	...	...	...
Main features	...	...	...	...	...	...	...	Rotating body	Rotating body	...	...	...	...	...	...	Plug equipped with an on/off switch with LED indicator, compliant with the Uni-Schuko standard	...	Plug equipped with an additional socket outlet, compliant with the Uni-Schuko standard	• Heat resistance : 850 °C (650 °C - housing) • IEC/EN 60309-1, IEC/EN 60309-2 compliance • Screw-free plug closure • Integrated cable gland	...	...	Color : Black	Color : Black	Color : White	
Material	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	Plastic - Polyamide 6	...	...	...	PVC	PVC	PVC
"Index of Protection"	...	...	...	...	...	IP44	IP44	...	...	...	...	...	...	...	...	...	...	...	IP44	IP44 / IP54	IP44 / IP54	IP54	...	...	...
Mechanical strength	...	...	...	...	...	IK08	IK08	...	...	...	...	...	...	...	...	...	...	...	IK09	...	...	...	...	...	...
Weight	0.028 kg	0.026 kg	0.032 kg	0.032 kg	0.032 kg	0.058 kg	0.046 kg	0.036 kg	0.034 kg	0.056 kg	0.026 kg	0.022 kg	0.022 kg	0.015 kg	0.015 kg	0.074 kg	0.058 kg	0.07 kg	0.19 kg	0.2 kg	0.23 kg	0.074 kg	...	...	...
Dimensions	Ø 37 x 62 mm	Ø 37 x 62 mm	84 x 37 x 44 mm	84 x 37 x 42 mm	84 x 43 x 37 mm	122 x 43 x 42 mm	41 x 43 x 100 mm	Ø 37 x 74 mm	Ø 37 x 74 mm	43 x 86 x 87 mm	Ø 37 x 82 mm	Ø 37 x 49 mm	Ø 37 x 49 mm	67 x 36 x 14 mm	62 x 36 x 14 mm	79 x 75 x 55 mm	122 x 43 x 42 mm	79 x 75 x 55 mm	180 x 78 x 68 mm	150 x 80 x 67 mm	155 x 85 x 73 mm	100 x 45 x 41 mm	55 x 55 x 46 mm	50 x 50 x 65 mm	55 x 55 x 46 mm
Color	White	White	White	Black	Black	Black	Gray	White	Black / Gray	White	Black	White	Black	Black	White / Gray	Black	White / Gray	Gray + Blue	Red	Red	Black (RAL 9005)	...	...	...	...
Manufacturer / Brand	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	LEGRAND	PCE	PCE	PCE	...	...	...	...
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years