| | SOCKET MOTION DETECTOR MS-1 Virone | LIGHT BULB SOCKET WITH MOTION SENSOR OR-CR-210 ORNO | LIGHT BULB SOCKET WITH REMOTE CONTROL OR-GB-431 ORNO | NIGHT LAMP WITH MOTION SENSOR OR-LA-1406 ORNO | NIGHT LAMP WITH AN ELECTRIC SOCKET OR-LA-1408 ORNO | DIGITAL TIMER OR-PRE-409 ORNO | MECHANICAL TIMER OR-PRE-443 ORNO | INSULATING SHIELD BOX LE-001356 FOR MODULES MOUNTED ON DIN TS-35 RAIL LEGRAND | MODULAR BELL LE-004107 LEGRAND | AUXILIARY CONTACT LE-406250 FOR THE LEGRAND DEVICES OF THE TX3, DX3, FR300, FRX300, FRX400 SERIES LEGRAND | SHUNT TRIP LE-406278 FOR THE LEGRAND DEVICES OF THE TX3, DX3, FR300, FRX300, FRX400 SERIES LEGRAND | OVERVOLTAGE LIMITER LE-412223 THREE-PHASE 2 TYPE LEGRAND |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| |  | | | | | | |  | | | | |
| | 32.78 PLN<br>40.32 PLN | 31.91 PLN<br>39.25 PLN | 42.04 PLN<br>51.71 PLN | 23.33 PLN<br>28.70 PLN | 18.02 PLN<br>22.16 PLN | 53.27 PLN<br>65.52 PLN | 17.56 PLN<br>21.60 PLN | 5.28 PLN<br>6.49 PLN | 101.57 PLN<br>124.93 PLN | 55.16 PLN<br>67.85 PLN | 133.78 PLN<br>164.55 PLN | 324.86 PLN<br>399.58 PLN |
| Voltage | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Max. current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| PTZ control | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | The appearance of voltage | ... |
| Light source | ... | ... | ... | 3 x LED | LED SMD | ... | ... | ... | ... | ... | ... | ... |
| Device type | Socket Motion Detector | Light Bulb Socket with Motion Sensor | Light Bulb Socket with Remote Control | Night Lamp with Motion Sensor | Night Lamp with an Electric Socket | Digital timer | Mechanical timer | ... | Bell | Auxiliary contact | Shunt trip | Overvoltage limiter, Three-phase |
| Power measurement | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of pins | ... | ... | ... | ... | ... | ... | ... | ... | ... | 1 | ... | ... |
| Transparent door | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Minimum load | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Current consumption | ... | ... | ... | ... | ... | ... | ... | ... | 23 mA | ... | ... | ... |
| Contact type | ... | ... | ... | ... | ... | ... | ... | ... | ... | NO/NC | ... | ... |
| In package | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| AC voltage measurement | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Measuring accuracy | ... | ... | ... | ... | ... | ≤ 1 minute / month | ... | ... | ... | ... | ... | ... |
| Number of inputs | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Total maximal current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Rated voltage | 230 V / 50 Hz | 230 V / 50 Hz | 230 V / 50 Hz | ... | ... | ... | ... | ... | 230 V AC, 50 / 60 Hz | 230 V AC | 110 V ... 415 V AC | 230 / 400 V AC, 50 / 60 Hz |
| Maximal current | ... | ... | ... | ... | ... | 16 A | 16 A | ... | ... | ... | ... | ... |
| Number of outputs | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Nominal voltage of surge suppressor | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Protection level of surge suppressor | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Material | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Motion detector | ... | ... | ... | ✓ | — | ... | ... | ... | ... | ... | ... | ... |
| Maximal voltage | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 320 V AC, 50 / 60 Hz |
| Equivalent Incandescent Lamp Power | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Relay maximal load | ... | ... | ... | ... | ... | ... | ... | ... | ... | 250 V AC / 6 A | ... | ... |
| Connector type | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Valve Size | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Maximal total load | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Detection range | 9 m | 6 m | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Combined voltage pulse $U_{OC}$ | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Twilight Sensor | ... | ... | ... | ✓ | ✓ | ... | ... | ... | ... | ... | ... | ... |
| Maximal load | • 1200 W,<br>• 300 W @ LED | 1 x 60 W | • 1 x 60 W,<br>• 1 x 22 W LED | ... | ... | 3680 W | 3680 W | ... | ... | ... | ... | ... |
| Energy class | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Detection angle | 120 ° | 360 ° | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of outlets | ... | ... | ... | ... | 1 pcs | ... | ... | ... | ... | ... | ... | ... |
| Luminous flux | ... | ... | ... | 10 lm | ... | ... | ... | ... | ... | ... | ... | ... |
| Range of displayed power | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of LEDs | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Timing range | ... | ... | ... | ... | ... | 1 minute ... 168 hours ( 7 days ) | 15 minutes ... 24 hours | ... | ... | ... | ... | ... |
| Opening/closing time | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Class | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 2 type ( Class C ) |
| Strip length | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Detection range adjustment | 2 m ... 9 m | — | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Light color | ... | ... | ... | Cool, 6500 K | Neutral, 4000 K | ... | ... | ... | ... | ... | ... | ... |
| Protection level Up | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Length of the cable | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Range of displayed voltage | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| The maximum countdown time | ... | ... | ... | ... | ... | 99 hours 59 minutes | 24 hours | ... | ... | ... | ... | ... |
| Safety class | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Torque | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Plug type | ... | ... | ... | ... | CEE 7/7 | ... | ... | ... | ... | ... | ... | ... |
| CRI | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Complies with norms | ... | ... | ... | ... | ... | ... | ... | PN-EN 60439-3 | ... | ... | ... | ... |
| Light intensity adjustment range | < 3 Lux ... 2000 Lux | < 3 Lux ... 2000 Lux | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Grounding | ... | ... | ... | ... | ✓ | ... | ... | ... | ... | ... | ... | ... |
| Range of displayed cumulative electricity | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Thread type | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Protection level Up L/PE, N/PE | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 1.2 kV @ 8/20 µs (T2) |
| Illumination angle | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Nominal discharge current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Cumulative cost of electricity | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| LED lifetime | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Dimmable | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Lighting time adjustment range | 10 s ± 3 s ... 7 minutes ± 2 minutes | 10 s ± 3 s ... 5 minutes ± 1 minute | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| IK rating | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Maximum stroke current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |

| | OVERVOLTAGE LIMITER LE-412253 THREE-PHASE 1+2 TYPE LEGRAND | PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412297 2 TYPE 20 kA LEGRAND | PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412302 1+2 TYPE 50 kA LEGRAND | POWER METER WITH LCD DISPLAY OR-WAT-419 ORNO | POWER METER WITH LCD DISPLAY OR-WAT-435 ORNO | SMART SWITCH ATLO-B1-TUYA Wi-Fi, Tuya Smart | VALVE ACTUATOR ATLO-V1-TUYA Wi-Fi, Tuya Smart | DOOR FOR 48-MODULAR DISTRIBUTION CABINETS LE-337252 XL$^3$ S 160 LEGRAND | DOOR FOR 72-MODULAR DISTRIBUTION CABINETS LE-337253 XL$^3$ S 160 LEGRAND | DOOR FOR 96-MODULAR DISTRIBUTION CABINETS LE-337254 XL$^3$ S 160 LEGRAND | OVERVOLTAGE LIMITER LE-50670 2P+Z 2 x RJ45 3500 W LEGRAND | ADAPTER + BLANKING PLATE LE-665195 Niloe, Mosaic LEGRAND |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | |  | | |  |  | | | |
| | 799.84 PLN<br>983.80 PLN | 97.40 PLN<br>119.80 PLN | 194.55 PLN<br>239.30 PLN | 43.00 PLN<br>52.89 PLN | 60.67 PLN<br>74.62 PLN | 25.42 PLN<br>31.27 PLN | 113.36 PLN<br>139.43 PLN | 209.29 PLN<br>257.43 PLN | 234.16 PLN<br>288.02 PLN | 330.66 PLN<br>406.71 PLN | 80.00 PLN<br>98.40 PLN | 14.75 PLN<br>18.14 PLN |
| Voltage | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Max. current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| PTZ control | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Light source | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Device type | Overvoltage limiter, Three-phase | ... | ... | Power meter with LCD display | Power meter with LCD display | ... | ... | ... | ... | ... | ... | ... |
| Power measurement | ... | ... | ... | 0.1 ... 3680 W | 0 ... 3680 W | ... | ... | ... | ... | ... | ... | ... |
| Number of pins | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Transparent door | ... | ... | ... | ... | ... | ... | ... | — | — | — | ... | ... |
| Minimum load | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Current consumption | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Contact type | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| In package | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| AC voltage measurement | ... | ... | ... | 200 ... 276 V | 150 ... 276 V | ... | ... | ... | ... | ... | ... | ... |
| Measuring accuracy | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of inputs | ... | ... | ... | ... | ... | 1 | ... | ... | ... | ... | ... | ... |
| Total maximal current | ... | ... | ... | ... | ... | 10 A | ... | ... | ... | ... | 16 A | ... |
| Rated voltage | 230 / 400 V AC, 50 / 60 Hz | 230 / 400 V AC, 50 / 60 Hz | 230 / 400 V AC, 50 / 60 Hz | ... | ... | 100 ... 240 V | ... | ... | ... | ... | 230 V / 50 Hz | ... |
| Maximal current | ... | ... | ... | 16 A | 16 A | ... | ... | ... | ... | ... | ... | ... |
| Number of outputs | ... | ... | ... | ... | ... | 1 | ... | ... | ... | ... | ... | ... |
| Nominal voltage of surge suppressor | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 250 V / 50 Hz | ... |
| Protection level of surge suppressor | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 1 kV | ... |
| Material | ... | ... | ... | ... | ... | ... | ... | Steel | Steel | Steel | ... | Plastic |
| Motion detector | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Maximal voltage | 320 V AC, 50 / 60 Hz | 320 V AC, 50 / 60 Hz | 320 V AC, 50 / 60 Hz | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Equivalent Incandescent Lamp Power | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Relay maximal load | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Connector type | ... | ... | ... | ... | ... | screw terminals | ... | ... | ... | ... | ... | ... |
| Valve Size | ... | ... | ... | ... | ... | ... | 1/4 ", 3/8 ", 1/2 ", 3/4 ", 1 ", 1 1/4 ", 1 1/2 " | ... | ... | ... | ... | ... |
| Maximal total load | ... | ... | ... | ... | ... | 2400 W | ... | ... | ... | ... | 3500 W | ... |
| Detection range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Combined voltage pulse $U_{OC}$ | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 4 kV | ... |
| Twilight Sensor | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Maximal load | ... | ... | ... | 3680 W | 3680 W | ... | ... | ... | ... | ... | ... | ... |
| Energy class | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Detection angle | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of outlets | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 2 pcs RJ45 | ... |
| Luminous flux | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Range of displayed power | ... | ... | ... | 0.0 ... 9999 W | 0.0 ... 9999 W | ... | ... | ... | ... | ... | ... | ... |
| Number of LEDs | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Timing range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Opening/closing time | ... | ... | ... | ... | ... | ... | 5 ... 10 s | ... | ... | ... | ... | ... |
| Class | 1+2 type ( Class B+C ) | 2 type ( Class C ) | 1+2 type ( Class B+C ) | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Strip length | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Detection range adjustment | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Light color | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Protection level Up | ... | 1.2 kV @ 8/20 µs (T2) | 1.2 kV @ 10/350 µs (T1)<br>1.7 kV @ 8/20 µs (T2) | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Length of the cable | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Range of displayed voltage | ... | ... | ... | 0.0 ... 9999 V | 0.0 ... 9999 V | ... | ... | ... | ... | ... | ... | ... |
| The maximum countdown time | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Safety class | ... | ... | ... | ... | ... | ... | ... | Grade 2 | Grade 2 | Grade 2 | ... | ... |
| Torque | ... | ... | ... | ... | ... | ... | 2.9 ... 5.9 Nm | ... | ... | ... | ... | ... |
| Plug type | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | CEE 7/7 | ... |
| CRI | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Complies with norms | ... | ... | ... | ... | ... | ... | ... | IEC 60695-2-1 | IEC 60695-2-1 | IEC 60695-2-1 | ... | ... |
| Light intensity adjustment range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Grounding | ... | ... | ... | ... | ... | — | ... | ... | ... | ... | ✓ | ... |
| Range of displayed cumulative electricity | ... | ... | ... | 0.000 ... 9999 kWh | 0.000 ... 9999 kWh | ... | ... | ... | ... | ... | ... | ... |
| Thread type | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Protection level Up L/PE, N/PE | 1.2 kV @ 10/350 µs (T1)<br>1.7 kV @ 8/20 µs (T2) | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Illumination angle | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Nominal discharge current | ... | 5 kA @ 8/20 µs (T2) | 8 kA @ 10/350 µs (T1)<br>20 kA @ 8/20 µs (T2) | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Cumulative cost of electricity | ... | ... | ... | 0.00 ... 9999 € | 0.00 ... 9999 € | ... | ... | ... | ... | ... | ... | ... |
| LED lifetime | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Dimmable | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Lighting time adjustment range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| IK rating | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | IK04 | ... |
| Maximum stroke current | ... | 20 kA @ 8/20 µs (T2) | 50 kA @ 8/20 µs (T2) | ... | ... | ... | ... | ... | ... | ... | ... | ... |

| | COVER PLATE LE-754810 Valena Life FOR LE-753056 LEGRAND | DIMMER WITH A POWER SOCKET OR-AE-13114 230 V ORNO | ELECTRIC SOCKETS PLUS REMOTE CONTROL OR-GB-438 3000 W ORNO | ELECTRIC SOCKETS PLUS REMOTE CONTROL OR-GB-439 2 PCS SET 3000 W ORNO | ELECTRIC SOCKET PLUS REMOTE CONTROL OR-GB-440 3000 W ORNO | INTELLIGENT EXTERNAL MULTI-SOCKET PLUG SL-PS34 Wi-Fi, Tuya Smart | SMART LIGHT BULB WITH DIMMER TL-TAPO-L510E Wi-Fi TP-LINK | SMART MULTICOLOR LIGHT BULB TL-TAPO-L530E Wi-Fi TP-LINK | SMART RGB LED LIGHT STRIP TL-TAPO-L900-5 Wi-Fi TP-LINK | MOUNTING CLAWS LE-665099 LEGRAND | MAINS ADAPTER WITH GROUNDING WS-PL/GS-UNI |
|---|---|---|---|---|---|---|---|---|---|---|---|
| |  | | | | | |  |  | | |  |
| | 5.30 PLN<br>6.52 PLN | 40.50 PLN<br>49.81 PLN | 137.20 PLN<br>168.76 PLN | 86.64 PLN<br>106.57 PLN | 57.90 PLN<br>71.22 PLN | 137.40 PLN<br>169.00 PLN | 46.13 PLN<br>56.74 PLN | 61.26 PLN<br>75.35 PLN | 112.02 PLN<br>137.78 PLN | 1.45 PLN<br>1.78 PLN | 5.70 PLN<br>7.01 PLN |
| Voltage | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 250 V AC |
| Max. current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 10 A |
| PTZ control | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Light source | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Device type | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Power measurement | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of pins | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Transparent door | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Minimum load | ... | 40 W | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Current consumption | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Contact type | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| In package | ... | ... | ... | **2 pcs The price for package** | ... | ... | ... | ... | ... | ... | ... |
| AC voltage measurement | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Measuring accuracy | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of inputs | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Total maximal current | ... | ... | ... | ... | ... | 16 A | ... | ... | ... | ... | ... |
| Rated voltage | ... | 230 V / 50 Hz | 230 V, 50 Hz | 230 V, 50 Hz | 230 V, 50 Hz | 100 ... 250 V, 50 / 60 Hz | 220 ... 240 V, 50 / 60 Hz | 220 ... 240 V, 50 / 60 Hz | 220 ... 240 V, 50 / 60 Hz (power adapter included) | ... | ... |
| Maximal current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of outputs | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Nominal voltage of surge suppressor | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Protection level of surge suppressor | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Material | Plastic | ... | ... | ... | ... | ... | ... | ... | ... | ... | PVC |
| Motion detector | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Maximal voltage | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Equivalent Incandescent Lamp Power | ... | ... | ... | ... | ... | ... | 60 W | 60 W | ... | ... | ... |
| Relay maximal load | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Connector type | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Valve Size | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Maximal total load | ... | ... | 3000 W | 3000 W | 3000 W | 4000 W | ... | ... | ... | ... | ... |
| Detection range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Combined voltage pulse $U_{OC}$ | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Twilight Sensor | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Maximal load | ... | 280 W | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Energy class | ... | ... | ... | ... | ... | ... | F | F | ... | ... | ... |
| Detection angle | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of outlets | ... | 1 pcs | 3 pcs (included) | 1 pcs | 1 pcs | 2 pcs | ... | ... | ... | ... | ... |
| Luminous flux | ... | ... | ... | ... | ... | ... | 806 lm | 806 lm | ... | ... | ... |
| Range of displayed power | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Number of LEDs | ... | ... | ... | ... | ... | ... | ... | ... | 150 | ... | ... |
| Timing range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Opening/closing time | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Class | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Strip length | ... | ... | ... | ... | ... | ... | ... | ... | 5 m | ... | ... |
| Detection range adjustment | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Light color | ... | ... | ... | ... | ... | ... | Warm, 2700 K | 2500 ... 6500 K | ... | ... | ... |
| Protection level Up | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Length of the cable | ... | ... | ... | ... | ... | 30 cm | ... | ... | ... | ... | ... |
| Range of displayed voltage | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| The maximum countdown time | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Safety class | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Torque | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Plug type | ... | ... | CEE 7/6 | CEE 7/6 | CEE 7/6 | CEE 7/7 | ... | ... | ... | ... | ... |
| CRI | ... | ... | ... | ... | ... | ... | ≥ 80 | ≥ 80 | ... | ... | ... |
| Complies with norms | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Light intensity adjustment range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Grounding | ... | ✓ | ✓ | ✓ | ✓ | ✓ | ... | ... | ... | ... | ... |
| Range of displayed cumulative electricity | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Thread type | ... | ... | ... | ... | ... | ... | E27 thread | E27 thread | ... | ... | ... |
| Protection level Up L/PE, N/PE | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Illumination angle | ... | ... | ... | ... | ... | ... | 220 ° | 220 ° | ... | ... | ... |
| Nominal discharge current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Cumulative cost of electricity | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| LED lifetime | ... | ... | ... | ... | ... | ... | 15000 h | 15000 h | 25000 h | ... | ... |
| Dimmable | ... | ... | ... | ... | ... | ... | ✓ | ✓ | ✓ | ... | ... |
| Lighting time adjustment range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| IK rating | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Maximum stroke current | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Cost electricity setting range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 00.00 ... 99.99 €/kWh | 00.00 ... 99.99 €/kWh | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Nominal discharge current (L/PE, N/PE) | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 5 kA @ 8/20 µs (T2) | 8 kA @ 10/350 µs (T1)<br>20 kA @ 8/20 µs (T2) | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Wireless | ... | ... | • 433 MHz<br>• Remote controller<br>• Operating range in open area : 30 m | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n | Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n | ... | ... | ... | ... | ... | ... | ... | • 433 MHz<br>• Remote controller<br>• Operating range in open area : 30 m | • 433 MHz<br>• Remote controller<br>• Operating range in open area : 30 m | • 433 MHz<br>• Remote controller<br>• Operating range in open area : 30 m | Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n | WiFi 2.4 GHz | WiFi 2.4 GHz | WiFi 2.4 GHz | ... | ... |
| Time display range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 0 s ... 9999 days | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Power consumption | ... | ... | ... | ... | 0.8 W | ... | ... | ... | 4 VA | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | • 8.7 W<br>• 0.2 W (Standby mode) | • 9 W<br>• 0.4 W (Standby mode) | • 13.5 W<br>• 0.4 W (Standby mode) | ... | ... |
| Maximum stroke current (L/N, L/PE, N/PE) | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 20 kA @ 8/20 µs (T2) | 50 kA @ 8/20 µs (T2) | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Mobile phones support | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | • The Tuya Smart free application on Android<br>• The Tuya Smart free application on iOS | • The Tuya Smart free application on Android<br>• The Tuya Smart free application on iOS | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | • The Tuya Smart free application on Android<br>• The Tuya Smart free application on iOS | Access by a cloud (P2P)<br>• TP-Link Tapo (ANDROID)<br>• TP-Link Tapo (iOS) | Access by a cloud (P2P)<br>• TP-Link Tapo (ANDROID)<br>• TP-Link Tapo (iOS) | Access by a cloud (P2P)<br>• TP-Link Tapo (ANDROID)<br>• TP-Link Tapo (iOS) | ... | ... |
| Operation state indication | ... | ... | ... | ... | ... | ... | ... | ... | – | ... | ... | ✔ | ✔ | ✔ | ✔ | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Price display range | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 00.00 ... 99.99 €/kWh | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Connectors type | ... | ... | ... | ... | ... | ... | ... | ... | screw terminals | screw terminals | screw terminals | screw terminals | screw terminals | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Width in 17.5 mm modules | ... | ... | ... | ... | ... | ... | ... | 2 | 1 | 0.5 | 1 | 4 | 4 | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| "Index of Protection" | ... | ... | ... | ... | ... | ... | ... | IP30 | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | IP20 | ... | ... | ... | ... | ... | ... | IP44 | ... | ... | ... | ... | ... |
| Operation voltage | ... | ... | ... | ... | ... | 175 ... 276 V AC, 45 ... 65 Hz | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Operation temp | ... | ... | ... | ... | ... | 0 °C ... 50 °C | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Security class | IP20 | IP20 | IP20 | ... | ... | IP20 | IP20 | ... | ... | ... | ... | ... | ... | ... | ... | IP20 | IP20 | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Socket type | 2P+Z, E type | bulb E27 | bulb E27 | ... | CEE 7/5 E type | 2P+Z, E type | 2P+Z, E type | ... | ... | ... | ... | ... | ... | ... | ... | 2P+Z, E type | 2P+Z, E type | ... | ... | ... | ... | ... | CEE 7/17 | ... | ... | CEE 7/17 | CEE 7/5 E type | CEE 7/5 E type | CEE 7/5 E type | CEE 7/3 (Schuko) | ... | ... | ... | ... | ... |
| Application | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | Distribution cabinets 2 x 24-modular - $XL^3$ S 160 | Distribution cabinets 3 x 24-modular - $XL^3$ S 160 | Distribution cabinets 4 x 24-modular - $XL^3$ S 160 | ... | Mosaic product series, Niloe product series | LE-753056, Valena Life product series | ... | ... | ... | ... | ... | ... | ... | inside area | Niloe, Valena Life product series | ... |
| Main features | ... | • PIR detector<br>• Assembly : 2 m ... 3.5 m | ... | • PIR detector - Detection angle : 110 ° / 40 °, Range : 5 m<br>• Lighting time after motion detection : 30 s ... 40 s<br>• 2 Operation modes : continuous, Auto - Motion Detection | Twilight Sensor - turning on the LED : Illuminance < 10 lx | • Time settings for switching electrical devices on and off<br>• 16 programs<br>• Manual or random on / off<br>• 16 weekday combinations<br>• Daylight saving (summer) and winter time function<br>• 12 or 24 hour mode<br>• Count down function<br>• Large, readable LCD display<br>• built-in battery | Time settings for switching electrical devices on and off | Heat resistance : 85 °C | Provided space for a label with description | ... | ... | ... | ... | Varistor | Varistor | • Operation modes : Power consumption, Voltage, Cumulated amount of electricity, Cumulative cost of electricity, Cost of electricity ( €/kWh )<br>• Large, readable LCD display<br>• Simple configuration of the cost calculation setting | • Operation modes : Power consumption, Voltage, Current consumption, Current frequency, Power factor, Cumulated amount of electricity, Cumulative cost of electricity, Programmable price of 1 kWh, Cost of electricity ( €/kWh ), Cumulative time of energy consumption measurement The average weight of $CO_2$ emissions for the production of consumed energy<br>• Large, readable LCD display<br>• Simple configuration of the cost calculation setting<br>• built-in battery | • schedule,<br>• timer,<br>• remote access,<br>• voice control<br>• Pairing button<br>• Wi-Fi indicator | • schedule,<br>• timer,<br>• Setting scenarios by different events,<br>• remote access,<br>• voice control<br>• Wi-Fi indicator<br>• Easy installation - the actuator is mounted on ball valves with a lever<br>• Possibility of manual change of the valve position<br>• Easy pairing function<br>• Safe 12V DC power supply | • Reversible door<br>• 1 closing point<br>• Supplied with handle in the kit | • Reversible door<br>• 1 closing point<br>• Supplied with handle in the kit | • Reversible door<br>• 1 closing point<br>• Supplied with handle in the kit | ... | ... | ... | Smooth power adjustment | • Type of remote keyfob battery : CR2032 3V<br>• Easy operation<br>• "Index of Protection" : IP20 | • Type of remote keyfob battery : CR2032 3V<br>• Easy operation<br>• "Index of Protection" : IP20 | • Type of remote keyfob battery : CR2032 3V<br>• Easy operation<br>• "Index of Protection" : IP20 | • schedule,<br>• timer,<br>• remote access,<br>• voice control<br>• Away Mode – automatically turns devices on and off at different times to give the appearance that someone is home<br>• Easy operation<br>• ON/OFF button<br>• STATUS indicator<br>• Built-in Bluetooth module that allows you to control the device in case of loss of connection to the WiFi network<br>• The design of the housing allows for convenient installation of the device on the wall | • Adjusting the brightness of the light - built-in dimmer,<br>• Save presets,<br>• schedule - Time mode, sunrise and sunset mode,<br>• timer,<br>• remote access,<br>• local access,<br>• Away Mode - simulating the presence of residents by randomly turning the lighting on and off<br>• Easy operation<br>• Wi-Fi - IEEE 802.11 b/g/n<br>• System requirements : Android 4.4 or newer, iOS 9.0 or newer | • Adjusting the brightness and color of the light - 16 M hues to choose from,<br>• Save presets,<br>• Automatically restore last light state,<br>• schedule - Time mode, sunrise and sunset mode,<br>• timer,<br>• remote access,<br>• local access,<br>• Away Mode - simulating the presence of residents by randomly turning the lighting on and off<br>• Easy operation<br>• Wi-Fi - IEEE 802.11 b/g/n<br>• System requirements : Android 4.4 or newer, iOS 9.0 or newer | • Adjusting the brightness and color of the light - 16 M hues to choose from,<br>• Save presets,<br>• Lighting sync to music,<br>• schedule - Time mode, sunrise and sunset mode,<br>• timer,<br>• remote access,<br>• local access,<br>• Away Mode – automatically turns devices on and off at different times to give the appearance that someone is home<br>• Easy operation<br>• Wi-Fi - IEEE 802.11 b/g/n<br>• System requirements : Android 4.4 or newer, iOS 9.0 or newer | ... | Color : Black |
| Housing | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic | ... | Plastic, DIN, TS-35 rail mounting | Plastic, Direct mounting on selected Legrand DIN TS-35 rail mounting units, on the left-hand side of the device | Plastic, Direct mounting on selected Legrand DIN TS-35 rail mounting units, on the left-hand side of the device | Plastic, DIN, TS-35 rail mounting | Plastic, DIN, TS-35 rail mounting | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic, Waterproof | ... | ... | ... | Plastic | ... | ... | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic | ... | ... | ... |
| Power supply | 230 V AC, 50 Hz | 230 V AC, 50 Hz | • 230 V AC, 50 Hz - Socket<br>• 12V, type A23 battery (included) - Remote controller | 4.5 V DC, 3 x 1.5V, type AA/LR6/FR6 battery (included) | 230 V AC / 50 Hz | • 230 V AC, 50 Hz<br>• built-in battery | 230 V AC, 50 Hz | ... | ... | ... | ... | ... | ... | ... | ... | 230 V AC, 50 Hz | • 230 V AC, 50 Hz<br>• 3.6 V DC, 40 mAh NiMH - built-in battery | ... | 12 V / 1 A (power adapter included) | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| Color | White | White | White | White | White | ... | ... | White - RAL9010 | ... | ... | ... | ... | ... | ... | ... | ... | ... | White | Black | White | White | White | Gray / White | White | White | White | White | White | White | Black | White | White | RGB | Black | ... |
| Operation temp | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | -20 °C ... 50 °C | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | -20 °C ... 60 °C | 0 °C ... 40 °C | 0 °C ... 40 °C | -15 °C ... 40 °C | ... | ... |
| Permissible relative humidity | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ≤ 80 % | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... | 10 % ... 90 % (non-condensing) | 10 % ... 90 % (non-condensing) | 10 % ... 90 % (non-condensing) | ... | ... |
| Weight | 0.11 kg | 0.07 kg | • 0.07 kg - Socket<br>• 0.03 kg - Remote controller | 0.13 kg | 0.08 kg | 0.15 kg | 0.15 kg | 0.09 kg | 0.061 kg | 0.034 kg | 0.086 kg | 0.334 kg | 0.552 kg | 0.042 kg | 0.098 kg | 0.12 kg | 0.17 kg | 0.04 kg | 0.4 kg | 2.724 kg | 3.622 kg | 4.9 kg | 0.142 kg | 0.025 kg | 0.008 kg | 0.11 kg | • 0.09 kg - Socket<br>• 0.02 kg - Remote controller | • 0.09 kg - Socket<br>• 0.02 kg - Remote controller | • 0.09 kg - Socket<br>• 0.02 kg - Remote controller | 0.33 kg | 0.068 kg | 0.042 kg | 0.055 kg | 0.001 kg | ... |
| Dimensions | 98 x 52 x 73 mm | Ø 56 x 116 mm | • Ø 55 x 115 mm - Socket<br>• 82 x 36 x 14 mm - Remote controller | 78 x 65 x 40 mm | 65 x 55 x 55 mm | 115 x 55 x 78 mm | 126 x 72 x 85 mm | 140 x 52 x 68 mm | 66 x 83 x 18 mm | 9 x 85 x 78 mm | 18 x 85 x 78 mm | 71 x 83 x 70 mm | 71 x 83 x 70 mm | 62 x 54 x 17 mm | 62 x 54 x 17 mm | 108 x 64 x 75 mm | 149 x 70 x 77 mm | 88 x 40 x 25 mm | • 105 x 70 x 107 mm<br>• 1.35 m (cable length) | 547 x 394 x 27 mm | 547 x 544 x 27 mm | 547 x 694 x 28 mm | 85 x 85 x 78 mm | 76 x 76 x 25 mm | 55 x 55 x 8 mm | 56 x 96 x 79 mm | • 75 x 55 x 55 mm - Socket<br>• 81 x 38 x 13 mm - Remote controller | • 75 x 55 x 55 mm - Socket<br>• 81 x 38 x 13 mm - Remote controller | • 75 x 55 x 55 mm - Socket<br>• 81 x 38 x 13 mm - Remote controller | 107 x 101 x 53 mm | Ø 60 x 115 mm | Ø 60 x 115 mm | 5000 x 10 x 1.6 mm | 33 x 19 x 7 mm | 55 x 55 x 46 mm |
| Manufacturer / Brand | Virone | ORNO | ORNO | ORNO | ORNO | ORNO | ORNO | LEGRAND | LEGRAND | LEGRAND | LEGRAND | LEGRAND | LEGRAND | LEGRAND | LEGRAND | ORNO | ORNO | ... | ... | LEGRAND | LEGRAND | LEGRAND | LEGRAND | LEGRAND | LEGRAND | ORNO | ORNO | ORNO | ORNO | ... | TP-LINK | TP-LINK | TP-LINK | LEGRAND | ... |
| Guarantee | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years |