









	DIRECTIONAL ANTENNA 11/21-48	DIRECTIONAL ANTENNA 19/21-48	DIRECTIONAL ANTENNA SMART-CITY	DIRECTIONAL ANTENNA 17/21-48/TRIDIGIT	DIRECTIONAL ANTENNA 3/21-48 DIPOL	DIRECTIONAL ANTENNA 44/21-48/TRIDIGIT	DIRECTIONAL ANTENNA SMART-HORIZON	DIRECTIONAL ANTENNA DIGIT-ACTIVA/DVB-T
								
	49.79 PLN 61.24 PLN	62.61 PLN 77.01 PLN	93.49 PLN 114.99 PLN	74.66 PLN 91.83 PLN	31.14 PLN 38.30 PLN	124.84 PLN 153.55 PLN	156.97 PLN 193.07 PLN	140.95 PLN 173.37 PLN
Receiving channels	21 ... 48	21 ... 48	21 ... 48	21 ... 48	...	21 ... 48	21 ... 48	21 ... 69
Frequency range	...	...	...	...	470 ... 694 MHz	...	...	...
Gain	6 ... 10 dB	9 ... 14 dB	• 5 ... 10 dBi - passive mode - no power, • 22.5 ... 27 dB - active mode - DC 12V power supply (power adapter not included)	14 dBi	max. 5 dBi	14 ... 16.8 dBi	• 11 ... 14 dBi - passive mode - no power, • 25 ... 32 dB - active mode DC 12V power supply (power adapter not included)	max. 4.5 dBi
Polarization	Horizontal	Horizontal	Horizontal / Vertical	Horizontal / Vertical ( when rotated by 90° )	Horizontal / Vertical	Horizontal / Vertical - when rotated by 90°	Horizontal / Vertical - when rotated by 90°	Horizontal
Impedance	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω
Manufacturer / Brand	...	...	...	...	DIPOL	...	...	TELMOR
Main features	• Number of elements : 11 • Matching transformer included	• Number of elements : 19 • Matching transformer included	• Number of elements : 17, • Built-in LTE filter, • Built-in antenna amplifier with a bypass - operation in passive or active mode, • The main bar of the antenna is divided - possible mounting in a compact version, • The design of the antenna enables simple, quick assembly without the use of tools	• Number of elements : 17 • Matching transformer included	• Number of elements : 3 • Matching transformer included	• Number of elements : 44 • Matching transformer included • Mast mounting diameter max. Ø 50 mm	• Number of elements : 25 • Built-in LTE filter, • Built-in antenna amplifier with a bypass - operation in passive or active mode, • Mast mounting diameter max. Ø 60 mm • The design of the antenna enables simple, quick assembly without the use of tools	• Gain : 0 ... 18 dB • It has a tight and UV-resistant housing • Small dimensions • Power supply : 12 V / 45 mA (power adapter included)
Weight	...	...	...	0.86 kg	...	1.51 kg	1.6 kg	0.7 kg
Dimensions	580 x 320 x 350 mm	1300 x 320 x 410 mm	1040 x 355 x 405 mm	670 x 400 x 320 mm	263 x 267 x 76 mm	1200 x 320 x 350 mm	1110 x 590 x 500 mm	350 x 325 x 150 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00