

	GATE MAGNETIC DETECTOR KN-CA52D-PS	GATE MAGNETIC DETECTOR KN-CA55L	GATE MAGNETIC DETECTOR KN-CA56D	GATE MAGNETIC DETECTOR KN-CA59	GATE MAGNETIC DETECTOR KN-CA59L	GATE MAGNETIC DETECTOR KN-D2	GATE MAGNETIC DETECTOR KN-D3	GATE MAGNETIC DETECTOR KN-D4	GATE MAGNETIC DETECTOR KN-OC55	GATE MAGNETIC DETECTOR B-4L SATEL	GATE MAGNETIC DETECTOR B-4M SATEL	GATE MAGNETIC DETECTOR B-4S SATEL
												
	31.59 EUR 31.59 EUR	8.94 EUR 8.94 EUR	8.14 EUR 8.14 EUR	7.27 EUR 7.27 EUR	8.42 EUR 8.42 EUR	8.66 EUR 8.66 EUR	9.72 EUR 9.72 EUR	10.16 EUR 10.16 EUR	4.40 EUR 4.40 EUR	17.22 EUR 17.22 EUR	19.37 EUR 19.37 EUR	19.37 EUR 19.37 EUR
In package	5 pcs The price for package	...	...	...	...	...	...	...	...	...	...	...
Detection	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Gate opening	Gate opening	Gate opening	Opening the door or window	Gate opening	Gate opening	Gate opening
Maximum reed switched voltage	20 V	20 V	20 V	20 V	20 V	20 V	100 V	20 V	20 V	100 V	100 V	100 V
Maximal switched current	10 mA	10 mA	10 mA	10 mA	10 mA	400 mA	500 mA	400 mA	10 mA	400 mA	400 mA	400 mA
Make distance	19 mm	55 mm	19 mm	19 mm	19 mm	38 mm	38 mm	68 mm	40 mm	75 mm	75 mm	75 mm
Break distance	20 mm	70 mm	20 mm	20 mm	20 mm	40 mm	40 mm	70 mm	65 mm	80 mm	80 mm	80 mm
Manufacturer / Brand	...	...	...	...	...	...	...	...	...	SATEL	SATEL	SATEL
Main features	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cables : 40 cm • The cables are protected with a metal spiral tube with a length of 36.5 cm	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cables : 40 cm • The cables are protected with a metal spiral tube with a length of 36.5 cm • Included bracket for attaching the magnet	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cables : 40 cm • The cables are protected with a metal spiral tube with a length of 36.5 cm	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cables : 40 cm • The cables are protected with a metal spiral tube with a length of 36.5 cm	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cables : 40 cm	• Rugged, metal sealed body, Aluminum • Armored cables • Length of the cable : 30 cm	• Rugged, metal sealed body, Aluminum • Armored cables • Length of the cable : 35 cm	• Rugged, metal sealed body, Aluminum • Alarm output NC - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Armored cables • Length of the cable : 40 cm • Angle bar included in the kit	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cables : 40 cm • The cables are protected with a metal spiral tube with a length of 36.5 cm	• Rugged, metal sealed body • Armored cables	• Rugged, metal sealed body • Angle bar included in the kit	• Rugged, metal sealed body • Armored cables
Color	Silver	Silver	Silver	Silver	Silver	...	...	...	Silver	...	...	...
Weight	0.12 kg (total)	0.16 kg (total)	0.15 kg (total)	0.19 kg (total)	0.18 kg (total)	0.18 kg	0.3 kg	0.23 kg	0.17 kg (total)	0.24 kg	0.23 kg	0.01 kg
Dimensions	49 x 19.5 x 9.8 mm	105 x 37.5 x 9.5 mm - Reed switch 106 x 15.5 x 15.2 mm - Magnet	48 x 24 x 14.5 mm	106 x 48 x 9.5 mm - Reed switch 88 x 20 x 20 mm - Magnet	106 x 48 x 9.5 mm - Reed switch 106 x 15.5 x 15.2 mm - Magnet	• 105.7 x 38 x 9.8 mm - Reed switch • 105.8 x 15.8 x 15.4 mm - magnet	• 87 x 37 x 9.8 mm - Reed switch • 87.6 x 35 x 41.5 mm - magnet	• 105.7 x 38 x 9.8 mm - Reed switch • 105.8 x 15.8 x 15.4 mm - magnet • 106.5 x 50 x 50 mm - L-bracket	105 x 37.5 x 9.5 mm - Reed switch 106 x 15.5 x 15.2 mm - Magnet	104.5 x 44.5 mm	107 x 50 mm	88.9 x 44.5 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00