

	VIDEO DOORPHONE INTEGRATED WITH MAILBOX S551-SKM VIDOS	VIDEO DOORPHONE INTEGRATED WITH MAILBOX S551-SKP VIDOS	VIDEO DOORPHONE INTEGRATED WITH MAILBOX S561D-SKP VIDOS	VIDEO DOORPHONE INTEGRATED WITH MAILBOX S562D-SKM VIDOS	VIDEO DOORPHONE S20DA VIDOS	VIDEO DOORPHONE S35 VIDOS	VIDEO DOORPHONE S36 VIDOS	VIDEO DOORPHONE S50D VIDOS	VIDEO DOORPHONE S551 VIDOS	VIDEO DOORPHONE S561D VIDOS	VIDEO DOORPHONE S562D VIDOS	VIDEO DOORPHONE S564 VIDOS	VIDEO DOORPHONE S601 VIDOS	VIDEO DOORPHONE S601D-2 VIDOS	VIDEO DOORPHONE S602 VIDOS	INDOOR PANEL M320B VIDOS	INDOOR PANEL M670B VIDOS	INDOOR PANEL M670B-S2 VIDOS	INDOOR PANEL M670W VIDOS	INDOOR PANEL M670W-S2 VIDOS					
																									
Compatibility	358.89 EUR 358.89 EUR VIDOS Analog Video Doorphones	382.82 EUR 382.82 EUR VIDOS Analog Video Doorphones	454.61 EUR 454.61 EUR VIDOS Analog Video Doorphones	466.66 EUR 466.66 EUR VIDOS Analog Video Doorphones	114.85 EUR 114.85 EUR VIDOS Analog Video Doorphones	86.13 EUR 86.13 EUR VIDOS Analog Video Doorphones	95.71 EUR 95.71 EUR VIDOS Analog Video Doorphones	107.67 EUR 107.67 EUR VIDOS Analog Video Doorphones	157.91 EUR 157.91 EUR VIDOS Analog Video Doorphones	191.41 EUR 191.41 EUR VIDOS Analog Video Doorphones	212.94 EUR 212.94 EUR VIDOS Analog Video Doorphones	212.94 EUR 212.94 EUR VIDOS Analog Video Doorphones	126.81 EUR 126.81 EUR VIDOS Analog Video Doorphones	193.80 EUR 193.80 EUR VIDOS Analog Video Doorphones	191.41 EUR 191.41 EUR VIDOS Analog Video Doorphones	150.74 EUR 150.74 EUR VIDOS Analog Video Doorphones	179.45 EUR 179.45 EUR VIDOS Analog Video Doorphones	191.41 EUR 191.41 EUR VIDOS Analog Video Doorphones	179.45 EUR 179.45 EUR VIDOS Analog Video Doorphones	191.42 EUR 191.42 EUR VIDOS Analog Video Doorphones					
Shield	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	7" TFT-LCD color matrix	7" TFT-LCD color matrix	7" TFT-LCD color matrix	7" TFT-LCD color matrix	7" TFT-LCD color matrix					
Sensor	1/3", 600 TVL	1/3", 600 TVL	1/3", 600 TVL	1/3", 600 TVL	1/3", 800 TVL	1/3" 600 TVL	1/3" 600 TVL	1/3" 600 TVL	1/3" 600 TVL	1/3" 600 TVL	1/3" 600 TVL	1/3" 600 TVL	1/3" 600 TVL	1/3" 600 TVL	1/3" 600 TVL	7" TFT-LCD color matrix	7" TFT-LCD color matrix	7" TFT-LCD color matrix	7" TFT-LCD color matrix	7" TFT-LCD color matrix					
Resolution	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	800 x 600	800 x 600	800 x 600	800 x 600	800 x 600					
View angle	87°	87°	87°	87°	110°	87°	87°	87°	87°	87°	87°	87°	87°	87°	87°	...	...	...	...	...					
IR illuminator	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	...	...	...	...	...					
LED illuminator	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...					
proximity reader built-in	...	...	...	...	Standard - Unique EM 125kHz	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...					
Fingerprint reader built-in	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...					
Built-in keypad	...	...	✓	✓	✓	...	...	...	✓	✓	...	...	...	✓	...	...	...	...	...	...					
The number of subscribers served	1	1	1	2	1	1	2	1	1	1	2	4	1	1	2	...	...	...	...	...					
Video output	compatible with the VIDOS DUO digital video doorphone system	✓	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	compatible with VIDOS analog video door-phone system	...	...	...	...	...					
Main features	• Integrated mailbox - Through • Camera - Angle adjustment range ± 10° • Backlight - 8 x LED IR • Vandal-proof front panel • Electric strikes and electromagnetic locks support • Call button - Blue backlight	• Integrated mailbox - Through • Camera - Angle adjustment range ± 10° • Backlight - 8 x LED IR • Vandal-proof front panel • Electric strikes and electromagnetic locks support • Call button - Blue backlight	• Integrated mailbox - Through • Camera - Angle adjustment range ± 10° • Vandal-proof front panel • Electric strikes and electromagnetic locks support • Illuminated buttons and signboard for the surname • Adjustment of the opening time of the electric strike: 1s ... 99s • Output for the additional lock release button • Timer output specifying temporary access	• Integrated mailbox - Through • Camera - Angle adjustment range ± 10° • Vandal-proof front panel • Electric strikes and electromagnetic locks support • Illuminated buttons and signboard for the surname • Adjustment of the opening time of the electric strike: 1s ... 99s • Output for the additional lock release button • Timer output specifying temporary access	• Number of supported proximity cards - 200 • Number of supported PIN codes - 200 - Protection against unauthorized use • Electric strikes and electromagnetic locks support • Illuminated buttons and signboard for the surname • Vandal-proof front panel • Illuminated buttons and signboard for the surname	• Electric strikes and electromagnetic locks support • Illuminated button and signboard for the surname	• Electric strikes and electromagnetic locks support • Illuminated button and signboard for the surname	• Number of supported PIN codes: 30 • Adjustment of the opening time of the electric strike: 1s ... 99s • Electric strikes and electromagnetic locks support • Output for the additional lock release button • Timer output specifying temporary access • Vandal-proof front panel • Illuminated buttons and signboard for the surname	• Camera - Angle adjustment range ± 10° • Backlight - 8 x LED IR • Vandal-proof front panel • Call button - Blue backlight	• Adjustment of the opening time of the electric strike: 1s ... 99s • Electric strikes and electromagnetic locks support • Output for the additional lock release button • Timer output specifying temporary access • Vandal-proof front panel • Illuminated buttons and signboard for the surname	• Adjustment of the opening time of the electric strike: 1s ... 99s • Electric strikes and electromagnetic locks support • Output for the additional lock release button • Timer output specifying temporary access • Vandal-proof front panel • Illuminated buttons and signboard for the surname	• Electric strikes and electromagnetic locks support • Vandal-proof front panel • Illuminated buttons and signboard for the surname	• Electric strikes and electromagnetic locks support • Vandal-proof front panel • Illuminated buttons and signboard for the surname	• 2 zones support • Built-in code lock allows to control the opening state of two independent entrances with separate codes (eg wicket + automatic gate) • Possibility to program up to 1010 codes for 2 zones • Adjustment of the opening time of the electric strike: 1s ... 99s • Electric strikes and electromagnetic locks support • Output for the additional lock release button • Timer output specifying temporary access • Possibility of working in bistable mode (entering the code releases the electric strike, re-entering the code closes it) • Vandal-proof front panel • Illuminated buttons and signboard for the surname	• Electric strikes and electromagnetic locks support • Vandal-proof front panel • Illuminated buttons and signboard for the surname	...	...	...	...	...					
Power consumption	≤ 1.5 W (operation)	≤ 1.5 W (operation)	≤ 1.5 W (operation)	≤ 1.5 W (operation)	• 0.95 W (operation) • 0.4 W (Standby mode)	...	...	≤ 1.5 W (operation)	≤ 1.5 W (operation)	≤ 1.5 W (operation)	≤ 1.5 W (operation)	≤ 1.5 W (operation)	≤ 1.5 W (operation)	≤ 1.5 W (operation)	≤ 1.5 W (operation)	...	...	...	...	...					
Housing	• Acid-proof steel - Front panel, Rear panel • Steel galvanized - Drawer	Acid-proof steel, Waterproof	Acid-proof steel, Waterproof	• Acid-proof steel - Front panel, Rear panel • Steel galvanized - Drawer	Aluminum / Plastic, Waterproof	Aluminum	Aluminum	Aluminum, Waterproof	Acid-proof steel, powder painting / Plastic, Waterproof	Acid-proof steel / Plastic, Waterproof	Acid-proof steel / Plastic, Waterproof	Acid-proof steel / Plastic, Waterproof	Acid-proof steel / Plastic, Waterproof	Acid-proof steel / Plastic, Waterproof	Acid-proof steel / Plastic, Waterproof	...	...	...	...	...					
"Index of Protection"	IP54	IP65	IP65	IP54	IP65	...	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65	...	...	...	...	...					
Main features	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	• Plug & Play. • Ultra-flat hands-free monitor, with speakerphone • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Large, readable buttons. • Support for 2 door stations, or 1 station and 1 CCTV camera. • Possibility to extend the system with any 3 additional indoor panels or uniphones from the VIDOS brand. • Preview image from the door station with the possibility of turning on the sound and opening the gate. • Control of the electric strike and automatic gate. • Microphone built-in. • Speakers built-in. • Bidirectional communication. • OSD menu. • The kit includes power supply adapter designed for rail mounting DIN TS-35	• Plug & Play. • Ultra-flat hands-free monitor, with speakerphone • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Touch control keys - Blue backlight. • Support for 2 door stations, or 1 station and 1 CCTV camera. • Possibility to extend the system with any 3 additional indoor panels or uniphones from the VIDOS brand. • Preview image from the door station with the possibility of turning on the sound and opening the gate. • Control of the electric strike and automatic gate. • Intercom and call forwarding function. • Microphone built-in. • Speakers built-in. • Bidirectional communication. • OSD menu. • The kit includes power supply adapter designed for rail mounting DIN TS-35	• Plug & Play. • Ultra-flat hands-free monitor, with speakerphone • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Touch control keys - Blue backlight. • Support for 2 door stations, or 1 station and 1 CCTV camera. • Possibility to extend the system with any 3 additional indoor panels or uniphones from the VIDOS brand. • Preview image from the door station with the possibility of turning on the sound and opening the gate. • Control of the electric strike and automatic gate. • Intercom and call forwarding function. • Microphone built-in. • Speakers built-in. • Bidirectional communication. • OSD menu. • The kit includes power supply adapter designed for rail mounting DIN TS-35	• Plug & Play. • Ultra-flat hands-free monitor, with speakerphone • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Touch control keys. • Support for 2 door stations, or 1 station and 1 CCTV camera. • Possibility to extend the system with any 3 additional indoor panels or uniphones from the VIDOS brand. • Preview image from the door station with the possibility of turning on the sound and opening the gate. • Control of the electric strike and automatic gate. • Intercom and call forwarding function. • Microphone built-in. • Speakers built-in. • Bidirectional communication. • OSD menu. • The kit includes power supply adapter designed for rail mounting DIN TS-35	• Plug & Play. • Ultra-flat hands-free monitor, with speakerphone • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Touch control keys. • Support for 2 door stations, or 1 station and 1 CCTV camera. • Possibility to extend the system with any 3 additional indoor panels or uniphones from the VIDOS brand. • Preview image from the door station with the possibility of turning on the sound and opening the gate. • Control of the electric strike and automatic gate. • Intercom and call forwarding function. • Microphone built-in. • Speakers built-in. • Bidirectional communication. • OSD menu. • The kit includes power supply adapter designed for rail mounting DIN TS-35	...	...	...	...	...
Power supply	From internal panel	From internal panel	12 V DC ... 15 V DC	12 V DC ... 15 V DC	12 V DC ... 15 V DC	From internal panel	12 ... 14.5 V DC	12 V DC ... 15 V DC	From internal panel	12 V DC ... 15 V DC	12 V DC ... 15 V DC	12 V DC ... 15 V DC	12 V DC ... 15 V DC	12 V DC ... 15 V DC	12 V DC ... 15 V DC	14.5 V DC	14.5 V DC	14.5 V DC	14.5 V DC	14.5 V DC					
Max. current	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	1.3 A (power adapter included)	1.3 A (power adapter included)	1.3 A (power adapter included)	1.3 A (power adapter included)	1.3 A (power adapter included)					
Color	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Black	Black	Black	White	White					
Operation temp	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-25 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-20 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C					
Supported languages	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...					
Weight	4.5 kg	4.8 kg	5 kg	5 kg	0.4 kg	0.37 kg	0.44 kg	0.68 kg	0.94 kg	0.94 kg	0.95 kg	0.92 kg	0.37 kg	0.66 kg	0.63 kg	0.39 kg	0.53 kg	0.52 kg	0.52 kg	0.52 kg					
Dimensions	• Front panel : 285 x 332 mm • Rear panel : 260 x 110 mm • Adjustable depth of the box : 260 ... 410 mm	• Front panel : 285 x 385 mm • Rear panel : 265 x 360 mm • Adjustable depth of the box : 190 ... 255 mm	• Front panel : 285 x 385 mm • Rear panel : 265 x 360 mm • Adjustable depth of the box : 190 ... 255 mm	• Front panel : 285 x 385 mm • Rear panel : 260 x 110 mm • Adjustable depth of the box : 260 ... 410 mm	150 x 84 x 39 mm	132 x 97 x 45 mm	132 x 97 x 45 mm	78 x 183 x 60 mm	203 x 150 x 55 mm	250 x 120 x 50 mm	250 x 120 x 50 mm	250 x 120 x 51 mm	110 x 100 x 55 mm	195 x 100 x 55 mm	245 x 161 x 19.5 mm	241 x 161 x 24 mm	241 x 161 x 24 mm	241 x 161 x 24 mm	241 x 161 x 24 mm	241 x 161 x 24 mm	241 x 161 x 24 mm				
Manufacturer / Brand	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS					
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years					

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00