

	BATTERY 12V/7AH- ALARMTEC-BP ALARMTECH	POWERBANK POWERPLAY-20S-BLACK-GC 20000 mAh 22.5 W Green Cell	POWERBANK POWERPLAY-20S-WHITE-GC 20000 mAh 22.5 W Green Cell	CHARGER LIFEPO4- CHARG/14.6V/10A-GC Green Cell	CHARGER MW-SC4B MW POWER	CHARGER MW-SC8E MW POWER	BATTERY 12V/18AH- ALARMTEC-BP ALARMTECH
							
	12.79 EUR 12.79 EUR	28.71 EUR 28.71 EUR	28.71 EUR 28.71 EUR	74.16 EUR 74.16 EUR	24.26 EUR 24.26 EUR	37.78 EUR 37.78 EUR	35.62 EUR 35.62 EUR
Rated voltage	12 V	...	...	...	...	...	12 V
Maximal load power	...	22.5 W	22.5 W	...	...	...	...
Number of inputs	...	2 pcs - Charging can be done through the dedicated port or the PD port	2 pcs - Charging can be done through the dedicated port or the PD port	...	...	...	...
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery	...	...	12.8 V : LiFePO ₄	6 V, 12 V : Lead-Acid, Sealed lead-acid, AGM	12 V, 24 V : Lead-Acid, Sealed lead-acid, AGM	Maintenance-free AGM (Absorbent Glass Mat) battery
Battery lifetime	3 ... 5 years	...	...	...	...	...	3 ... 5 years
Connector	T1 type	...	...	...	...	...	M5 screw
Number of outputs	...	• 2 pcs USB-C, • 1 pcs USB-A	• 2 pcs USB-C, • 1 pcs USB-A	...	...	...	...
Battery capacity	7 Ah	20000 mAh	20000 mAh	...	• 6 V : 1.2 Ah ... 14 Ah, • 12 V : 1.2 Ah ... 120 Ah	• 12 V : 1.2 Ah ... 240 Ah, • 24 V : 1.2 Ah ... 120 Ah	18 Ah
Power inputs	...	USB-C1 : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A - 18 W (max) USB-C2 PD : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A - 18 W (max)	USB-C1 : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A - 18 W (max) USB-C2 PD : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A - 18 W (max)	...	...	...	...
Battery charging current	max. 2.1 A	...	...	12.8 V : 10 A	• 6 V : 1 A ± 10 %, • 12 V : 1 A / 4 A ± 10 %	• 12 V : 1 A / 4 A / 8 A, • 24 V : 1 A / 4 A	max. 5.4 A
Battery charging voltage	...	...	...	14.6 V	• 7.2 V / 7.4 V DC ± 25 % • 14.4 V / 14.7 V DC ± 25 %	• 14.4 V / 14.7 V DC • 28.8 V / 29.4 V DC	...
LED indicator	...	...	...	✓	—	—	...
LCD display	...	...	...	—	✓	✓	...
Length of the cables	...	...	...	...	• 1.45 m - Battery cable • 1.50 m - Power cord	...	...
Power supply	...	...	...	200 ... 240 V AC / 50 Hz	220 ... 240 V AC / 50 Hz	220 ... 240 V AC / 50 Hz	...
Power consumption	...	...	...	max. 240 W	max. 70 W	max. 140 W	...
Power outputs	...	• 1 pcs USB-C2 PD : 5 V / 3 A ... 9 V / 2.22 A ... 12 V / 1.67 A, 22.5 W (max) - Power Delivery, • 1 pcs USB-C3 : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A, 18 W (max) - Ultra Charge, • 1 pcs USB-A : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A, 18 W (max) - Ultra Charge	• 1 pcs USB-C2 PD : 5 V / 3 A ... 9 V / 2.22 A ... 12 V / 1.67 A, 22.5 W (max) - Power Delivery, • 1 pcs USB-C3 : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A, 18 W (max) - Ultra Charge, • 1 pcs USB-A : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A, 18 W (max) - Ultra Charge	...	...	...	...
"Index of Protection"	...	...	...	—	IP65	IP65	...
Isolation class	...	...	...	...	Class II	Class II	...
Operation temp	...	...	...	-20 °C ... 45 °C	-10 °C ... 40 °C	-5 °C ... 40 °C	...
Protections	...	• Short-circuit • Discharge • Temperature • Input and output voltage matching	• Short-circuit • Discharge • Temperature • Input and output voltage matching	...	...	...	...
Main features	...	• Pass-Through - simultaneous powering of connected devices and charging the battery • Li-Poly battery • Battery status indicator - 4 x LED • Compatible with Power Delivery 2.0 / 3.0, Quick Charge 2.0 / 3.0, PPS, FCP / AFC / SFCP, Mediatek Pump Express 1.1 / 2.0, USB-C DRP	• Pass-Through - simultaneous powering of connected devices and charging the battery • Li-Poly battery • Battery status indicator - 4 x LED • Compatible with Power Delivery 2.0 / 3.0, Quick Charge 2.0 / 3.0, PPS, FCP / AFC / SFCP, Mediatek Pump Express 1.1 / 2.0, USB-C DRP	• Short-circuit protection, Overvoltage • Overcharge protection • Thermal protection • Protection against reverse polarity connection • Insulated crocodile clips • Light and durable construction	• Microprocessor control system • Fully automatic 10-stage charging process • Keeping the battery charged • Detection and regeneration of an exhausted battery • Short-circuit protection, Overvoltage • Overcharge protection • Thermal protection • Protection against reverse polarity connection • Insulated crocodile clips • The device is designed to work both inside and outside the building	• Microprocessor control system • Fully automatic 10-stage charging process • Keeping the battery charged • Detection and regeneration of an exhausted battery • Short-circuit protection, Overvoltage • Overcharge protection • Thermal protection • Protection against reverse polarity connection • Insulated crocodile clips • The device is designed to work both inside and outside the building • Easy to hook	...
Color	...	Black	White	...	...	...	...
Weight	2.04 kg	0.35 kg	0.35 kg	0.8 kg	0.4 kg	0.65 kg	5.42 kg
Dimensions	151 x 65 x 99 mm	140 x 72 x 25 mm	140 x 72 x 25 mm	170 x 90 x 50 mm	194 x 75 x 42 mm	218 x 90 x 50 mm	182 x 77 x 168 mm
Manufacturer / Brand	ALARMTECH	Green Cell	Green Cell	Green Cell	MW POWER	MW POWER	ALARMTECH
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00