

	IP MOBILE CAMERA ATE: CAM-IPC890 - 1080p 2.8 mm AUTONE	IP MOBILE CAMERA ATE: CAM-IPC763 - 1080p 2.8 mm AUTONE	IP MOBILE CAMERA ATE: CAM-IPC925 - 1080p 2.8 mm AUTONE	IP MOBILE CAMERA DS-2XM6522G0-IM/ND - 1080p 2.8 mm Hikvision	IP MOBILE CAMERA DS-2XM6522G0-IM/ND(4mm)(C) - 1080p 4.0 mm Hikvision
					
	59.34 EUR 59.34 EUR	60.87 EUR 60.87 EUR	59.34 EUR 59.34 EUR	362.48 EUR 362.48 EUR	362.48 EUR 362.48 EUR
Standard	TCP/IP	TCP/IP	TCP/IP	TCP/IP	TCP/IP
Sensor	1/2.8 " CMOS	1/2.8 " CMOS	1/2.7 " SC2235 CMOS	1/2.8 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS
Scanning system	...	...	...	Progressive	Progressive
Matrix size	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx
Resolution	1920 x 1080 - 1080p	1920 x 1080 - 1080p	1920 x 1080 - 1080p	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm	2.8 mm	2.8 mm	4.0 mm
S/N ratio	≥ 58 dB	≥ 50 dB	≥ 58 dB	...	...
View angle	93 °	93 °	• 95 ° (manufacturer data) • 87 ° (our tests result)	• 104 °	• 77 ° (manufacturer data) • 74 ° (our tests result)
Image compression method	H.265 / H.264	H.265 / H.264	H.264	...	...
Compression	...	...	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	15 m	10 m	10 m	10 m	10 m
Alarm inputs / outputs	—	—	—	—	—
Audio	—	—	—	—	—
Memory card slot	—	—	—	—	—
Main stream frame rate	...	...	20 fps @ 1080p	25 fps @ 1080p	25 fps @ 1080p
Network interface	10/100 Base-T - M12, 6-pin socket - Code A	10/100 Base-T - M12, 6-pin socket - Code A	10/100 Base-T - M12, 6-pin socket - Code A	10/100 Base-TX The connection cable has been terminated with the M12 connector	10/100 Base-TX, M12, 4-pin socket - code D
Default user password	admin / -	admin / -	admin / -	...	...
Network protocols	...	...	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, Bonjour	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, Bonjour
WEB Server	...	...	...	Built-in	Built-in
Max. number of on-line users	...	...	...	20	20
ONVIF	✓	✓	✓	✓	✓
Mobile phones support	—	—	—	Port no.: 8000 or access by a cloud (P2P) • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	...	...	...	admin / -	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.26	192.168.1.33	192.168.1.3	192.168.1.64	192.168.1.64
Web browser access ports	8899	8899	8899	80	80
PC client access ports	8899	8899	8899	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	...	...	8000	8000
Port ONVIF	...	...	...	80	80
RTSP URL	...	...	...	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
RS-485 interface	—	—	—	—	—
Main features	• Motion Detection • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation • WDR - Wide Dynamic Range	• Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation • WDR - Wide Dynamic Range	• Motion Detection • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • HLC - High Light Compensation (spot) • BLC - Back Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Lens focus loss detection • The device has a built-in heater • Intelligent image analysis : Motion Detection, intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, abandoned/missing object, scene changing, face detection	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • HLC - High Light Compensation (spot) • BLC - Back Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Configurable Privacy Zones • Lens focus loss detection • The device has a built-in heater • Intelligent image analysis : Motion Detection, intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, abandoned/missing object, scene changing, face detection
Power supply	12 V DC	12 V DC	12 V DC / 600 mA	PoE (802.3af)	PoE (802.3af)
Power consumption	...	...	≤ 5 W	≤ 8.8 W	≤ 8.8 W
Housing	Mini, Metal	Dome, Metal	Dome, Metal	Compact, Aluminum	Compact, Aluminum
Color	Black	Black	White	Black	Black
Vandal-proof	...	...	...	IK10	IK10
"Index of Protection"	IP67	IP67	IP65	IP68	IP68
Operation temp	-30 °C ... 70 °C	-30 °C ... 70 °C	-20 °C ... 60 °C	-40 °C ... 70 °C	-40 °C ... 70 °C
Supported languages	English	English	English	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Weight	0.32 kg	0.24 kg	0.29 kg	0.88 kg	0.88 kg

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	86 x 68 x 68 mm	97 x 84 x 70 mm	99 x 97 x 57 mm	164 x 123 x 65 mm	164 x 123 x 65 mm
Manufacturer / Brand	AUTONE	AUTONE	AUTONE	Hikvision	Hikvision
SAP Code	...	...	...	311311921	316400111
Guarantee	2 years	2 years	2 years	3 years	3 years