

	SWITCH SPU-21-02 DiSEqC 2.0 AXING	SWITCH SPU-41-02 DiSEqC 2.0 AXING	SWITCH SW-2/1-DSQ-SIG DiSEqC 2.0 SIGNAL
			
	8.75 EUR 8.75 EUR	12.03 EUR 12.03 EUR	3.69 EUR 3.69 EUR
SAT frequency range	950 MHz ... 2200 MHz	950 MHz ... 2200 MHz	950 MHz ... 2150 MHz
Attenuation	4 dB	4 dB	2 dB
Isolation between inputs	≥ 20 dB	≥ 30 dB	25 dB
Passing voltage	✓	✓	12 ... 20 V DC
DiSEqC	2.0	2.0	2.0
Number of inputs	2 pcs	4 pcs	2 pcs
Number of outputs	1 pcs	1 pcs	1 pcs
Connectors type	F type connectors	F type connectors	F type connectors
Operation temp	-20 °C ... 50 °C	-20 °C ... 50 °C	...
Main features	...	...	• load 500 mA • High separation of inputs and outputs • Grounding connector • Housing - Plastic (ABS) • Easy and universal mounting system • Cable ties - 2 pcs included
Weight	0.096 kg	0.15 kg	0.06 kg
Dimensions	118 x 68 x 28 mm	118 x 108 x 28 mm	80 x 79 x 30 mm
Manufacturer / Brand	AXING	AXING	SIGNAL
Guarantee	2 years	2 years	2 years