	VIDEO DOORPHONE VTO2111D-P-S2 DAHUA	VIDEO DOORPHONE VTO2202F-P-S2 DAHUA	WIRELESS VIDEO DOORPHONE VTO2211G-P-IP DAHUA	WIRELESS VIDEO DOORPHONE VTO2211G-WP-W-Fi / IP DAHUA	VIDEO DOORPHONE VTO2311R-WP-W-Fi / IP DAHUA	VIDEO DOORPHONE VTO2311D-P2-S2 DAHUA	VIDEO DOORPHONE VTO2311D-P6-S2 DAHUA	WIRELESS VIDEO DOORPHONE VTO3311G-WP-W-Fi / IP DAHUA	VIDEO DOORPHONE VTO3311D-P DAHUA	KEYBOARD MODULE VTO4202F-MB1 FOR MODULE VTO4202F-P DAHUA	KEYBOARD MODULE VTO4202F-MR2 FOR MODULE VTO4202F-P DAHUA	KEYBOARD MODULE VTO4202F-MR5 FOR MODULE VTO4202F-P DAHUA	KEYBOARD MODULE VTO4202F-MK FOR MODULE VTO4202F-P DAHUA	INDICATOR MODULE VTO4202F-ML DAHUA	BLANK MODULE VTO4202F-MN DAHUA	PROXIMITY READER MODULE VTO4202F-MR FOR MODULE VTO4202F-P DAHUA	PROXIMITY READER MODULE VTO4202F-MR1 FOR MODULE VTO4202F-P DAHUA	DISPLAY MODULE VTO4202F-MS FOR MODULE VTO4202F-P DAHUA	VIDEO DOORPHONE VTO4202F-P-S2 DAHUA	KEYBOARD MODULE VTO4202FB-MB1 FOR MODULE VTO4202FB-P DAHUA	KEYBOARD MODULE VTO4202FB-MR2 FOR MODULE VTO4202FB-P DAHUA	KEYBOARD MODULE VTO4202FB-MR5 FOR MODULE VTO4202FB-P DAHUA	INDICATOR MODULE VTO4202FB-ML DAHUA	BLANK MODULE VTO4202FB-MN DAHUA	VIDEO DOORPHONE VTO4202FB-P-S2 DAHUA	VIDEO DOORPHONE VTO6221E-P DAHUA	VIDEO DOORPHONE VTO6521K DAHUA	VIDEO DOORPHONE VTO6541H DAHUA	FINGERPRINT READER MODULE VTO4202F-MF FOR MODULE VTO4202F-P DAHUA	VIDEO DOORPHONE VTO2101E-P-S2 DAHUA	KEYBOARD MODULE VTO4202FB-MK FOR MODULE VTO4202FB-P-S2 DAHUA	PROXIMITY READER MODULE VTO4202FB-MR1 FOR MODULE VTO4202FB-P-S2 DAHUA	PROXIMITY READER MODULE VTO4202FB-MR1 FOR MODULE VTO4202FB-P-S2 DAHUA
	201.23 EUR 201.23 EUR	276.28 EUR 276.28 EUR	239.71 EUR 239.71 EUR	252.62 EUR 252.62 EUR	126.67 EUR 126.67 EUR	296.35 EUR 296.35 EUR	358.73 EUR 358.73 EUR	325.03 EUR 325.03 EUR	189.80 EUR 189.80 EUR	49.71 EUR 49.71 EUR	60.47 EUR 60.47 EUR	76.48 EUR 76.48 EUR	129.06 EUR 129.06 EUR	41.59 EUR 41.59 EUR	26.05 EUR 26.05 EUR	48.28 EUR 48.28 EUR	48.28 EUR 48.28 EUR	61.42 EUR 61.42 EUR	293.49 EUR 293.49 EUR	49.71 EUR 49.71 EUR	60.47 EUR 60.47 EUR	76.48 EUR 76.48 EUR	41.59 EUR 41.59 EUR	26.05 EUR 26.05 EUR	356.10 EUR 356.10 EUR	581.00 EUR 581.00 EUR	749.96 EUR 749.96 EUR	1195.93 EUR 1195.93 EUR	161.80 EUR 161.80 EUR	329.10 EUR 329.10 EUR	129.06 EUR 129.06 EUR	48.28 EUR 48.28 EUR	48.28 EUR 48.28 EUR
Shield																		5 * STN																	
Cards support																13.56 MHz S50	Unique EM 125kHz																	13.56 MHz S50	Unique EM 125kHz
Reading distance of proximity																max. 8 cm	max. 8 cm																	max. 8 cm	max. 8 cm
Sensor	1/4 ", 1 Mpx CMOS	2 Mpx CMOS	2.1 Mpx	2.1 Mpx	1/2.8 ", 2 Mpx CMOS	1/2.8 ", 2 Mpx CMOS	1/2.8 ", 2 Mpx CMOS	1/2.8 ", 2 Mpx CMOS	1/2.8 ", 2 Mpx CMOS										2 Mpx CMOS						2 Mpx CMOS	1/2.9 ", 2 Mpx CMOS	1/2.8 ", 2.0 Mpx CMOS	1/2.7 ", 2 Mpx CMOS			1/2.8 ", 2.1 Mpx CMOS			
Number of supported proximity cards																10000	10000																10000	10000
Autonomous operation																—	—																—	—
Keyboard built-in																—	—																—	—
Doorbell button																—	—																—	—
Tamper output																—	—																—	—
Compatibility	DAHUA	DAHUA			DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	VTO4202F-P	VTO4202F-P	VTO4202F-P	VTO4202F-P			VTO4202F-P	VTO4202F-P	VTO4202F-P	DAHUA	VTO4202FB-P	VTO4202FB-P	VTO4202FB-P			DAHUA	DAHUA	DAHUA	DAHUA	VTO4202F-P	DAHUA	VTO4202FB-x	VTO4202FB-x	VTO4202FB-x
Camera view angle			125 °	125 °																														
Lens		1.95 mm																	1.9 mm						1.9 mm	2 mm		4 mm, F1.6		3.6 mm			
View angle	107 °	168 °			110 °	129 °	129 °	125 °	125 °										160 °						160 °	138 °		87 °		80 °			
RS-485		✓							✓										✓						✓	✓							
Display																										2.3 " OLED	4.3 " LCD, 800 x 480 px	4.3 " IPS - 800 x 480 px					
Permissible relative humidity																													10 ... 90 % (non-condensing)				
Resolution	• Main stream : 800 x 480, 1280 x 720, 720 x 576 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240		Main stream : 720p - 1280 x 720 ; Sub stream : 1080p - 1920 x 1080	Main stream : 720p - 1280 x 720 ; Sub stream : 1080p - 1920 x 1080	• Main stream :1280 x 720, 800 x 480, 720 x 576, 352 x 288 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288	• Main stream : 800 x 480, 1280 x 720, 720 x 576 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240	• Main stream : 800 x 480, 1280 x 720, 720 x 576 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240	• Main stream :1280 x 720, 800 x 480, 720 x 576, 352 x 288 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240																					Main stream : 720p - 1280 x 720 ; Sub stream : 1080p - 1920 x 1080					
LED illuminator		—	—	—				—	—										—						—	✓	✓	✓		—			
IR illuminator	✓	✓	✓	✓	✓	✓	✓	✓	✓										✓						✓	—	—	✓		✓			
PIR detector			—	—				—																									
proximity reader built-in	Access control cards - 13.56 MHz S50	—	Access control cards - 13.56 MHz S50	Access control cards - 13.56 MHz S50	Access control cards - 13.56 MHz S50 • Ethernet 10 / 100 Mbps • Wi-Fi • Wi-Fi	Access control cards - 13.56 MHz S50	Access control cards - 13.56 MHz S50	Access control cards - 13.56 MHz S50 • Ethernet 10 / 100 Mbps • Wi-Fi	Access control cards - 13.56 MHz S50, Memory of 3000 RFID cards										—						—	13.56 MHz S50	13.56 MHz S50						
Wireless transmission range				The range limited only by the availability of the Wi-Fi network	The range limited only by the availability of the Wi-Fi network			The range limited only by the availability of the Wi-Fi network																									
Video output			—	—																													
Image compression method	H.264	H.265	H.264	H.264	H.264 / H.265	H.264	H.264	H.265 / H.264	H.265 / H.264										H.265						H.265	H.264	H.264	H.264		H.265 / H.264			
The number of subscribers served	1		1	1	1	2	4	4																									
Wi-Fi standard				IEEE 802.11b / IEEE 802.11g / IEEE 802.11n	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n			IEEE 802.11b / IEEE 802.11g / IEEE 802.11n																									
Supported audio formats			G.711, PCM	G.711, PCM																													
Alarm inputs			1 pcs																														
Network interface			Ethernet 10 / 100 Mbps	• Ethernet 10 / 100 Mbps • Wi-Fi	• Ethernet 10 / 100 Mbps • Wi-Fi			• Ethernet 10 / 100 Mbps • Wi-Fi																									
RS-485 interface			✓	✓				✓																									
Vandal-proof										IK07	IK07	IK07	IK07			IK07	IK07	IK07		IK07	IK07	IK07					IK08		IK07		IK07	IK07	IK07
Mount			Surface-mounted	Surface-mounted																													
IK rating		IK07							IK08					IK07	IK07				IK07				IK07	IK07	IK07	IK08							
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS										Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS					Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS				Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS			

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	• It can only work with the mobile application, without the VTH monitor • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Multicast • WDR - Wide Dynamic Range • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - opening the enclosure, • Door contact and request button for exit inputs	• SD memory cards up to 32GB support (possible local recording), • Call button button, • LED diodes, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface, • Power output 12 V DC / 100 mA	• It can only work with the mobile application, without the VTH monitor, • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Multicast • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection, • Tamper signaling, • Door contact and request button for exit inputs, • The microSD - max. 128 GB cards support, • Full support via network : WiFi / LAN, • Video Doorphone is mounted in a surface housing	• It can only work with the mobile application, without the VTH monitor, • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Motion Detection, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection, • Tamper signaling, • Door contact and request button for exit inputs, • The microSD - max. 128 GB cards support, • Full support via network : WiFi / LAN, • Video Doorphone is mounted in a surface housing	• It can only work with the mobile application, without the VTH monitor, • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Micro SD memory cards up to 256GB support (possible local recording), • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and reduction / digital noise reduction, • Tamper detection - opening the enclosure, • Vandal-proof front panel, • Output for the additional lock release button, • WDR - 120 dB - Wide Dynamic Range, • Motion Detection	• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and reduction / digital noise reduction, • Tamper detection - opening the enclosure, • Vandal-proof front panel, • Output for the additional lock release button, • WDR - 120 dB - Wide Dynamic Range, • Motion Detection	• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and reduction / digital noise reduction, • Tamper detection - opening the enclosure, • Vandal-proof front panel, • Output for the additional lock release button, • WDR - 120 dB - Wide Dynamic Range, • Motion Detection	• Micro SD memory cards up to 256GB support (possible local recording), • Unlocking by card, application or indoor monitor, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 2D-DNR, 3D-DNR - Digital Noise Reduction, • DayNight mode (color/b&w/auto), • ICR - Movable InfraRed filter, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Vandal-proof front panel, • LED diodes, • Alarm inputs / outputs : 1 / 1, • Output for the additional lock release button, • Rain cover included	• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel, • Micro SD memory cards up to 256GB support (possible local recording), • Support up to 4 subscriber numbers, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 2D-DNR, 3D-DNR - Digital Noise Reduction, • DayNight mode (color/b&w/auto), • ICR - Movable InfraRed filter, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Vandal-proof front panel, • LED diodes, • Alarm inputs / outputs : 1 / 1, • Output for the additional lock release button, • Rain cover included	Doorbell button - 1 pcs	Doorbell button - 2 pcs	Doorbell button - 5 pcs	• Large, readable buttons • White backlight	...	...	• Bidirectional communication, • Microphone built-in, • Speakers built-in • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction, • Power output : 12 V DC / 100 mA, • Tamper detection - removing from mounting surface ,	Doorbell button - 1 pcs	Doorbell button - 2 pcs	Doorbell button - 5 pcs	...	• Bidirectional communication, • Microphone built-in, • Speakers built-in • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction, • Power output : 12 V DC / 100 mA, • Tamper detection - removing from mounting surface ,	• The device can be used both in 1-storey and multi-family installations, • Keyboard built-in, • Call button, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface, • Wiegand interface	• Camera view angle : 86 °, • LCD display, • Bidirectional communication, • WDR - 120 dB - Wide Dynamic Range, • Door can be open the gate using a QR code, • Memory of 10 000 RFID cards, 20 000 indexed users, • Power output : 12 V DC / 200 mA, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Daylight mode • ICR - Movable InfraRed filter • Motion Detection • Taking pictures • Records a short video message if there is no response to the doorbell button • 20 000 indexed users • proximity reader built-in : 13.56 MHz S50 - Memory of 10 000 RFID cards • Fingerprint reader built-in - Memory of 10000 fingerprint patterns, • Face recognition - Memory of 10000 face templates, • Keyboard built-in - Touch control keys, • Cooperation with the SIP server • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper signaling, • Alarm inputs / outputs : 2 / 2, • Relay output - NO / NC, • Door contact and request button for exit inputs, • RS-485, • Wiegand • Opening the door : PIN / RFID card / Fingerprint / face detection / Remote client • View information : How many VTH monitors and VTO door stations can be connected to the Dahua intercom installation?	Support up to 3000 finger prints	• It can only work with the mobile application, without the VTH monitor • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH / VTO2 / VTH5 indoor panel • Call button, • Lock control, • Bidirectional communication, • Microphone built-in, • Speaker built-in, • Noise and echo reduction • Tamper detection - removing from mounting surface, • RS-485 interface • Alarm inputs : 1 pcs • Video PUSH personal messaging • Voice message • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • DayNight mode (color/b&w/auto) • ICR - Movable InfraRed filter	• Large, readable buttons • White backlight	...	...
Housing	Plastic, Waterproof	Aluminum	Plastic	Plastic	Aluminum alloy, Waterproof	Aluminum alloy, Waterproof	Aluminum alloy, Waterproof	Aluminum alloy, Waterproof	Aluminum	aluminum	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof	Metal + Plastic	Metal + Plastic	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof	Aluminum	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof	Metal + Plastic	Metal + Plastic	Aluminum	Aluminum	Metal	Plastic (PC + ABS)	Metal + Plastic, Waterproof	Metal - Zinc alloy, Waterproof - IK10	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof	Metal + Plastic, Waterproof
Color	Graphite	Silver	Black + Gray	Black + Gray	Graphite	Graphite	Graphite	Graphite	Graphite	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Silver	Graphite	Graphite	Graphite	Graphite	Graphite	Graphite	Silver	Silver	Silver	Black + Silver	Silver	Graphite	Graphite	Graphite
Power supply	• PoE (802.3af), • 12 V DC / 1000 mA	• PoE (802.3af), • 2-Wire IP interface	• PoE (802.3af) • 12 V DC / 500 mA (max)	• PoE (802.3af) • 12 V DC / 500 mA (max)	• PoE (802.3af), • 12 V DC / 500 mA	• PoE (802.3af), • 12 V DC / 1 A	• PoE (802.3af), • 12 V DC / 1 A	• PoE (802.3af), • 12 V DC / 1 A	• 48 V / 1 A, • PoE (802.3af), • 2-Wire IP interface	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules		5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	• PoE (802.3af), • 2-Wire IP interface	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules	• PoE (802.3af), • 2-Wire IP interface	• PoE (802.3af), • 12 V DC / 500 mA	12 V DC / 2 A	12 V DC / 2 A	5 V DC - Supplied from other modules	• PoE (802.3af), • 2-Wire IP interface	5 V DC - Supplied from other modules	5 V DC - Supplied from other modules
"Index of Protection"	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65	IP65	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65	IP65	IP65	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
Power consumption	≤ 5 W	≤ 12 W	≤ 1 W (standby), ≤ 7 W (operation)	≤ 7 W (operation)	≤ 6 W (operation) ≤ 3.5 W (Standby mode)	≤ 7 W (operation) ≤ 1 W (Standby mode)	≤ 7 W (operation) ≤ 1 W (Standby mode)	≤ 6 W (operation) ≤ 3 W (Standby mode)	≤ 4 W (Standby mode) ≤ 8 W (operation)	≤ 1 W	≤ 1 W	≤ 1 W	≤ 1 W	≤ 1 W	≤ 1 W		≤ 1 W	≤ 1 W	≤ 1 W	≤ 12 W	≤ 1 W	≤ 1 W	≤ 1 W	...	...	≤ 12 W	≤ 6 W	≤ 18 W (operation) ≤ 5 W (Standby mode)	≤ 18 W	< 1 W	≤ 5 W (operation) ≤ 2.5 W (Standby mode)	≤ 1 W	≤ 1 W	≤ 1 W
Mechanical strength	...	...	...	...	...	...	...	IK08	IK08	...	...	...	...	...	...		...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C	-30 °C ... 60 °C	-30 °C ... 60 °C	-40 °C ... 60 °C	-30 °C ... 60 °C	-30 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C		-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-30 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C			-30 °C ... 60 °C	40 °C ... 60 °C	-30 °C ... 60 °C	-30 °C ... 60 °C	-20 °C ... 60 °C	-30 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C
Weight	0.16 kg	0.33 kg	0.35 kg	0.37 kg	0.24 kg	0.48 kg	0.48 kg	0.6 kg	0.6 kg	0.11 kg	0.1 kg	0.19 kg	0.2 kg	0.12 kg	0.11 kg		0.09 kg	0.1 kg	0.22 kg	0.28 kg	0.1 kg	0.1 kg	0.19 kg	0.12 kg	0.11 kg	0.31 kg	0.46 kg	1.51 kg	0.91 kg	0.23 kg	0.67 kg	0.2 kg	0.09 kg	0.09 kg
Dimensions	135 x 71 x 35 mm	130 x 96 x 28.5 mm	100 x 150 x 25 mm	100 x 150 x 28 mm	170 x 57 x 35 mm	182 x 101 x 32 mm	182 x 101 x 32 mm	≈ 188 x 107 x 30 mm (without cover) ≈ 191 x 112 x 44 mm (with cover)	≈ 188 x 107 x 30 mm (without cover) ≈ 191 x 112 x 44 mm (with cover)	100 x 49.9 x 30.5 mm	100 x 49.9 x 30.5 mm	100 x 100 x 31 mm	100 x 100 x 31 mm	100 x 50 x 29 mm	100 x 50 x 29 mm		100 x 49.9 x 28.5 mm	100 x 49.9 x 28.5 mm	100 x 100 x 28.5 mm	100 x 100 x 49.3 mm	100 x 49.9 x 30.5 mm	100 x 49.9 x 30.5 mm	100 x 100 x 30.5 mm	100 x 50 x 29 mm	100 x 50 x 29 mm	100 x 100 x 49.3 mm	200 x 98 x 34.7 mm	406 x 143 x 52 mm	389 x 146 x 45 mm	100 x 100 x 38.5 mm	73 x 163 x 55 mm	100 x 100 x 31 mm	100 x 49.9 x 28.5 mm	100 x 49.9 x 28.5 mm
Supported languages	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian	Polish, English	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian	Polish, English	Polish, English	...	...	...	...	...	...	...	...	...	...	Polish, English	...	...	...	...	Polish, English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian	English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian	Slovak, Hungarian	...	...	English	...	...	...
Manufacturer / Brand	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA		DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years		3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00